

ATM Mini-DSLAM

Total Access 1210 ATM Mini-DSLAM

Product Features Cost-effective DSLAM for

- CO, CEV, RT, and customer premises applications

 24 ports of ADSL plus
- baseband POTS

 DMT.G.lite. and T1.413
- modulations

 Front panel access to all connections
- Two field replaceable GMT type 3 amp fuses
- POTS service is not power dependent
- Provisioning and alarm monitoring via SNMP/ASCII text and TL1 through the local craft interface and ATM in-band management channel
- Inverse Multiplexing over ATM (IMA) for up to four E1 IMA links
- Interoperable with any E1 IMA device that is built to current IMA specifications which includes the Total Access 3000 IMA Aggregation System

Carriers want to deploy DSLAM solutions that can leverage their existing telecommunications resources. They are looking for solutions that control cost, promote efficiency, and simplify operations. The ADTRAN Total Access 1210 is a temperaturebardened DSLAM that enables delivery of 24 ports of POTS and ADSL from smaller Central Offices (COs), Controlled Environmental Vaults (CEVs), Multiple Dwelling Units (MDUs), and Remote Terminals (RTs). The ADSL is generated locally and placed, via onboard splitters, on the same pair as the corresponding POTS signal for delivery to the customer. The DSLAM performs Inverse Multiplexing over ATM (IMA) for up to four E1 IMA links.

ADTRAN has engineered a compact, IU high until that provides RT space savings while offering multiple options for placement within the RT. Design flexibility leverages existing facilities and enables the Total Access 1210 to be mounted as a rack, wall, or vertical positioned until trissled the RT. Transacrase 4.45 cm H x 48.42 cm W x 28.26 cm D and offers redundant power uning—42 to ~64 VDC.

The Total Access 1210 offers a scalable network interface today with the Quad IMA module. Future capabilities include Octal IMA, DS3, and STM-1. These modules assure easy deployment and dynamic network utilization, as subscriber needs dictate. Using multiple shelves for a single network feed can scale the unit into a system-wide RT solution with up to 96 ports. It supports an ADSL service range of 18,000 feet.

Developed with ADTRANY concern for currier field needs, the Total Access 120 h carrier field needs, the Total Access 120 h pre-Installed fam modules complete with fan fillers. Each fam modules and fint filter and penderthy field epilaceable. The fam are controlled by hear sensing circuits and will run only when precessary. Front pariet access is available for all connections. The intertop the intercoperable with any ELIMA device that is built to current MA specifications, which includes the Total Access 2000 IMA.

Management is made simple and convenient through a choice of SNMP. ASCII, T.I., or IDBase-T Ethernet support, Provisioning, alarms, and performance monitoring are provided through the local craft interface and ATM in-band management channel.

ADTRAN's Total Access 1210 Mini-DSLAM brings a cost-effective and efficient IMA, ADSL, and POTS solution to carriers providing subscriber services at rural CO, MDU, CEV, and RT sites.







ADTRAN, Inc. Attention: International Department

International Department 901 Explorer Boulovard Huntsville, Alabama 35996

WWW.sdtrsn.com

+1 256 963 8000 voice +1 256 963 6300 fax international/Badtran com

Customer Service

Asia Pacific— Beijing, China +86 10 8857 6415 voice +86 10 8857 6417 fzx

sales, chino@advan.com Asia Pacific (Other than China and Australia)— Hong Kong, China

+852 2004 8283 voice +852 2824 8928 fax seies asio@actran.com Asia Pacific— Guaegrhou, China

+85 20 8384 9015 voice +85 20 8384 7127 fax sales, china@advan.com Asia Pacific—

Melbourne, Australia +61 3 9658 0500 voice +61 3 9658 0593 fax

saies australibiliadran com Europe/Middle East/Africa— Bad Homburg, Germany

+49 6172 463 2304 voice +49 6172 483 2305 fox sales.curope@adtran.com

Europe/Middle East/Africa— Dublin, Ireland +353 1 569 4790 voice +353 1 969 4791 fox sales ourope/flud/ray com

Latin America/Caribboan +1 854 474 4424 voice +1 854 474 1288 fax sales latin@udran.com

+1 954 474 4924 voice +1 954 474 1298 fax sales mexicolibatican com

AGTEAN is a 600 9000 9000 registered company

ALTTAN is a
TI, 5000 registered company.
184179611L1-8A Soptember 2800
Copyright to 2000 ALTERAL Inc.

ATM Mini-DSLAM



24 ADSL+POTS

Total Access 1210 ATM Mini-DSLAM

1 to 4 Ets Total Access 1210 Mini-DSLAM

IMA Interface
24 POTS

Product Specifications

Front Panel Features

Five LEBs: Power, ADSL, Network, Alarm, T1/E1

Two 59-pin amphenol interfaces: PDTS.

ADSL+PDTS

BB-9 craft interface

■ DB-15 Alarm Interface, input/output ■ Four RJ-45 uplink trunks

Mechanical

■ Dimensions: 4.45 cm H x 43.82 cm W x 28.26 cm D

(1.75 in. H x 17.25 in. W x 11.13 in. D)

Weight 3.63 kg (8 lb)
 Mounting: Rackmount or wallmount
 Can be mounted in either a flush mount or mid-mount

orientation in either a 19-inch or 23-inch rack Interfaces Network

■ Quad IMA ■ Dotal IMA – future ■ DS3 – future

■ DS3 – future ■ STM-1 – future ■ PDTS

Subscriber

ADSL+PDTS

Modulation Supported

■ DMT ■ 6.Uite ■ T1.413

Electrical ■ -42 VDC to -56 VDC

Regulatory Standards

■ NEBS Level 3 ■ CE Mark

■ IEC 60950 ■ EN 60950 ■ EN 300 396-2

Management

Lecal: ASCII – monu

■ Remote: SNMP, TL1, 10Base-T Ethernet Environmental ■ Operating: ~40°C to +70°C

Storage: -40°C to +85°C
Relative humidity: 95 percent, noncondensing

| Conference | Con

Specifications subject to change without notice, ADTRAN is a trademark of ADTRAN, loc, and/or its affiliates in the U.S. and certain other countries. Total Access is a registered trademark of ADTRAN, Inc., in the U.S. All other trade makes medicined in this document are the property of their respective series.