



NETWORK CONNECTION PINOUT

Pin	Name	Description
1	R1 RXDATA	Receive data from the Network - Ring
2	T1 RXDATA	Receive data from the Network - Tip
3, 6, 7, 8	UNUSED	n/a
4	R TXDATA	Transmit data towards the Network - Ring
5	T TXDATA	Transmit data towards the Network - Tip

REAR PANEL DESCRIPTIONS

Network Connector	Connection to T1 circuit
V35 Connector	High-speed DTE interface
Power Switch	Turns power to the TSU on or off
115 VAC Connection	Power cord connection for a reliably grounded 115 VAC, 60 Hz power source

INSTALLATION INFORMATION

- An eight-position modular jack (labeled **Network**) is provided to connect to the network T1 circuit. The pinout is provided on this Quick Start Guide. See Chapter 2, installation, of the TSU ACE User Manual for more information.
- The rear panel contains a single V35 interface for connecting to DTE equipment. The pinout for this interface is located in Appendix C of the TSU ACE User Manual.
- When shipped from the factory, the TSU ACE is uninitialized and set to factory default conditions. At the first application of power, the unit will automatically execute self-tests followed by an initialization sequence.
- The TSU ACE can be configured and controlled using the local front panel of the unit or from ADTRAN's PC Control Program, T-WATCH. A limited menu tree is provided on the back of this sheet. For more detailed menu information, refer to the TSU User Manual.
- Additional information can be found on the product CD which contains the TSU ACE User Manual, FAQs, Data Sheets, Applications, and White Papers.

MENU TREE - OVERVIEW
