

NetVanta 344

Business-class ADSL/ADSL2/ADSL2+ Router with Four-port Switch

Product Features

- Affordable routing solutions for businessclass ADSL networks
- Integral 4-port managed Ethernet switch
- Innovative ADSL2+ technology provides further reach and higher bandwidth (up to 25 Mbps)
- Standards-based routing/ switching protocols, based on the widely deployed NetVanta Series
- Feature-rich ADTRAN Operating System (AOS)
- Stateful inspection firewall for network security
- Optional VPN for secure corporate connectivity across the Internet
- Recognizable Command Line Interface (CLI) eliminates re-training
- User-friendly web Graphical User Interface (GUI)
- NAT-compatible SIP ALG for VoIP
- Interoperable with other NetVanta product offerings and carrier-based ADSL service offerings
- Industry-leading support, service, and warranty

The NetVanta 344 is a business-class ADSL/ ADSL2/ADSL2+ IP access router with an integral four-port Ethernet switch. It provides a single ADSL network interface and four auto-sensing 10/100Base-T Ethernet interfaces. This product is ideal for carrier bundled service offerings and enterprise Internet access for secure, high-speed corporate connectivity. In addition to supporting ADSL (Annex A and B), and ADSL2, the NetVanta 344 supports today's most advanced ADSL technology, ADSL2+, for applications taking advantage of its greater reach and higher bandwidth, up to 25 Mbps. A variety of WAN protocols are supported including PPP over ATM and PPPoE over ATM.

Standards Protocols

The versatile hardware platform of the NetVanta 344 is further complemented with the ADTRAN Operating System (AOS). The AOS allows for the support of standards-based switching, VLAN tagging, static and default routes, demand routing, and allows for fast, accurate network convergence using routing protocols such as BGP, OSPF, and RIP.

Security

The AOS provides a powerful, high performance stateful inspection firewall. It will examine all incoming and outgoing packets against the security policies established by the IT manager. In addition, the firewall can identify and protect against common Denial of Service (DoS) attacks like TCP syn flooding, IP spoofing, ICMP redirect, ping-of-death, and IP reassembly problems.

With the AOS Enhanced Feature Pack Upgrade, the NetVanta 344 supports up to five simultaneous IPSec VPN tunnels, and encryption algorithms like DES, 3DES, and AES. With this upgrade, the NetVanta 344 is fully compatible with other IPSec VPN equipped NetVanta products.

Quality of Service (QoS)

QoS is also supported for delay sensitive traffic like VoIP or video. To prioritize mission critical traffic and control network congestion, the NetVanta 344 uses Low Latency Queuing, Weighted Fair Queuing (WFQ), Class-based WFQ, and DiffServ marking to establish priority of IP packets routed over the WAN.

VoIP Ready

In combination with the QoS features, a specialized SIP Application Layer Gateway (ALG) allows SIP traffic to traverse NAT-enabled firewalls. For an enterprise network, this interoperability allows IP PBXs, phones, and other SIP-based devices to set up, tear down, and pass voice and call control messages seamlessly through the integral NAT-enabled firewall.

Administration

The AOS offers a standard Command Line Interface (CLI) that mimics the widely adopted, industry de facto standard. The sequence of commands to configure similar devices is almost identical, virtually eliminating training costs associated with re-learning a new operating system or costly industry certifications. The CLI also allows for configuration scripts to be used, saved, and downloaded for a quick and easy recovery mechanism. In addition, an intuitive Web-based GUI provides step-by-step configuration wizards, management capability, and the ability to upload firmware updates.

ADTRAN, the leader in WAN connectivity, offers proven and dependable equipment that will increase your network performance, lower costs, and allow migration to next generation technologies. The NetVanta 344 is no exception.





ADTRAN Inc.

International Department 901 Explorer Boulevard Huntsville, Alabama 35806 USA

www.adtran.com/global

U.S. Headquarters

+1 256 963 8000

+1 256 963 6300 fax international@adtran.com

International Customer Service

+1 256 963 8716 voice

Asia—Beijing, China

+86 10 8527 5011 +86 10 8527 5010 fax sales.china@adtran.com

Hong Kong

+852 3187 7111 +852 2116 4084 fax

sales.asia@adtran.com

Asia—Bangkok, Thailand

+66 2 625 3085 +66 2 625 3142 fax

sales.asia@adtran.com

Asia—Singapore

+65 6248 4665

+65 6320 8521 fax sales.asia@adtran.com

Australia/New Zealand— Melbourne, Australia

+61 3 9658 0501

+61 3 9658 0599 fax sales.australia@adtran.com

Australia/New Zealand—

Sydney, Australia

+61 2 9959 2485 +61 2 9959 2244 fax

sales.australia@adtran.com

Canada—Montreal, Quebec

+1 877 923 8726

+1 514 989 3198 fax sales.canada@adtran.com

Canada—Toronto, Ontario

+1 514 940 2888

+1 514 989 3198 fax

sales.canada@adtran.com

EMEA Regional Headquarters— **United Kingdom**

+44 1256 884055

+44 1256 884056 fax

sales.emea@adtran.com

sales.europe@adtran.com Mexico/Central America/

Caribbean—USA

+1 256 963 3113

+1 256 963 6300 fax

sales.latin@adtran.com sales.caribbean@adtran.com

sales.mexico@adtran.com

sales.ai@adtran.com

South America—USA

+1 954 474 4424

+1 954 474 1298 fax

sales.latin@adtran.com

sales.brazil@adtran.com sales ai@adtran com



ADTRAN is an ISO 9001, ISO 14001, and a TL 9000 certified supplier.

I-61200426L1-8F AOS 16.1 August 2007 Copyright© 2007 ADTRAN, Inc. All rights reserved

NetVanta 344

Business-class ADSL/ADSL2/ADSL2+ Router with 4-port Switch

Physical Interface

■ DSL: ADSL/ADSL2/ADSL2+ Interface

ADSL ITU G.992.1 (Annex A)

ADSL ITU G.992.1 (Annex B)

ADSL ITU G.992.2 (Annex A) G.Lite

Extended Reach ADSL (RADSL)

ADSL2 ITU G.992.3 (Annex A)

ADSL2+ ITU G.992.5 (Annex A)

■ Ethernet: Four-port, Auto-sensing Ethernet Switch 10/100Base-T Full Duplex (RJ-45)

Diagnostics LEDs

- Power
- Ethernet
- DSI
- Internet

Memory

■ RAM: 32 MB

■ FLASH: 16 MB

Protocols

- eBGP/iBGP
- PPP over ATM (RFC 2364)
- OSPF
- PPPoE over ATM (RFC 2516)
- RIP (v1 and v2)
- Classical IP over ATM (RFC 2225)
- Demand Routing AAL5
- GRE
- PAP and CHAP
- IGMP v2

Quality of Service

- DSL: Low Latency, Weighted Fair Queuing (WFQ), and Class-based WFQ
- Ethernet: Weighted Round Robin (WRR) and Strict Priority Queuing
- DiffServ Packet Marking and Recognition
- Frame Relay Fragmentation

Switching

- VLAN Support (802.10)
- Spanning Tree (802.1D)
- Rapid Spanning Tree (802.1w)
- 802.1p and DiffServ QoS

Administration

- Familiar Command Line Interface (CLI)
- Web-based GUI
- n-Command support
- SNMP v3
- SYSLOG Logging
- Email Alerts (SMTP)
- Policy Statistics

DHCP

Client, Server, and Relay

Specifications subject to change without notice. ADTRAN and NetVanta are a registered trademark of ADTRAN, Inc. All other trademarks mentioned in this document are the property of their respective owners. For more information regarding ADTRAN's export license, please visit www.adtran.com/exportlicense

ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Content subject to change without notice. ADTRAN provides an industry-leading warranty with all of its products. For more details, visit www.adtran.com/warranty

An Export License is required if these ADTRAN products are sold to a Government Entity outside of the EU+8 (Austria, Australia, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Ireland, Italy, Japan, Lat-via, Lithuania, Luxembourg, Malta, Netherlands, New Zealand, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, and the United Kingdom). This is per DOC/BIS ruling G030477 issued June 6, 2003.

Security

Firewall

- Stateful Inspection Firewall
- Denial of Service (DoS) Protection
- Access Control Lists
- Application Level Gateways (ALGs)

Network Address Translation

- Basic NAT (1:1), NAPT (Many:1), and Port Translation
- NAT compatible SIP ALG

Secure Management

- Multi-level access control
- RADIUS AAA
- TACACS+
- SSH CLI and SSL GUI

Optional Virtual Private Network (VPN)

- IPSec Tunnel Mode: 5 Tunnels
- Encryption: DES, 3DES, and AES
- Authentication Mechanisms: XAUTH, Digital certificates, Preshared keys, and Secure ID

Environment

- Operating Temperature: 0° to 50 °C (32° to 122 °F)
- Storage Temperature: -20° to 70 °C (-4° to 158 °F)
- Relative Humidity: Up to 95%, non-condensing

Physical

- Chassis: Self-standing, plastic enclosure
- Dimensions: 4.1cm H, 19.0 cm W, 13.3 cm D
- Weight: 1 kg
- Power: 12 VDC, 800 mA, 6 W (AC to DC Power Adapter Included)

- **Agency Approvals** FCC Part 68
 - Industry Canada CS03 ■ CE Mark, UL and Canadian UL (CUL), IEC/EN, CSA

Ordering Information

J	
Equipment	Part #
NetVanta 344 (Annex A)	
NetVanta 344	4200426E1#IN
NetVanta 344 with VPN	4200426E2#IN
NetVanta 344 (Annex B)	
NetVanta 344	1200423E1#IN
NetVanta 344 with VPN	4200423E2#IN

VPN Software Upgrade NetVanta 344 VPN Software Upgrade (Annex A) 1950426L2 NetVanta 344 VPN Software Upgrade (Annex B) 1950423L2

