

# Enterprise Network Compute System (ENCS)

Cisco vBranch Architecture

Per Jensen, [per@cisco.com](mailto:per@cisco.com)

Sept 2017


# Agenda: Tech Update september-2017

1. ENCS update + demo v/Per
2. Viptela update + demo v/Dr Søren

# The Current Enterprise Branch Landscape


## Multiple Devices

Routers, Appliances, Servers



## Difficult to Manage

Device integration and operation



## Costly to Operate

Upgrades, refresh cycles, site visits



Horseman of the branch apocalypse



# What Enterprise NFV Can Do For You


Quickly roll out new services and locations

Gives you flexible deployment options

Simplify day to day operations

Simple and easy  
to design, provision,  
manage the trusted  
services that are critical  
to your business

# What Is Enterprise NFV?



# Introducing Cisco Enterprise NFV

## Network Services in Minutes, on Any Platform



Cisco Enterprise Service Automation (ESA) on APIC-EM  
Network Services Orchestrator (NSO)



**Network Functions Virtualization Infrastructure Software (NFVIS)**





Cisco 4000 Series ISR +  
UCS® E-Series

Enterprise Network Compute  
System  
(ENCS)

Cisco® UCS  
C-Series

# Freedom of Choice

## Cisco Intelligent Branch

Traditional	Enterprise NFV		
<p><b>Physical Router</b></p>  <p>Cisco® 4000 Series ISR</p>	<p><b>Physical Router Virtual Services</b></p>  <p>4000 Series ISR + UCS® E-Series</p> 	<p><b>Virtual Router Virtual Services</b></p>  <p>Enterprise Network Compute System (ENCS)</p> 	<p><b>Virtual Router Virtual Services</b></p>  <p>UCS C-Series</p> 
<p>Centralized services Fixed integrated services Conservative</p>	<p>Upgradable hardware Deterministic routing performance</p>	<p>Elastic routing and services Router / Server Hybrid</p>	<p>Elastic routing and services Performance Early adopter</p>




 Access to Ongoing Innovation
 
 License Portability
 
 Investment Protection

# ENCS 5400 Series



# ENCS 5400 Series - Chassis Options




	<b>ENCS5406</b>	<b>ENCS5408</b>	<b>ENCS5412</b>
CPU	6-core, 1.9GHz	8-core, 2.0GHz	12-core, 1.5GHz
PoE	No	200W	200W
Capacity Guidance	ISRv + 2 VNFs	ISRv + 3 VNFs	ISRv + 5 VNFs


# ENCS 5400 Series - Bezel

## New Industrial Design


First platform with new Cisco design language  
Intended to create a common look across Cisco products



# ENCS 5400 Series




# ENCS 5400 Major Components



\* Roadmap


# Hardware Features

# ENCS 5400 CPU Allocation Planning




- 1 core = 1 vCPU = 1 physical core
- 1-core allocation for NFVIS to cover OS, Hypervisor & vSwitch functions
- 2-core minimum allocation for ISRV
- Multiple VNF profiles target specific performance
- Cisco VNFs will be pinned to respective cores for performance.

# ENCS 5400 RAM Allocation Planning




- Refer to VNF Datasheet for specific guidance. RAM over-subscription is not recommend for production environments.

# ENCS 5400 Storage Summary




# ENCS 5400 Dual-mode GE Ports

- 2 built-in GE ports for WAN or LAN uplink
- RJ45 Copper or SFP connectivity (10/100/1000 Mbps)
- Auto-sensing mode. Usable in a active-standby configuration.




# ENCS 5400 Internal Networking


↔ Data Path  
 ↔ Control Path



# NFVIS Auto-selects Optimum Packet Path




# Cisco Server Management



## Cisco Integrated Management Controller

- Hardware-level out-of-band lights-out management
- CLI, GUI, XML API
- Same experience as UCS E-Series & C-Series
  
- Key functions:
  - HW configuration – e.g. RAID, Boot order, BIOS
  - Monitoring & troubleshooting. Failure alerts.
  - Platform power cycling
  - Virtual console & remote media mount
  - Disaster recovery



# ENCS 5400 CIMC Access Modes

Option 1  
Dedicated GE MGMT Port


Requires a dedicated physical connection to an external LAN switch.

Option 2  
Shared LAN On Motherboard

Uses the WAN GE Ports  
Shares physical connection with other VNFs

Option 3 (Roadmap)  
Through NFVIS MGMT Port

Shares the physical connection with NFVIS



# ENCS 5400 Power Supply

- Single Integrated Power Supply Unit
  - 250W for regular PSU
  - 500W for POE PSU (ENCS5408 & ENCS5412 only)
- Universal POE on built-in LAN ports (Up to 60W)
  - Total limit of 200W
- Field-replaceable unit

# Software NFVIS & VNFs

# Network Services from Cisco

Consistent software across physical and virtual



## ISRV

High Performance  
Rich Features




## ASA/FTD\*

Full DC-class Featured  
Functionality



## vWAAS

Application Optimization  
and Akamai Connect



## vWLC

Built for small and medium  
branches



## Windows Server

Active Directory,  
File Share,  
Server Applications



## Linux

Custom Applications  
DNS/DHCP




## 3<sup>rd</sup> Party

Network Services  
Management & Monitoring

# Product Positioning

ISRv vs CSR



## **Integrated Services Router - Virtual**

- Packaged for NFVIS
- Branch-Specific Features
- Branch-Specific Pricing
- Look-and-feel of an ISR 4000
- Not available separately




## **Cloud Services Router**

- Cloud and VDC Deployments
- Aggregation Use-Cases
- Flexible Pricing & Packaging
- Virtual ASR 1000 Series
- Available on multiple platforms

# Optimized for Network Services

## Enterprise NFV Infrastructure Software (NFVIS)



# Power in Software

## NFVIS Software Stack

