

Product name	Confidentiality level
E3372h-510	CONFIDENTIAL
Product version	Total 8 pages
V1.0	

HUAWEI E3372h TCPU-V200R002B315D01SP00C00

Release Notes V10.0

Prepared by	E3372h Team	Date	2015/11/25
-------------	-------------	------	------------



HUAWEI

Huawei Technologies Co., Ltd.



Revision Record

Date	Revision version	FW-WebUI/HiLink Version	Change Description	Author
2014-9-30	1.0	FW 22.180.03.00.00	First version	Tanzhengbin
2014-10-11	2.0	FW 22.180.05.00.00	Second version	Tanzhengbin
2014-11-11	3.0	FW 22.180.09.00.00	Third version	Tanzhengbin
2014-12-18	4.0	FW 22.200.01.00.00	Fourth version	Tanzhengbin
2014-12-28	5.0	FW 22.200.03.00.00	Fifth version	Tanzhengbin
2015-1-22	6.0	FW 22.200.05.00.00	Sixth version	Tanzhengbin
2015-4-8	7.0	FW 22.200.07.00.00	Seventh version	Huwuming
2015-4-18	8.0	FW 22.200.09.00.00	Eighth version	Huwuming
2015-6-19	9.0	FW 22.200.13.00.00	nineth version	Liuhuan
2015-8-29	10.0	FW 22.200.15.00.00	MR version	Liuhuan
2015-11-15	11.0	FW 22.315.01.00.00	MR version	Liuhuan

Table of Contents

1	Main Features	4
2	Hardware.....	4
2.1	Version Description	4
2.2	Hardware Specifications	4
2.3	Improvements in the Previous Version	5
2.4	Known Limitations and Issues	5
3	Firmware	5
3.1	Version Description	5
3.2	Firmware Specifications	6
3.3	Improvement in the Previous Version	6
3.4	Known Limitations and Issues	6
4	WebUI/HiLink	6
4.1	Version Description	6
4.2	WebUI/HiLink Specifications	6
4.3	Improvement in the Previous Version	6
4.4	Known Limitations and Issues	7
5	Software Vulnerabilities Fixes	7
6	Accessory Product from other Vendor	7
6.1	Known Limitations and Issues	8
7	Others	8
8	Reference	8



HUAWEI E3372h TCPU-V200R002B200D15SP00C00 Release Notes V10.0

Abbreviations	Description

1 Main Features

The E3372h supports the following standards:

- LTE cat4 data service up to 150Mbit/s (Downlink) and 50Mbit/s(Uplink)
- DC-HSPA+ data service up to 43.2 Mbit/s
- HSPA+ data service up to 21.6 Mbit/s
- HSDPA packet data service of up to 14.4 Mbit/s
- HSUPA data service up to 5.76 Mbit/s
- WCDMA PS domain data service of up to 384 Kbit/s
- Equalizer and receive diversity
- microSD Card Slot (Up to 32G)
- Data and SMS Service
- Plug and play
- Standard USB interface
- CSFB

2 Hardware

2.1 Version Description

Hardware Version:	CL2E3372HM Ver.A
Platform & Chipset:	Balong Hi6921 V7R11M,

2.2 Hardware Specifications

Item	Specifications
Hardware Version	<ul style="list-style-type: none">● CL2E3372HM
Technical standard	<ul style="list-style-type: none">● LTE 3GPP R9● HSPA+/UMTS: 3GPP R99/R5/R6/R7/R8● GSM/GPRS/EDGE: 3GPP R99
External interfaces	USB: Type A with standard USB 2.0 High speed interface
	LED: indicating the status of the Data Card
	SD card: standard TF card interface
	SIM/USIM card: standard 6-pin SIM card interface



Item	Specifications
	RF interface: external RF interface
Maximum power consumption	≤ 3.5 W
Power supply	5V
Dimensions (D × W × H)	About 88mm(D) × 28mm(W) × 11.5mm (H)
Weight	≤ 25 g
Temperature	<ul style="list-style-type: none">Operating: -10°C to $+40^{\circ}\text{C}$Storage: -20°C to $+70^{\circ}\text{C}$
Humidity	5% to 95%
Base Information	<ul style="list-style-type: none">Plug and play (PnP)
	<ul style="list-style-type: none">Standard USB 2.0 High Speed interface, auto installation, convenient for use
Note: 3GPP = The 3rd Generation Partnership Project TS = Technical Specification LED = Light-Emitting Diode SIM = Subscriber Identity Module USIM = UMTS Subscriber Identity Module	

2.3 Improvements in the Previous Version

Index	Case ID	Issue Description
Hardware Version		CL2E3372HM Ver.A
Previous Hardware Version		NA
NA		

2.4 Known Limitations and Issues

Index	Case ID	Issue Description
NA		NA

3 Firmware

3.1 Version Description

Firmware Version:	22.315.01.00.00
Baseline information	Hi6921 V7R11M

3.2 Firmware Specifications

Item	Specifications

3.3 Improvement in the Previous Version

Index	Case ID	Issue Description
Firmware Version		22.315.01.00.00
Previous Version		22.200.15.00.00
1		
2		
3		

3.4 Known Limitations and Issues

Index	Case ID	Issue Description
1	Unrealized Features	NA
2		
3		

4 WebUI/HiLink

4.1 Version Description

WebUI/HiLink Version: 17.100.13.01.03

4.2 WebUI/HiLink Specifications

Item	Specifications

4.3 Improvement in the Previous Version

Index	Case ID	Issue Description
WebUI Version		17.100.13.01.03
Previous Version		17.100.12.02.03



Index	Case ID	Issue Description
WebUI Version		17.100.13.01.03
Previous Version	WebUI	17.100.12.02.03
1	New Features	
2		
3		

4.4 Known Limitations and Issues

Index	Case ID	Issue Description
1	Unrealized Features	
2		
3		

5 Software Vulnerabilities Fixes

Software/Module name	Version	CVE ID	Vulnerability Description	Solution
Linux kernel	Linux kernel 3.14.1	CVE-2014-2851	【 P711s 】 CVE-2014-2851 , CVE-2013-1763 , CVE-2014-4943 漏洞 合入	DTS2015021307041
Linux Kernel	Linux kernel 3.7.10	CVE-2013-1763	【 P711s 】 CVE-2014-2851 , CVE-2013-1763 , CVE-2014-4943 漏洞 合入	DTS2015021307041
Linux kernel	Linux kernel 3.15.6	CVE-2014-4943	【 P711s 】 CVE-2014-2851 , CVE-2013-1763 , CVE-2014-4943 漏洞 合入	DTS2015021307041
Ipv4	NA	ANDROID-20770158	【 Android 补丁 】 ANDROID-20770158 : i pv4: Missing sk_nulls_node_init() in ping_unhash()	在ping_unhash()中缺少sk_nulls_node_init()。

6 Accessory Product from other Vendor

Version Description

Accessory Product Version:



6.1 Known Limitations and Issues

7 Others

8 Reference