

SAF, LOTC Disk Replication Communication Failed

Ericsson Centralized User Database

Operating Instructions

Copyright

© Ericsson AB 2016-2018. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document *Trademark Information*.



Contents

1	Introduction	1
1.1	Alarm Description	1
1.2	Prerequisites	2
2	Procedure	4
	Glossary	5



SAF, LOTC Disk Replication Communication Failed



1 Introduction

This instruction concerns alarm handling for the SAF, LOTC Disk Replication Communication Failed alarm.

1.1 Alarm Description

This alarm is related to Service Availability Forum (SAF). For details, refer to LOTC Disk Replication Communication.

This alarm is issued when one of the System Controllers (SCs) is down for more than 20 minutes.

The possible alarm causes and the corresponding fault reasons, fault locations, and impacts are described in [Table 1](#).

Table 1 Alarm Causes

Alarm Cause	Description	Fault Reason	Fault Location	Impact
An SC blade is being replaced. ⁽¹⁾	If the SC blade is down for more than 20 minutes during the blade replacement procedure, then the alarm will be raised, because the disk replication cannot be done.	SC blade replacement	Replaced SC blade	Loss of redundancy in the SC blades.
An SC Virtual Machine (VM) is being recovered. ⁽²⁾	If the SC VM is down for more than 20 minutes during the VM recovery procedure, then the alarm will be raised, because the disk replication cannot be done.	SC VM recovery	Recovered SC VM	Loss of redundancy in the SC VMs.
One SC is down for more than 20 minutes.	When the peer SC is down the disk replication can not be done. After 20 minutes of non-synchronization, the alarm is raised.	SC down	SC	Loss of redundancy in the SCs.

(1) For CUDB systems deployed on native BSP 8100.

(2) For CUDB systems deployed on a cloud infrastructure.

The alarm attributes are listed and explained in [Table 2](#).

Table 2 Alarm Attributes

Attribute Name	Attribute Value
Auto Cease	Yes
Module	SAF



Attribute Name	Attribute Value
Error Code	7
Timestamp First	Date and time when the alarm was raised for the first time.
Repeated Counter	Number which indicates how many times the alarm was raised.
Timestamp Last	Date and time of the most recent alarm raise.
Resource ID	.1.3.6.1.4.1.193.169.9.7. <length> . <NOI>
Alarm Model Description	LOTc disk replication communication, SAF
Alarm Active Description	SAF platform: LOTc disk replication communication @ <NON>
ITU Alarm Event Type	equipmentAlarm (5)
ITU Alarm Probable Cause	equipmentMalfunction (514)
ITU Alarm Perceived Severity	(3) - Critical
Originating source IP	Node IP where the alarm was raised.
Sequence Number	Number which indicates the order in which the alarms are raised.

In [Table 2](#), the indicated variables are as follows:

- <NON> is the notifying object name that indicates where the component that generates the alarm is. For example:

safNode=PL_2_3

- <NOI> is the notifying object identifier. It corresponds to <NON> in a dot-separated, ASCII-decimal-encoded, character-per-character format. For example:

80.76.95.50.95.51 for safNode=PL_2_3.

- <length> is the number of characters in <NON> , which is equivalent to the number of octets in <NOI> . In the previous example, <length> is 6.

For further information about attribute descriptions, refer to [CUDb Node Fault Management Configuration Guide](#).

1.2 Prerequisites

This section provides information on the documents, tools, and conditions that apply to the procedure.

1.2.1 Documents

This instruction references the following documents:

- [CUDb Node Fault Management Configuration Guide](#)
- [LOTc Disk Replication Communication](#)



1.2.2 Tools
Not applicable.

1.2.3 Conditions
Not applicable.



2 Procedure

If the alarm is raised, do the following:

Steps

1. If the SC blade has been replaced (for CUDB systems deployed on native BSP 8100) or the SC VM has been recovered (for CUDB systems deployed on a cloud infrastructure), then wait for the replication to be done. The alarm must cease automatically after 5 hours.
2. If the alarm does not cease 5 hours after the blade replacement or VM recovery, then follow the instructions specified in [LOTC Disk Replication Communication](#).
3. .If the alarm does not cease, contact the next level of maintenance support. Further actions are outside the scope of this Operating Instruction.



Glossary

For the terms, definitions, acronyms and abbreviations used in this document, refer to CUDB Glossary of Terms and Acronyms