

# Change Prefix for Exported Backup Names

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2016. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Prerequisites	1
<b>2</b>	<b>Procedure</b>	<b>3</b>



Change Prefix for Exported Backup Names



# 1 Introduction

This document describes how to change prefix for exported backup names.

This is used to specify a text (maximum 128 characters) that is to be added to the beginning of the label generated for all backup export packages. It can be used to identify the managed element from which the exported backup originated.

## 1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

### 1.1.1 Conditions

The following conditions must apply:

- No other backup operation is in progress.
- The prefix text is known.
- An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.





## 2 Procedure

To change the prefix for exported backup names:

1. Navigate to the BrM managed object, for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,BrM=1
```

2. Enter Config mode:

```
(BrM=1)>configure
```

3. Enter the export package label prefix, for example:

```
(config-BrM=1)>exportPackageLabelPrefix=NODE06ST
```

**Note:** The value of attribute exportPackageLabelPrefix cannot be cleared using ECLI command `no exportPackageLabelPrefix`.

The exportPackageLabelPrefix text string supports alphanumeric, dash, underscore, and period characters.

4. Commit the change:

```
(config-BrM=1)>commit
```

5. Verify the change:

```
(BrM=1)>show
```

The following is an example output:

```
exportPackageLabelPrefix="NODE06ST"
```