

# Configure Trust Category for ECLI or NETCONF

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Prerequisites	1
<b>2</b>	<b>Procedure</b>	<b>3</b>
2.1	Configure Trust Category for ECLI	3
2.2	Configure Trust Category for NETCONF	3



Configure Trust Category for ECLI or NETCONF



# 1 Introduction

This document describes how to configure the Trust Category for ECLI or NETCONF.

## 1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

### 1.1.1 Conditions

The following conditions must apply:

- An Ericsson Command-Line Interface (ECLI) in exec mode is in progress.
- A known TrustCategory Managed Object (MO) exists; in these examples, TrustCategory=1 is used.





## 2 Procedure

### 2.1 Configure Trust Category for ECLI

To configure the Trust Category for ECLI:

1. Navigate to the `CliTls` MO, for example:

```
>dn ManagedElement=1,SystemFunctions=1,SysM=1,CliTls=1
```

2. Enter Config mode:

```
(CliTls=1)>configure
```

3. Set the reference to the applicable `TrustCategory` MO, for example:

```
(config-CliTls=1)>trustCategory="ManagedElement=1,SystemFunctions=1,SecM=1,CertM=1,TrustCategory=1"
```

4. Commit the settings:

```
(config-CliTls=1)>commit
```

5. Verify the settings:

```
(CliTls=1)>show
```

The following is an example output:

```
CliTls=1
[...]
trustCategory="ManagedElement=1,SystemFunctions=1,⇒
SecM=1,CertM=1,TrustCategory=1"
```

### 2.2 Configure Trust Category for NETCONF

To configure the Trust Category for NETCONF:

1. Navigate to the `NetconfTls` MO, for example:

```
>dn ManagedElement=1,SystemFunctions=1,SysM=1,NetconfTls=1
```

2. Enter Config mode:

```
(NetconfTls=1)>configure
```

3. Set the reference to the applicable `TrustCategory` MO, for example:

```
(config-NetconfTls=1)>trustCategory="ManagedElement=1,SystemFunctions=1,SecM=1,CertM=1,TrustCategory=1"
```



4. Commit the settings:

```
(config-NetconfTls=1)>commit
```

5. Verify the settings:

```
(NetconfTls=1)>show
```

The following is an example output:

```
NetconfTls=1
[...]  
    trustCategory="ManagedElement=1, SystemFunctions=1, ⇒  
    SecM=1, CertM=1, TrustCategory=1"
```