

# Change NTP Server Address

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Description</b>	<b>1</b>
<b>2</b>	<b>Procedure</b>	<b>1</b>
2.1	Change NTP Server Address	1



Change NTP Server Address



# 1 Description

This instruction describes how to change the Network Time Protocol (NTP) server address.

The procedure consists of the following main steps:

- 1 Perform backups of the current system configuration
- 2 Change an NTP server address
- 3 Perform backups of the new system configuration

## 2 Procedure

### 2.1 Change NTP Server Address

#### Prerequisites

- This instruction references the following document:
  - [Export Backup](#)
- No tools are required.
- The following conditions must apply:
  - No other Backup and Restore Framework (BRF) backup operation is in progress.
  - The NTP server ID to change is known, for example, NTPServer1.
  - The new NTP server address is known.
  - `userLabel` text for the new NTP server is known.
  - An Ericsson Command-Line Interface (ECLI) session is in progress.

#### Steps

1. Navigate to the `BrmBackupManager` Managed Object (MO), for example:

```
>dn ManagedElement=N0DE06ST,SystemFunctions=1,BrM=1,BrmBackupManager=SYSTEM_DATA
```



2. Start the software backup operation, for example:

```
(BrmBackupManager=SYSTEM_DATA)>createBackup B4NTPChange
```

**Note:** The backup name can have up to 50 characters. Alphanumeric, dash, and underscore characters are supported.

The system returns output `true` or `false`.

3. Verify that the backup was created:

```
(BrmBackupManager=SYSTEM_DATA)>show progressReport
```

**Note:** As this is a long-running operation, it can be necessary to enter the command several times until the final operation result is shown in the progress report.

After a backup is successfully created, the progress report shows, for example, the following:

```
progressReport
  actionId=0
  actionName="CREATE"
  additionalInfo
    "Create Backup for B4NTPChange: Initialized"
    "Create Backup for B4NTPChange: Succeeded"
  progressInfo=""
  progressPercentage=100
  result=SUCCESS
  resultInfo="B4NTPChange was created successfully."
  state=FINISHED
  timeActionCompleted="2015-12-15T10:44:41"
  timeActionStarted="2015-12-15T10:42:37"
  timeOfLastStatusUpdate="2015-12-15T10:44:41"
```

**Note:** To free up storage space, and for increased safety, export the backup to a different location; refer to [Export Backup](#).

4. Navigate to the `NtpServer` MO, for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SysM=1,TimeM=1,Ntp=1,NtpServer=NTPserver1
```

**Note:** Press the **Tab** key twice at `NtpServer=` to list the current `NtpServer` MOs.

5. List the current settings:

```
(NtpServer=NTPserver1)>show -v
```

The following is an example output:



```
NtpServer=NTPserver1
administrativeState=UNLOCKED
ntpServerId="NTPserver1"
serverAddress="100.0.12.13"
userLabel="Primary NTP server"
```

6. Enter Config mode:

```
(NtpServer=NTPserver1)>configure
```

7. Set the new NTP server address, for example:

```
(config-NtpServer=NTPserver1)>serverAddress="100.0.12.14"
```

8. Set the attribute userLabel, for example:

```
(config-NtpServer=NTPserver1)>userLabel="Primary NTP Server for application use"
```

9. Commit the setting:



### Attention!

Risk of system malfunction or traffic disturbance.

Connection to the NTP server is lost during the transition to the new NTP server address.

```
(config-NtpServer=NTPserver1)>commit
```

10. Verify the changed NTP settings:

```
(NtpServer=NTPserver1)>show -v
```

The following is an example output:

```
NtpServer=NTPserver1
administrativeState=UNLOCKED
ntpServerId="NTPserver1"
serverAddress="100.0.12.14"
userLabel="Primary NTP Server for application use"
```

11. Navigate to the BrmBackupManager MO, for example:

```
>dn ManagedElement=NODE06ST, SystemFunctions=1, BrM=1, BrmBackupManager=SYSTEM_DATA
```

12. Start the software backup operation, for example:



```
(BrmBackupManager=SYSTEM_DATA)>createBackup AfterNTPChange
```

**Note:** The backup name can have up to 50 characters. Alphanumeric, dash, and underscore characters are supported.

The system returns output true or false.

13. Verify that the backup was created:

```
(BrmBackupManager=SYSTEM_DATA)>show progressReport
```

**Note:** As this is a long-running operation, it can be necessary to enter the command several times until the final operation result is shown in the progress report.

After a backup is successfully created, the progress report shows the following:

```
progressReport
  actionId=0
  actionName="CREATE"
  additionalInfo
    "Create Backup for AfterNTPChange: Initialized"
    "Create Backup for AfterNTPChange: Succeeded"
  progressInfo=""
  progressPercentage=100
  result=SUCCESS
  resultInfo="AfterNTPChange was created successfully."
  state=FINISHED
  timeActionCompleted="2015-12-15T10:54:14"
  timeActionStarted="2015-12-15T10:52:37"
  timeOfLastStatusUpdate="2015-12-15T10:54:14"
```

**Note:** To free up storage space, and for increased safety, export the backup to a different location; refer to [Export Backup](#).