

Delete Account Policy

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2015, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	1
2.1	Delete Account Policy	1





1 Description

This instruction describes how to delete an account policy for local Operation and Maintenance (O&M) user accounts.

2 Procedure

2.1 Delete Account Policy

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - The user has sufficient access rights to perform the task, for example, the user has System Security Administrator role.
 - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.
 - The account policy is known.

Steps

1. Navigate to the `AccountPolicy` Managed Object (MO), for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LocalAuthenticationMethod=1,AccountPolicy=1
```

2. Show the user accounts that use this account policy:

```
(AccountPolicy=1)>show reservedByAccount
```

The following is an example output:

```
"ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,⇒  
UserManagement=1,LocalAuthenticationMethod=1,⇒  
UserAccountM=1,UserAccount=joedoe"  
"ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,⇒  
UserManagement=1,LocalAuthenticationMethod=1,⇒  
UserAccountM=1,UserAccount=doegeo"
```



3. Change AccountPolicy for a user account.

4. Navigate to the UserAccount MO, for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LocalAuthenticationMethod=1,UserAccountM=1,UserAccount=johndoe
```

5. Enter Config mode:

```
(UserAccount=johndoe)>configure
```

6. Change the account policy for the user account, by setting the reference to the appropriate AccountPolicy MO, for example:

```
(config-UserAccount=johndoe)>accountPolicy="ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LocalAuthenticationMethod=1,AccountPolicy=2"
```

7. Commit the settings:

```
(config-UserAccount=johndoe)>commit
```

8. Are there more user accounts to change that was listed in step 2?

Yes: Proceed with Step 3.

No: Continue with next step.

9. Navigate to LocalAuthenticationMethod MO, for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LocalAuthenticationMethod=1
```

10. Enter Config mode:

```
(LocalAuthenticationMethod=1)>configure
```

11. Delete the AccountPolicy MO, for example:

```
(config-LocalAuthenticationMethod=1)>no AccountPolicy=1
```

12. Commit the deletion:

```
(config-LocalAuthenticationMethod=1)>commit
```

13. Verify the deletion:

```
(LocalAuthenticationMethod=1)>show
```

The following is an example output:



```
LocalAuthenticationMethod=1
  userLabel="Local Authentication Method"
  AccountPolicy=2
  AdministratorAccount=la-admin
  PasswordPolicy=2
  PasswordQuality=1
  UserAccountM=1
```