

Temporarily Disable Active-Standby Geographical Redundancy

Ericsson Service-Aware Policy Controller

Operating Instructions

Copyright

© Ericsson AB 2018. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document [Trademark Information](#).

Contents

1	Description	1
2	Procedure	2
2.1	Disable Active-Standby Geographical Redundancy	2
2.2	Administrative Procedure	3
2.3	Enable Active-Standby Geographical Redundancy	3





1 Description

This instruction describes how to temporarily disable active-standby geographical redundancy in the SAPC.

Prerequisites

This section provides information of the prerequisites which must be fulfilled before using the procedure.

The following conditions must apply:

- Understand geographical redundancy functionality.
- Both SAPCs are in Active or Standby state.



2 Procedure

2.1 Disable Active-Standby Geographical Redundancy

To stop geographical redundancy, do the following:

Steps

1. Connect to the SAPC in which the administrative operation is executed and open an Ericsson Command-Line Interface (CLI) session:
2. Navigate to class `GeoRedManager` object:

```
>dn ManagedElement=1,PolicyControlFunction=1,GeoRedManager=1
```

3. Execute stop action:

```
(ManagedElement=1,PolicyControlFunction=1,GeoRedManager=1)>  
stop
```

If action was successfully executed, data replication stops until `start` command is executed.

During this period, DBS, NR, Redundancy Disabled alarm is raised. Also, the other SAPC raises Policy Control, Geographical Redundancy Unable To Reach Peer alarm.

If the other SAPC is in Standby state, it changes to Active state to takeover.

4. Verify the result of the action:

```
(ManagedElement=1,PolicyControlFunction=1,GeoRedManager=1)>  
show
```

Note: Since this is a long-running operation, it can be required to enter **show** command several times until the final operation result is shown in the progress report.

When the operation is successfully executed, it shows the following values:

```
lastOperationExecuted=STOP
```

```
lastOperationResult=ACTION_RESULT_OK
```

To check the status of the SAPC, verify that the attribute `currentState` is `Halted`

If an error occurs during the execution of the operation, it shows the following values:



```
lastOperationExecuted=STOP
```

```
lastOperationResult=ACTION_RESULT_NOT_OK
```

Attribute `lastOperationDetailedInfo` shows information about the error. It can take one of these values:

- Already in Halted state
- Not possible to execute stop action from <state> state
- Not possible to execute stop action when peer is initial or halted state

2.2 Administrative Procedure

Execute the administrative procedure in the SAPC in Halted state.

2.3 Enable Active-Standby Geographical Redundancy

To enable again geographical redundancy, do the following:

Steps

1. Configure Active SAPC as Preferred and Halted SAPC as Non-Preferred (See [Change Preferred Role in Active-Standby Geographical Redundancy](#)). This guarantees that the data changes performed during the administrative procedure are not lost.
2. Connect to the Halted SAPC and open an Ericsson Command-Line Interface (CLI) session:
3. Navigate to `class GeoRedManager` object:

```
>dn ManagedElement=1,PolicyControlFunction=1,GeoRedManager=1
```

4. Execute start action:

```
(ManagedElement=1,PolicyControlFunction=1,GeoRedManager=1)>  
start
```

If action was successfully executed, data replication starts and the SAPC synchronizes with the other SAPC.

DBS, NR, Redundancy Disabled alarm is cleared. The other SAPC clears Policy Control, Geographical Redundancy Unable To Reach Peer alarm.

5. Verify the result of the action:

```
(ManagedElement=1,PolicyControlFunction=1,GeoRedManager=1)>  
show
```



When the operation is successfully executed, it shows the following values:

`lastOperationExecuted=START`

`lastOperationResult=ACTION_RESULT_OK`

To check the status of the SAPC, verify that the attribute `currentState` is not `Halted`.

If an error occurs during the execution of the operation, it shows the following values:

`lastOperationExecuted=START`

`lastOperationResult=ACTION_RESULT_NOT_OK`

Attribute `lastOperationDetailedInfo` shows information about the error. It can take one of these values:

- Not possible to execute start action from `<state>` state
- Parameter `<parameter>` not valid