

List File Groups and File Information in Logical File System

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2014, 2015. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Introduction	1
1.1	Prerequisites	1
2	Procedure	3





1 Introduction

This document describes how to list file groups and file information in the logical file system using the Ericsson Command-Line Interface (ECLI). The user can perform this activity to accomplish the following:

- Get an overview of the logical file system.
- Check the effect of automatic deletion of files.
- Identify files that need to be manually deleted.

1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

1.1.1 Conditions

The following conditions must apply:

- The user has appropriate access rights to Managed Object (MO) *FileGroup*, matching the visible directories that have been set according to the security rules described in *Section 6* in *File Management*.
- An ECLI session in Exec mode is in progress.





2 Procedure

To list file groups and file information in the logical file system:

1. Navigate to the *LogicalFs* MO, for example:

```
>dn ManagedElement=NODE06ST, SystemFunctions=1, FileM=1  
, LogicalFs=1
```

2. List the available *FileGroup* MOs:

```
(LogicalFs=1) >show
```

The following is an example output:

```
LogicalFs=1  
FileGroup=AlarmLogs  
FileGroup=AlertLogs  
FileGroup=Function1Files  
FileGroup=Function2Files  
FileGroup=PerformanceManagementReportFiles
```

3. List the file information for a *FileGroup*, for example:

```
(LogicalFs=1) >show -r FileGroup=AlarmLogs
```

The following is an example output:



```
FileGroup=AlarmLogs
  internalHousekeeping=false
  files="FmAlarmLog.cfg"
    fileType="cfg"
    modificationTime="2014-11-20T13:33:57"
    size=108
  files="FmAlarmLog_20141025_210916.cfg"
    fileType="cfg"
    modificationTime="2014-10-25T21:09:16"
    size=108
  files="FmAlarmLog_20141025_210925.log"
    fileType="log"
    modificationTime="2014-10-25T21:09:27"
    size=0
  files="FmAlarmLog_20141025_211150_20141025_212046.log"
    fileType="log"
    modificationTime="2014-10-25T21:20:46"
    size=7168
  files="FmAlarmLog_20141025_212046.cfg"
    fileType="cfg"
    modificationTime="2014-10-25T21:20:46"
    size=108
  files="FmAlarmLog_20141027_175033_20141027_175714.log"
    fileType="log"
    modificationTime="2014-10-27T17:57:14"
    size=2048
  files="FmAlarmLog_20141027_175714.cfg"
    fileType="cfg"
    modificationTime="2014-10-27T17:57:14"
    size=108
  files="FmAlarmLog_20141027_180112_20141027_185409.log"
    fileType="log"
    modificationTime="2014-10-27T18:54:09"
    size=4096
  files="FmAlarmLog_20141027_185409.cfg"
    fileType="cfg"
    modificationTime="2014-10-27T18:54:09"
    size=108
  files="FmAlarmLog_20141028_184309.cfg"
    fileType="cfg"
    modificationTime="2014-10-28T18:43:09"
    size=108
  files="FmAlarmLog_20141120_133357.log"
    fileType="log"
    modificationTime="2014-11-20T14:34:10"
    size=5120
[...]
```