

Lock LDAP Authentication Method

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2014, 2015. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Introduction	1
1.1	Prerequisites	1
2	Procedure	3





1 Introduction

This document describes how to lock the Lightweight Directory Access Protocol (LDAP) authentication method.

In maintenance situations, the administrator can lock the LDAP authentication to prevent users from accessing the managed element over the Ericsson Command-Line Interface (ECLI) or NETCONF when it is not fully operational. When the LDAP authentication method is locked, only emergency access to the Management Information Base (MIB) is possible.

The procedure in this document must only be used during troubleshooting.

1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

1.1.1 Conditions

The following conditions must apply:

- The user has the System Security Administrator role.
- The LDAP administrative state is UNLOCKED.
- An ECLI session in Exec mode is in progress.





2 Procedure

To lock the LDAP authentication method:

1. Navigate to the `LdapAuthenticationMethod` managed object, for example:

```
>dn ManagedElement=N0DE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LdapAuthenticationMethod=1
```

2. Enter Config mode:

```
(LdapAuthenticationMethod=1)>configure
```

3. Lock the LDAP authentication method:

```
(config-LdapAuthenticationMethod=1)>administrativeState=LOCKED
```

4. Commit the setting:

```
(config-LdapAuthenticationMethod=1)>commit
```

5. Verify the result:

```
(LdapAuthenticationMethod=1)>show
```

```
LdapAuthenticationMethod=1
  administrativeState=LOCKED
  Ldap=1
```

Note: As long as the LDAP authentication method is locked, only local Linux® users belonging to the com-emergency group can start ECLI or NETCONF sessions. Ongoing ECLI and NETCONF sessions are not affected by the change.

An ongoing session can be disconnected because of inactivity. At the next logon, the user is possibly not able to access the session again. It is therefore important to stay active in the ongoing session.