

Delete Custom Role

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2014, 2015. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Introduction	1
1.1	Prerequisites	1
2	Procedure	3



Delete Custom Role



1 Introduction

This document describes how to delete a custom role.

The administrator can delete custom roles when they are no longer needed by the organization authorization policy.

1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

1.1.1 Conditions

The following conditions must apply:

- The user has the System Security Administrator role.
- The custom role to delete is known and reflects the wanted authorization policy change.
- An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.



Delete Custom Role



2 Procedure

To delete a custom role:

1. Navigate to the `LocalAuthorizationMethod` Managed Object (MO), for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LocalAuthorizationMethod=1
```

2. View the current settings:

```
(LocalAuthorizationMethod=1)>show -v
```

The following is an example output:

```
LocalAuthorizationMethod=1
  administrativeState=UNLOCKED
  CustomRole=CscfApplicationAdministratorCustom
  Role=CscfApplicationAdministrator
  Role=CscfApplicationOperator
  Role=CscfApplicationSecurityAdministrator
  Role=SystemAdministrator
  Role=SystemSecurityAdministrator
```

3. Enter Config mode:

```
(LocalAuthorizationMethod=1)>configure
```

4. Delete the `CustomRole` MO, for example:

```
(config-LocalAuthorizationMethod=1)>no CustomRole=CscfApplicationAdministratorCustom
```

5. Commit the deletion:

```
(config-LocalAuthorizationMethod=1)>commit
```

6. Verify the deletion by checking the `Role` instances:

```
(LocalAuthorizationMethod=1)>show -v
```

The following is an example output:



```
LocalAuthorizationMethod=1
administrativeState=UNLOCKED
Role=CscfApplicationAdministrator
Role=CscfApplicationOperator
Role=CscfApplicationSecurityAdministrator
Role=SystemAdministrator
Role=SystemSecurityAdministrator
```

7. The users that possess the deleted role have their authorization policy reduced.

The `CustomRule` MOs that remain unreferenced can be deleted, refer to [Delete Custom Rule](#).