

# Configure Referral Chasing

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Description</b>	<b>1</b>
<b>2</b>	<b>Procedure</b>	<b>1</b>
2.1	Configure Referral Chasing	1





# 1 Description

This instruction describes how to configure referral chasing. Such change can be triggered by the organization security policy.

## 2 Procedure

### 2.1 Configure Referral Chasing

#### Prerequisites

- This instruction references the following documents:
  - [Configure LDAP Basic Connection](#)
  - [Configure TLS for LDAP](#)
- No tools are required.
- The following conditions must apply:
  - The user has the System Security Administrator role.
  - The Managed Element (ME) is configured to connect with remote LDAP server, refer to [Configure LDAP Basic Connection](#) and [Configure TLS for LDAP](#).
  - The LDAP server is configured for the ME.
  - If the LDAP server is configured to return referrals, the returned referrals must point back to a directory tree within the same LDAP server instance; otherwise, access is denied for referred user accounts.
  - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

#### Steps

1. Navigate to the `Ldap` Managed Object (MO), for example:  

```
>dn ManagedElement=N0DE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LdapAuthenticationMethod=1,Ldap=1
```
2. Enter Config mode:



```
(Ldap=1)>configure
```

3. Enable referral chasing (`useReferrals`) in the `Ldap` (MO), for example:

```
(config-Ldap=1)>useReferrals=true
```

4. Commit the settings:

```
(config-Ldap=1)>commit
```

5. Verify the result:

```
(Ldap=1)>show
```

The following is an example output:

```
Ldap=1
baseDn="dc=my-domain,dc=com"
bindDn="cn=proxyaccount,dc=ericsson,dc=com"
bindPassword="1:XUC+jE8QV05dG570uv7hWi1s/wa+uWi0"
fallbackLdapIpAddress="192.0.2.11"
ldapIpAddress="192.0.2.10"
useTls=false
serverPort=1000
useReferrals=true
```