

# Configure SSH Algorithms

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Description</b>	<b>1</b>
<b>2</b>	<b>Procedure</b>	<b>1</b>
2.1	Configure SSH Algorithms	1





# 1 Description

This instruction describes how to configure a system-wide Secure Shell (SSH) algorithm setting.

## 2 Procedure

### 2.1 Configure SSH Algorithms

#### Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
  - The user has the System Security Administrator role.
  - The list of wanted set of algorithms is known.
  - The user has basic knowledge of cryptography.
  - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

#### Steps

1. Navigate to Ssh Managed Object (MO), for example:  
`>dn ManagedElement=N0DE06ST,SystemFunctions=1,SecM=1,Ssh=1`
2. Enter Config mode:  
`(Ssh=1)>configure`
3. Is it required to change selectedCiphers?  
Yes: Continue with next step.  
No: Proceed with Step 5.  
**Note:** The strongest SSH ciphers are selected by default.
4. Set attribute selectedCiphers to configure ciphers, for example:



```
(config-Ssh=1)>selectedCiphers=[aes256-ctr,aes192-ctr,aes128-ctr]
```

The string list must follow the constraints stated in datatype SshAlgorithm under Ssh.

5. Is it required to change selectedKeyExchanges?

Yes: Continue with next step.

No: Proceed with Step 7.

**Note:** The strongest key exchanges are selected by default.

6. Set attributesselectedKeyExchanges to configure key exchanges, for example:

```
(config-Ssh=1)>selectedKeyExchanges=[diffie-hellman-group-exchange-sha1,diffie-hellman-group14-sha1]
```

The string list must follow the constraints stated in datatype SshAlgorithm under Ssh.

7. Is it required to change selectedMacs?

Yes: Continue with next step.

No: Proceed with Step 9.

**Note:** The strongest message authentication codes are selected by default.

8. Set attributesselectedMacs to configure message authentication codes, for example:

```
(config-Ssh=1)>selectedMacs=[hmac-ripemd160@openssh.com,hmac-ripemd160,hmac-sha1-96]
```

The string list must follow the constraints stated in datatype SshAlgorithm under Ssh.

9. Commit the settings:

```
(config-Ssh=1)>commit
```

10. Verify the settings:

```
(Ssh=1)>show -v
```

The following is an example output:



```
selectedCiphers
  "aes256-ctr"
  "aes192-ctr"
  "aes128-ctr"
selectedKeyExchanges
  "diffie-hellman-group-exchange-sha1"
  "diffie-hellman-group14-sha1"
selectedMacs
  "hmac-ripemd160@openssh.com"
  "hmac-ripemd160"
  "hmac-sha1-96"
[...]
```