

Configure Time-Based Scaling

MTAS

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2019. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	2
2.1	Configure Time-Based Scaling	2
2.2	Troubleshooting	3





1 Description

The time-based scaling is a possibility to start scaling workflows in a predefined time. It can be used for scaling a Virtual Network Function (VNF) capacity dynamically in a well known time slot of a day depending on the traffic load. The VNF Life Cycle Management (VNF-LCM) triggers the scale-out and scale-in workflows automatically based on the MTAS Time Based Scaling Alert that raises on the VNF at a predefined time of a day.

Table 1 describes the MTAS Time Based Scaling SNMP alert.

Table 1 MTAS Time-Based Scaling Alert Attributes

Attribute Name	Attribute Value
Major Type	193
Minor Type	6619252
Managed Object Class	MtasScaling
Managed Object Instance	MtasFunction.applicationName=mtasFunction,MtasScaling.mtasScaling=default
Specific Problem	MtasScaling, MTAS Time Based Scaling
Event Type	ENVIRONMENTAL ALARM
Probable Cause	x733CommunicationsSubsystemFailure (306)
Additional Text	<ul style="list-style-type: none"> • MTAS Time Based Scale Out=<numberOfPayload> • MTAS Time Based Scale In=<numberOfPayload>
Perceived Severity	N/A

The following environment must be deployed on OpenStack before using this function:

- ENM
- VNF-LCM
- Target VNF



2 Procedure

2.1 Configure Time-Based Scaling

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - The VNF is onboarded using the VNF-LCM.
 - VNF-LCM is available, using either Operations Support System for Radio and Core (OSS-RC) or Ericsson Network Manager (ENM).
 - Virtual Infrastructure Manager (VIM) vCenter Server 6.0 or 6.5 is used.
 - The VIM is configured in VNF-LCM:

The VIM configuration in VNF-LCM can be checked with the `vnflcm vim list` command. For more information on VIM configuration, see VNF Lifecycle Manager System Administrator Guide, 1543-APR 901 0578 Uen.

Steps

1. In ECLI, navigate to `MtasScaling` MO, for example:

```
>ManagedElement=1,MtasFunction=MtasFunction,MtasScaling=default
```
2. Enter Config mode:

```
(MtasScaling=default)>configure
```
3. Enable time-based scaling:

```
(config-MtasScaling=default)>mtasScalingTimeBasedScalingEnabled=true
```
4. Set scale times and the wanted number of PLs, using the format `<HHMM>: <number of PLs>`, where HHMM is the time in 24-hour format, for example:

```
(config-MtasScaling=default)>mtasScalingScaleOut="1600:8"
```

```
(config-MtasScaling=default)>mtasScalingScaleIn="2200:4"
```

This means that the node is scaled out to 8 PLs at 16:00 (2 SCs+8 PLs) and is scaled in to 4 PLs at 22:00 (2 SCs+4 PLs).



5. Verify the settings:

```
(config-MtasScaling=default)>show
```

The following is an example output:

```
MtasScaling=default
  mtasScalingScaleIn="2200:4"
  mtasScalingScaleOut="1600:8"
  mtasScalingTimeBasedScalingEnabled=true
```

6. Commit the settings:

```
(config-MtasScaling=default)>commit
```

7. Exit ECLI.

```
(MtasScaling=default)>exit
```

8. Enable time-based automatic invocation of the Scale VNF WF (so-called time-based auto-scale WF):

- a. Copy `vmtas-time-based-scaling-autostart-rule.xml` included in the vMTAS Workflow Pack `CXP9034815_1-<R-state>.tar.gz` from the `autostart-rules` folder to `/vnflcm-ext/current/workflows/auto-start-rules`

- b. Restart Jboss:

```
sudo service jboss restart
```

2.2 Troubleshooting

Steps

1. Workflow log: the **Workflow Log** view in the VNF-LCM
2. If needed, increase the log level from INFO to DEBUG. For information on how to change log level, see VNF-Lifecycle Manager System Administration Guide, 1543-APR 901 0578.
3. Inspect the following logs to identify the cause of the failure:
 - Jboss Server log: `/ericsson/3pp/jboss/standalone/log/server.log`
 - System log: `/var/log/messages`
4. If a problem cannot be solved, consult the next level of maintenance support and provide the logs. Further actions are outside the scope of this instruction.