

TCAP ITU / ETSI / TTC / Chinese ITU (06/97)

STATEMENT OF COMPLIANCE

Copyright

© Ericsson AB 2000 - 2008, 2011, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.



Contents

1	Introduction	1
1.1	Concept	1
2	Compliance Lists	3
2.1	TCAP, ITU-T Q.77X	3
2.2	TCAP, ITU-T Q.75X	14
3	Notes	19
4	Glossary	21





1 Introduction

This document describes how Ericsson Signaling Transaction Capabilities Application Part (TCAP) ITU / ETSI / TTC / Chinese version complies with the following ITU-T standards of 06/97:

- ITU-T Q.752 (06/97), Monitoring and Measurements for Signaling System No.7 Networks
- ITU-T Q.771 (06/97), Signaling System No.7 - Function Description of Transaction Capabilities
- ITU-T Q.772 (06/97), Signaling System No.7 - Transaction Capabilities Information Element Definitions
- ITU-T Q.773 (06/97), Signaling System No.7 - Transaction Capabilities Formats and Encoding
- ITU-T Q.774 (06/97), Signaling System No.7 - Transaction Capabilities Procedures
- ITU-T Q.775 (06/97), Signaling System No.7 - Guidelines for Using Transaction Capabilities

1.1 Concept

This section will explain the different concepts that will be used in the compliance lists. The terms that are used are:

C	Ericsson module complies with the specified paragraph in the standard.
N	Ericsson module does not comply with the specified paragraph in the standard.
P	Ericsson module complies partly with the specified paragraph in the standard. Specify in a note what in the module that does comply and what that does not.
-	There is nothing to implement in the referred paragraph (used in column "C").





2 Compliance Lists

2.1 TCAP, ITU-T Q.77X

2.1.1 ITU-T Q.771, Function Description of TCAP

Table 1 ITU-T Q.771, Function Description of TCAP

References		C	N	P	Comments
1.	Introduction	-			
1.1	General	X			
1.2	Contents of the rec. Q771-Q.775	-			
1.3	Objectives	-			
1.3.1	Definition of Transaction Capabilities	X			
1.3.2	Scope of Transaction Capabilities	X			
2	Overview	-			
2.1	Terminology	-			
2.2	Structure of TC	-			
2.2.1	Architectural concepts	X			
2.2.2	Addressing issues	X			
2.2.3	Management aspects			X	Note 8
2.2.4	Alignment of TCAP with Rec.X.219 and X.229 (ROSE)	X			
2.2.5	Alignment of TCAP with Rec. X.217 and X.227 (ACSE)	X			
2.3	TC based on a Connectionless Network Service	-			
2.3.1	Service provided by the Component sub-layer	-			
2.3.1.1	Component	X			
2.3.1.2	Dialogue	X			
2.3.1.2.1	Unstructured dialogue	X			
2.3.1.2.2	Structured Dialogue	X			
2.3.1.2.3	Component Correlation	X			
2.3.1.3	Error Handling	X			
2.3.2	Service Provided by the Transaction Sub-Layer	X			
2.3.2.1	Unstructured Dialogue	X			

Table 1 ITU-T Q.771, Function Description of TCAP

References		C	N	P	Comments
2.3.2.2	Structured Dialogue	X			
3	Service provided by TC based on a connectionless network service	-			
3.1	Component sub-layer	-			
3.1.1	Overview of Component sub-layer primitives	X			
3.1.2	Dialogue handling	X			
3.1.2.1	Definition of parameters	X			
3.1.2.2	Dialogue facilities	X			
3.1.2.2.1	Unstructured dialogue	X			
3.1.2.2.2	Structured dialogue	X			
3.1.2.2.2.1	Beginning of a dialogue	X			
3.1.2.2.2.2	Confirmation of the dialogue	X			Note 17
3.1.2.2.2.3	Continuation of the dialogue	X			
3.1.2.2.2.4	End of a dialogue	X			Note 17
3.1.2.2.3	Exception Reporting and Message Return	X			
3.1.3	Component handling	-			
3.1.3.1	Definition of parameters	X			
3.1.3.2	Operation invocation	X			
3.1.3.3	Report of success	X			Note 4
3.1.3.4	Report of failure	X			
3.1.3.5	Reject by the TC-user	X			
3.1.3.6	Cancel of an operation	X			
3.1.3.7	Reset of an Operation Invocation	X			
3.1.3.8	Grouping of components inside a Message	X			
3.1.4	Abnormal situations	-			
3.1.4.1	Reject of a component by the Component sub-layer	X			
3.1.4.2	Dialogue abort	X			
3.1.5	Component states and state transition diagrams			X	Note 12
3.1.6	Mapping of Component sub-layer onto Transaction sub-layer	X			
3.2	Transaction sub-layer	-			



Table 1 ITU-T Q.771, Function Description of TCAP

References		C	N	P	Comments
3.2.1	Overview of the Transaction sub-layer primitives	X			
3.2.2	Information transfer in unstructured dialogue	X			
3.2.3	Transaction begin	X			
3.2.4	Transaction continuation	-			
3.2.4.1	Confirmation of the transaction	X			Note 17
3.2.4.2	Continuation of the transaction	X			
3.2.4.3	State transitions	X			
3.2.5	Transaction end	X			Note 17
3.2.5.1	Pre-arranged end	X			
3.2.5.2	Basic end	X			
3.2.5.3	Transaction abort by the TR-user	X			
3.2.6	Abnormal situations	-			
3.2.6.1	Abort by the Transaction sub-layer	X			
3.2.7	Exception Reporting and Message Return	X			
3.3	Services assumed from the connectionless network layer	X			

2.1.2 ITU-T Q.772, TCAP Information Element Definitions

Table 2 ITU-T Q.772, TCAP Information Element Definitions

References		C	N	P	Comments
1.	General	X			
2.	Transaction portion	-			
2.1	Message type	-			
2.1.1	Unidirectional	X			
2.1.2	Begin	X			
2.1.3	End	X			
2.1.4	Continue	X			
2.1.5	Abort	X			
2.2	Transaction IDs	X			
2.2.1	Originating transaction ID	X			
2.2.2	Destination transaction ID	X			

Table 2 ITU-T Q.772, TCAP Information Element Definitions

References		C	N	P	Comments
2.3	P-abort cause	X			
2.3.1	Unrecognized message type	X			
2.3.2	Unrecognized transaction ID	X			
2.3.3	Badly formatted transaction portion	X			
2.3.4	Incorrect transaction portion	X			
2.3.5	Resource limitation	X			
2.4	Dialogue portion	X			
2.5	Component portion	X			
3.	Component Portion	X			
3.1	Component type	X			
3.1.1	Invoke	X			
3.1.2	Return result (not last)	X			
3.1.3	Return result (last)	X			
3.1.4	Return error	X			
3.1.5	Reject	X			
3.2	Invoke ID	X			
3.3	Linked ID	X			
3.4	Operation code	X			
3.5	Parameter	X			
3.6	Error code	X			
3.7	Problem code	X			
3.7.1	General problem	X			
3.7.1.1	Unrecognized component	X			
3.7.1.2	Mistyped component	X			
3.7.1.3.	Badly structured component	X			
3.7.2	Invoke problem	X			
3.7.2.1	Duplicate invoke ID	X			
3.7.2.2	Unrecognized operation	X			
3.7.2.3	Mistyped parameter	X			
3.7.2.4	Resource limitation	X			
3.7.2.5	Initiating release	X			
3.7.2.6	Unrecognized linked ID	X			



Table 2 ITU-T Q.772, TCAP Information Element Definitions

References		C	N	P	Comments
3.7.2.7	Linked response unexpected	X			
3.7.2.8	Unexpected linked operation	X			
3.7.3	Return result problem	X			
3.7.3.1	Unrecognized invoke ID	X			
3.7.3.2	Return result unexpected	X			
3.7.3.3	Mistyped parameter	X			
3.7.4	Return error problem	X			
3.7.4.1	Unrecognized invoke ID	X			
3.7.4.2	Return error unexpected	X			
3.7.4.3	Unrecognized error	X			
3.7.4.4	Unexpected error	X			
3.7.4.5	Mistyped parameter	X			
4.	Dialogue portion	X			
4.1	Dialogue Control APDUs	X			
4.1.1	Dialogue Request (AARQ) APDU	X			
4.1.2	Dialogue Response (AARE) APDU	X			
4.1.3	Dialogue Abort (ABRT) APDU	X			
4.1.4	Dialogue Uni (AUDT) APDU	X			
4.2	Dialogue Portion Information Elements	-			
4.2.1	Application context name	X			
4.2.2	Protocol version	X			
4.2.3	User information	X			
4.2.4	Result	X			
4.2.5	Result source diagnostic	X			
4.2.6	Abort source	X			

2.1.3 ITU-T Q.773, TCAP Formats and Encoding

Table 3 ITU-T Q.773, TCAP Formats and Encoding

References		C	N	P	Comments
1.	Introduction	X			
2.	Description conventions	-			

Table 3 ITU-T Q.773, TCAP Formats and Encoding

References		C	N	P	Comments
3.	Abstract Syntax Description	-			
3.1	TC-Messages	X			
3.2	Dialogue Portion	X			
3.2.1	Structured Dialogue	X			
3.2.2	Unstructured Dialogue	X			
4.	Message representation	X			
4.1	Encoding rules	-			
4.1.1	Specification of Encoding rules	X			
4.1.2	Overview of Encoding Rules	-			
4.1.2.1	General message structure	X			
4.1.2.2	Tag	X			
4.1.2.2.1	Tag class	X			
4.1.2.2.2	From of the element	X			
4.1.2.2.3	Tag code	X			
4.1.2.3	Length of the Contents	X			Note 9
4.1.2.4	Contents	X			
4.1.3	Transmission order	X			
4.2	Message Encoding	-			
4.2.1	Transaction Portion	X			
4.2.1.1	Structure of the Transaction Portion	X			
4.2.1.2	Message Type Tag	X			
4.2.1.3	Transaction ID tags	X			
4.2.1.4	P-Abort Cause tag	X			
4.2.1.5	Dialogue Portion tag	X			
4.2.1.6	Component Portion tag	X			
4.2.2	Component Portion	X			
4.2.2.1	Component type tag	X			Note 18
4.2.2.2	Component ID tag	X			
4.2.2.3	Operation Code tag	X			
4.2.2.4	Parameter tag	X			
4.2.2.5	Error Code tag	X			
4.2.2.6	Problem Code	X			



Table 3 ITU-T Q.773, TCAP Formats and Encoding

References		C	N	P	Comments
4.2.3	Dialogue Portion	X			
4.2.3.1	Dialogue Control PDUs			X	Note 16

2.1.4 ITU-T Q.774, TCAP Procedures

Table 4 ITU-T Q.774, TCAP Procedures

References		C	N	P	Comments
1.	Introduction	X			
1.1	Basic guideline	X			
1.2	Overview	-			
2.	Addressing	X			
3.	Transaction capabilities based on a connectionless network service	-			
3.1	Sub-layering in TCAP	X			
3.2	Component sub-layer procedures	X			
3.2.1	Normal procedure	-			
3.2.1.1	Component handling procedure	-			
3.2.1.1.1	Mapping of TC component handling service primitives to component types	X			
3.2.1.1.2	Management of invoke IDs			X	Note 13
3.2.1.1.3	Operation classes			X	Note 12
3.2.1.1.4	Sample component flows	X			
3.2.1.2	Dialogue control by TC primitives	X			Note 17
3.2.2	Abnormal procedures	-			
3.2.2.1	Dialogue control	X			
3.2.2.2	Abnormal procedures relating to operations	X			
3.2.3	Compatibility issues	X			
3.3	Transaction sub-layer procedures	-			
3.3.1	General	X			
3.3.2	Mapping of TR service primitives to message types	X			
3.3.3	Normal procedures	-			
3.3.3.1	Message transfer without establishing a transaction	-			

Table 4 ITU-T Q.774, TCAP Procedures

References		C	N	P	Comments
3.3.3.1.1	Actions of sending end	X			
3.3.3.1.2	Actions of the receiving end	X			
3.3.3.2	Message transfer within a transaction	-			
3.3.3.2.1	Transaction begin	X			
3.3.3.2.1.1	Actions of the initiating end	X			
3.3.3.2.1.2	Actions of the receiving end	X			
3.3.3.2.2	Transaction continuation	X			
3.3.3.2.3	Transaction termination	X			
3.3.3.2.4	Abort by the TR-user	X			
3.3.3.2.5	Example of message exchange	X			
3.3.3.2.6	Transaction state transition diagrams	X			
3.3.4	Abnormal procedures relating to transaction control	X			

2.1.5 ITU-T Q.775, Guidelines for Using TCAP

Table 5 ITU-T Q.775, Guidelines for Using TCAP

References		C	N	P	Comments
1.	Introduction	-			
1.1	General	X			
1.2	Environment	X			
2.	Operations	-			
2.1	Definition			X	Note 13
2.2	Examples	-			
2.2.1	Simple operation handlings	X			
2.2.2	More complex operation handling	X			
2.3	Component-related facilities offered to TC-users	-			
2.3.1	Invocation			X	Note 13
2.3.2	Cancel (by the TC-user)	X			
2.3.3	Reject (by the TC-user)	X			
2.3.4	Remote cancel (by the TC-user)	X			Note 10
2.3.5	Reset of operation timer by the TC-user	X			



Table 5 ITU-T Q.775, Guidelines for Using TCAP

References		C	N	P	Comments
2.4	Component-related abnormal situations	-			
2.4.1	Component loss	X			
2.4.2	Component duplication	X			
2.4.3	Component missequencing	X			
2.4.4	Reject of a component by TCAP	X			
2.4.5	Operation timer expiry	X			
3.	Dialogues	X			
3.1	Grouping of components in a message	X			
3.2	Dialogue handling facilities	X			
3.2.1	Structured dialogue	-			
3.2.1.1	General	X			
3.2.1.2	Exchange of messages	X			
3.2.1.3	Dialogue end	X			
3.2.1.4	Message-related abnormal situations	X			
3.2.1.5	Relations between dialogue and component handling	X			
3.2.1.6	Addressing issues	X			
3.2.1.7	Quality of Service	X			
3.2.2	Unstructured dialogue	X			
3.3	Enhanced dialogue control facilities	-			
3.3.1	Overview	X			
3.3.2	Use of the Application-Context	X			
3.3.3	Use of user data			X	Note 14
3.3.4	Backward compatibility issues	X			
4.	Guidance for writing TC-users protocol specifications	-			Note 11
4.1	Introduction	-			Note 11
4.2	Decomposition of functionality	-			Note 11
4.2.1	Application process and application entity	-			Note 11
4.2.2	Application service element	-			Note 11
4.2.3	Communication between peer AEs/ASEs	-			Note 11
4.3	How to specify an application context	-			Note 11

Table 5 ITU-T Q.775, Guidelines for Using TCAP

References		C	N	P	Comments
4.4	How to specify an ASE	-			Note 11
4.5	How to specify Operations and Errors	-			
4.5.1	General considerations	-			Note 11
4.5.2	Use of the OPERATION MACRO notation	-			
4.5.2.1	Use of the type notation	-			Note 11
4.5.2.1.1	Specification of the operation argument	-			Note 11
4.5.2.1.2	Specification of positive outcomes	-			Note 11
4.5.2.1.3	Associated Errors	-			Note 11
4.5.2.1.4	Specification of linked operations	-			Note 11
4.5.2.2	Use of the value notation	-			Note 11
4.5.2.3	Specification of timers	-			Note 11
4.5.3	Use of the ERROR MACRO notation	-			Note 11
4.5.4	Use of the (information object) CLASS notation	-			Note 11
4.5.4.1	The OPERATION (information object) CLASS	-			
4.5.4.1.1	Specification of the operation argument	-			Note 11
4.5.4.1.2	Specification of the operation result	-			Note 11
4.5.4.1.3	Specification of positive outcomes	-			Note 11
4.5.4.1.4	Associated errors	-			Note 11
4.5.4.1.5	Specification of the linked operations	-			Note 11
4.5.4.1.6	Synchronous nature of the operations	-			Note 11
4.5.4.1.7	Operation code	-			Note 11
4.5.4.1.8	Classes of operation	-			Note 11
4.5.4.1.9	Specification of timers	-			Note 11
4.5.5	The ERROR (information object) CLASS	-			Note 11
4.5.5.1	Specification of the parameter accompanying an error	-			Note 11
4.5.5.2	Error code	-			Note 11
4.5.6	Examples of Operations and Errors description	-			
4.5.6.1	Operations and Errors purposes	-			Note 11
4.5.6.1.1	Provide routing information	-			Note 11
4.5.6.1.2	Get calling party number	-			Note 11
4.5.6.1.3	Invalid called number	-			Note 11



Table 5 ITU-T Q.775, Guidelines for Using TCAP

References		C	N	P	Comments
4.5.6.1.4	Subscriber not reachable	-			Note 11
4.5.6.1.5	Called barred	-			Note 11
4.5.6.1.6	Calling party number not available	-			Note 11
4.5.6.1.7	Processing failure	-			Note 11
4.5.6.2	ASN.1 specification	-			Note 11
4.5.7	Moving from the MACRO notation to the (information object) CLASS notation and use of ANS.1 modules	-			Note 11
4.5.8	Allocation and Management of Operation and Error Codes	-			
4.5.8.1	General considerations	-			Note 11
4.5.8.2	Import and Export of Operations and Errors	-			Note 11
4.5.8.3	Impact of ASE/AE structure on operation and error code administration	-			Note 11
4.5.8.3.1	Monolithic approach - One AC, one ASE	-			Note 11
4.5.8.3.2	One AC comprising more than one ASE	-			Note 11
4.5.8.4	Re-use of operation and errors	-			Note 11
4.6	Data types specifications	-			
4.6.1	General				Note 11
4.6.2	Use of tags	-			Note 11
4.6.3	Instances and types	-			Note 11
4.6.4	Exporting and importing data types	-			Note 11
4.7	How to specify abstract syntaxes	-			Note 11
4.8	Encoding rules	-			Note 11
5.	Mapping of the generic ROS concepts onto TC services	-			
5.1	Overview	-			Note 11
5.1.1	Notation and concept for the generic ROS model	-			Note 11
5.1.2	Communication model	-			Note 11
5.2	Remote operation service realization	-			
5.2.1	Basic services (stub)	-			Note 11
5.2.2	Bind and unbind operations	-			Note 11
5.2.2.1	Bind operation	-			Note 11

Table 5 ITU-T Q.775, Guidelines for Using TCAP

References		C	N	P	Comments
5.2.2.1.1	Invoking a bind operation	-			Note 11
5.2.2.1.2	Responding to a bind operation	-			Note 11
5.2.2.2	Unbind operations	-			
5.2.2.2.1	Invoking an unbind operation	-			Note 11
5.2.2.2.2	Responding to an unbind operation	-			Note 11
5.3	Information transfer	-			
5.3.1	Association realizations	-			Note 11
5.3.2	Transfer realization	-			Note 11
5.4	TC-based application context	-			Note 11
5.5	Abstract syntaxes	-			
5.5.1	Dialogue control	-			Note 11
5.5.2	User-defined syntaxes	-			
5.5.2.1	General	-			Note 11
5.5.2.2	Defining the abstract syntaxes	-			Note 11
5.6	Notation extension	-			Note 11

2.2 TCAP, ITU-T Q.75X

2.2.1 ITU-T Q.752, Monitoring and Measurements

Table 6 ITU-T Q.752, Monitoring and Measurements

Reference		C	N	P	Comments
1.	Introduction	-			
1.1	General	-			
1.2	Network view	-			
1.3	Guidelines for uses of measurements	-			
1.4	Grouping of measurements			X	Note 1, Note 3
1.5	Collection of measurements	-			
1.6	Definition of terms	-			
1.6.1	Fault			X	Note 2
1.6.2	Configuration	X			
1.6.3	Performance	X			



Table 6 ITU-T Q.752, Monitoring and Measurements

Reference		C	N	P	Comments
1.6.4	Accounting	-			Note 3
1.6.5	Network administration and planning	X			
1.6.6	Near-real-time measurements	X			
1.7	Listing of measurements	-			
1.7.1	General	-			
1.7.1.1	<no heading>	-			
1.7.1.2	<no heading>	-			
1.7.1.3	<no heading>	-			
1.7.1.4	<no heading>	-			
1.7.1.5	<no heading>	-			
1.7.1.6	<no heading>	-			
1.7.1.7	<no heading>	-			
1.7.2	Intervals for measurements		X		Note 2
1.8	Techniques for filtering measurements	X			
2.	MTP monitoring and measurements	-			
2.1	General	-			
2.2	Table 1	-			
2.3	Table 2	-			
2.4	Table 3	-			
2.5	Table 4	-			
2.6	Table 5	-			
2.7	Table 6	-			
3.	SCCP monitoring and measurements	-			
3.1	General	-			
3.2	Table 7	-			
3.3	Table 8	-			
3.4	Table 9	-			
3.5	Table 9 bis	-			
4.	ISDN-UP monitoring and measurements	-			
4.1	General	-			
4.2	Table 10	-			
4.3	Table 11	-			

Table 6 ITU-T Q.752, Monitoring and Measurements

Reference		C	N	P	Comments
4.4	Table 12	-			
5.	TC monitoring and measurements	-			
5.1	General	-			
5.2	Table 13				
	Table 13.1			X	Note 5
	Table 13.2			X	Note 5
	Table 13.3			X	Note 5
	Table 13.4			X	Note 5
	Table 13.5	-			
	Table 13.6		X		
	Table 13.7		X		
	Table 13.8	-			
	Table 13.9		X		
	Table 13.10		X		
	Table 13.11		X		
5.3	Table 14				
	Table 14.1			X	Note 2, Note 6
	Table 14.2	X			
	Table 14.3	X			
	Table 14.4			X	Note 2, Note 7
	Table 14.5			X	Note 2, Note 7
	Table 14.6			X	Note 2, Note 7
	Table 14.7		X		
	Table 14.8	X			
	Table 14.9	-			
	Table 14.10		X		
	Table 14.11	X			
	Table 14.12			X	Note 5
6.	Uses of measurements	-			
6.1	Introduction	-			
6.2	Message transfer part (MTP)	-			



Table 6 ITU-T Q.752, Monitoring and Measurements

Reference		C	N	P	Comments
6.2.1	Fault and configuration management measurements	-			
6.2.2	MTP performance	-			
6.3	Signaling Connection Control Part (SCCP)	-			
6.3.1	SCCP fault management	-			
6.3.2	SCCP configuration management	-			
6.3.3	SCCP performance	-			
6.4	Integrated services digital network user part (ISDN-UP)	-			
6.4.1	Fault and configuration management	-			
6.4.2	ISDN-UP performance	-			
6.5	Transaction Capabilities (TC)	-			
6.5.1	TC fault management measurements	X			
6.5.2	TC performance			X	Note 5
6.6	Preparation of traffic forecasts	-			
6.7	Network planning	-			
6.8	Evaluation of maintenance force effectiveness	-			
6.9	Near real time network control	-			
7.	Accounting of MTP and SCCP message traffic	-			
7.1	General	-			
7.2	MTP traffic registration	-			
7.2.1	Basic registration principles	-			
7.2.2	Limitations	-			
7.3	SCCP traffic registration	-			
7.4	Basic registration principles	-			
7.5	Limitations	-			
A.	TC: Fault Measurements pertinent to development of TC and its users	-			
A.1	Table A.1			X	Note 15





3 Notes

- Note 1** TCAP ITU / ETSI / TTC / Chinese supports the definition of most of the specified groups, but does not group the raw measurements together.
- Note 2** Faults are reported on each occurrence.
- Note 3** Accounting measurements are for further study in the ITU-T standard.
- Note 4** Segmentation is not supported in TCAP ITU / ETSI / TTC / Chinese; all segmentation or reassemble must be performed by the TC-user.
- Note 5** TCAP ITU / ETSI / TTC / Chinese provides the raw measurements necessary to calculate these statistics.
- Note 6** No measurements in table 14.1, section 5.3(Q.752) are logged per destination address.
- Note 7** No measurements in table 14.4 through 14.6, section 5.3(Q.752) are logged per destination address. The address may instead be obtained from the alarms raised by TCAP ITU / ETSI / TTC / Chinese which are logged on every occurrence.
- Note 8** The supported management primitives requires that the information is directed to a specific subsystem. It is up to SCCP to send the information to each an every subsystem that is to be informed.
- Note 9** The Length of Contents element has a maximum length of 3 octets.
- Note 10** The Remote Cancel by the TC-user is applicable to the TC-user only.
- Note 11** Applicable to the TC-user only.
- Note 12** States 'Wait for Reject' and 'Reject Pending' are not implemented in TCAP ITU / ETSI / TTC / Chinese.
- Note 13** Invoke IDs may be reallocated immediately on return of the corresponding Invocation State Machine to the Idle State.
- Note 14** TCAP ITU / ETSI / TTC / Chinese checks for a Sequence of Externals in User Information but not the format of data within each External.



- Note 15** Compare with the information in this report for section 5.3 of Q.75.
- Note 16** Protocol Version is Mandatory for the outgoing AARQ in TCAP ITU / ETSI / TTC / Chinese
- Note 17** Additional change of originating address according to the standard 3G TS 23.006 (Support of Mobile Number Portability) also supported
- Note 18** TCAP can be configured to handle malformed incoming INVOKE components using "Adapt Parameter Collection Tags Missing" configuration parameter. When the parameter is enabled TCAP EIT can handle malformed proprietary INVOKE components. Parameters section can be handled even without Sequence, SequenceOf, Set or SetOf Tags (when the number of parameters is greater than one). In this case TCAP EIT will wrap the parameters section into Sequence Tag before sending T_INVOKE_ind. The behavior are applicable only for incoming INVOKE components.



4 Glossary

ETSI	European Telecommunications Standards Institute
ITU	International Telecommunication Union
TCAP	Transaction Capabilities Application Part
TTC	Telecommunications Technology Committee