

# Change Enrollment Server

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2014, 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Description</b>	<b>1</b>
<b>2</b>	<b>Procedure</b>	<b>1</b>
2.1	Change Enrollment Server	1





# 1 Description

This instruction describes how to change an enrollment server.

## 2 Procedure

### 2.1 Change Enrollment Server

#### Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
  - The user has the System Security Administrator role.
  - The enrollment server is known.
  - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

#### Steps

1. Navigate to the **CertM** Managed Object (MO), for example:

```
>dn ManagedElement=N0DE06ST,SystemFunctions=1,SecM=1,CertM=1
```

2. Enter Config mode:

```
(CertM=1)>configure
```

3. View the **EnrollmentServerGroup** MOs:

```
(config-CertM=1)>show -v -r
```

The following is an example output:



```
CertM=1
[...]
  EnrollmentServerGroup=1
    enrollmentServerGroupId="1"
    userLabel=[] <empty>
    EnrollmentServer=1
  [...]
```

4. Select the `EnrollmentServer` MO to modify, for example:

```
(config-CertM=1)>EnrollmentServerGroup=1,EnrollmentServer=1
```

5. Modify the `EnrollmentServer` MO attributes, for example:

- `(config-EnrollmentServer=1)>uri=http://192.0.2.10:8080`
- `(config-EnrollmentServer=1)>userLabel=admin@organization.com`

6. Commit the settings:

```
(config-EnrollmentServer=1)>commit
```

7. Verify the settings:

```
(EnrollmentServer=1)>show -v
```

The following is an example output:

```
EnrollmentServer=1
[...]
  enrollmentServerId="1"
  protocol=CMP
  uri="http://192.0.2.10:8080"
  userLabel=[] <empty>
```