

SS7 MTP-L3 and M3UA IETF TTC 2002

STATEM OF COMPLIANCE

Copyright

© Ericsson AB 2008, 2011, 2013. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.



Contents

1	GENERAL	1
1.1	Introduction	1
1.2	Concept	1
2	Compliance Lists	3
2.1	JT-Q701	3
2.2	JT-Q704	4
2.3	JT-Q707	8
2.4	JT-Q2210	8
3	Notes and Comments	9
	Glossary	11
	Reference List	13





1 GENERAL

1.1 Introduction

This document describes to what extent the Ericsson SS7 MTPL3& M3UA IETF signaling component conforms with the standards Reference [1], Reference [2], Reference [3], and Reference [4].

1.2 Concept

The terms that are used are:

C	The Ericsson signaling component complies with the specified section in the standard.
N	The Ericsson signaling component does not comply with the specified section in the standard.
P	The Ericsson signaling component complies partly with the specified section in the standard.
-	There is nothing to implement in the referred section (always placed in column C).





2 Compliance Lists

2.1 JT-Q701

Table 1

References	C	N	P	Comments
1. Introduction	X			
2. Signaling system structure	X			
3. Message Transfer Part and the signaling network	-			
3.1 General	-			
3.1.1 Signaling network components			X	Note 1 on Page 9
3.1.2 Signaling modes	X			
3.1.3 Signaling point modes	X			
3.1.4 Message labelling	X			
3.2 Signaling message handling functions	X			
3.3 Signaling network management functions	X			
3.4 Testing and maintenance functions	X			
3.5 Use of signaling network	X			
4 Message transfer capability	X			
5 Differences from Blue Book	-			See Section 2.2 on page 4
6 Compatibility in the Message Transfer Part	X			
7 Interworking of yellow, red and blue MTP implementation	-			
7.1 Yellow Book to Red Book interworking		X		
7.1.1 Level 2 flow control		X		
7.1.2 Transfer restricted and Transfer controlled procedures		X		
7.1.3 Transfer allowed/Transfer prohibited acknowledgments		X		
7.1.4 Management inhibiting procedure		X		
7.2 Red Book to Blue Book interworking	-			

Table 1

References	C	N	P	Comments
7.2.1 Signaling Point Restart		X		
7.2.2 Q.703 and Q.704 timer values	X			
7.2.3 User flow control	X			
7.2.4 Management inhibit test procedure		X		
7.2.5 SIF length increase		X		
7.2.6 SIF length increase (National networks option)		X		
7.2.7 Processor outage		X		
7.3 Yellow Book to Blue Book interworking		X		
7.4 Blue Book to the present version interworking	X			
7.5 Red Book to the present version interworking	X			
8 Primitives and parameters of the Message Transfer Part	X			

2.2 JT-Q704

Table 2

References	C	N	P	Comments
1 Introduction	-			
1.1 General characteristics of the signaling network functions	X			
1.2 Signaling message handling	X			
1.3 Signaling network management			X	Note 2 on Page 9, Note 3 on Page 9
2 Signaling message handling	X			
3 Signaling network management	-			
3.1 General			X	Note 2 on Page 9
3.2 Status of signaling links	X			
3.3 Procedures used in connection with link status changes	-			
3.3.1 Signaling link failed	X			
3.3.2 Signaling link restored	X			



Table 2

References	C	N	P	Comments
3.3.3 Signaling link deactivated	X			
3.3.4 Signaling link activated	X			
3.3.5 Signaling link blocked			X	Note 6 on Page 9
3.3.6 Signaling link unblocked	X			
3.3.7 Signaling link inhibited	X			
3.3.8 Signaling link uninhibited	X			
3.4 Status of signaling routes3.3.8 Signaling link uninhibited	X			
3.5 Procedures used in connection with route status changes	X			
3.6 Status of signaling points	X			
3.7 Procedures used in connection with point status changes	X			
3.8 Signaling network congestion	X			
4 Signaling traffic management	-			
4.1 General	-			
4.2 Normal routing situation	X			Note 7 on Page 9
4.3 Signaling link unavailability	X			
4.4 Signaling link availability	X			
4.5 Signaling route unavailability	X			
4.6 Signaling route availability	X			
4.7 Signaling route restriction	X			
4.8 Signaling point availability	X			
5 Changeover	-			
5.1 General	X			
5.2 Network configurations for changeover	X			
5.3 Changeover initiation and actions	X			
5.4 Buffer updating procedure	X			
5.5 Retrieval and diversion of traffic	X			
5.6 Emergency changeover procedures			X	Note 4 on Page 9
5.7 Procedures in abnormal conditions	X			
6 Changeback	X			



Table 2

References	C	N	P	Comments
7 Forced rerouting	X			
8 Controlled rerouting initiation and actions	X			
9 MTP restart	X			
10 Management inhibiting	X			
11 Signaling traffic flow control	X			
12 Signaling link management	-			
12.1 General			X	Note 2 on Page 9
12.2 Basic signaling link management procedures	X			
12.3 Signaling link management procedures based on automatic allocation of signaling terminals	X			
12.4 Signaling link management procedures based on automatic allocation of signaling data links	X			
12.5 Automatic allocation of signaling terminals	X			
12.6 Automatic allocation of signaling data links	X			
12.7 Different signaling link management procedures at the two ends of a link set	X			
13 Signaling route management	-			
13.1 General	X			
13.2 Transfer prohibited	X			
13.3 Transfer-allowed	X			
13.4 Transfer-restricted (National option)	X			
13.5 Signaling-route-set-test	X			
13.6 Transfer-controlled (International network)	X			
13.7 Transfer-controlled (National option with congestion priorities)	X			
13.8 Transfer-controlled (National option without congestion priorities)	X			



Table 2

References	C	N	P	Comments
13.9 Signaling-route-set-congestion-test (National Option)	X			
14 Common characteristics of message signal unit formats	-			
14.1 General	X			
14.2 Service information octet	-			
14.2.1 Service indicator (SI)	X			
14.2.2 Sub-service field (SSF)	X			Note 8 on Page 9
14.3 Label	-			
15 Format and codes of signaling network management messages	-			
15.1 General	X			
15.2 Label	X			
15.3 Heading code (H0)	X			
15.4 Changeover message	X			
15.5 Changeback message	X			
15.6 Emergency changeover message	X			
15.7 Transfer-prohibited message	X			
15.8 Transfer-allowed message	X			
15.9 Transfer-restricted message (national option)	X			
15.10 Signaling-route-set-test message	X			
15.11 Management inhibit message	X			
15.12 Traffic restart allowed message	X			
15.13 Signaling-data-link-connection-order message		X		
15.14 Signaling-data-link-connection-acknowledgement message		X		
15.15 Transfer-controlled message	X			
15.16 Signaling-route-set-congestion-test message (national option)	X			
15.17 User Part unavailable message	X			
16 Static transition diagrams, abbreviations and timers	-			

Table 2

References	C	N	P	Comments
16.1 General	-			
16.2 Drafting conventions	-			
16.3 Signaling message handling	-			
16.4 Signaling traffic management	-			
16.5 Signaling link management	-			
16.6 Signaling route management	-			
16.7 Abbreviations used in Figures 23 onwards	-			
16.8 Timers and timer values			X	Note 5 on Page 9

2.3 JT-Q707

Table 3

References	C	N	P	Comments
1 General	-			
2 Testing	X			
3 Fault location	-			
4 Signaling network monitoring	-			
5 Formats and codes of signaling network testing and maintenance messages	X			
6 State transition diagrams	X			

2.4 JT-Q2210

Ericsson SS7 MTP-L3 TTC version R1 is compliant with TTC JT-Q2210 except for the deviations from TTC JT-Q704 (see Section 2.2 on page 4).



3 Notes and Comments

Note 1	Link groups not supported.
Note 2	Automatic allocation or reconfiguration of signaling equipment is not supported.
Note 3	See the notes for the individual signaling network management messages (clause 15).
Note 4	No difference between long- and short-term processor outage. All emergency changeovers are treated as being initiated by a long-term processor outage.
Note 5	The following timers are not implemented: T7, T9, T11, T24.
Note 6	Timer T24 not used. Signaling traffic management commences without interruptions.
Note 7	Priorities are not set on a per linkset basis, instead priorities are set on routes in routesets.
Note 8	The spare bits are sent transparently to/from the User Part and they are always used as priority bits.





Glossary

MSU

Message Signaling Unit

MTP

Message Transfer Part

SIF

Signaling Information Field





Reference List

TTC Standards

- [1] JT-Q701, Version 2, Nov. 28, 1990
- [2] JT-Q704, Version 4, May 30, 2002
- [3] JT-Q707, Version 2, Nov. 28, 1990
- [4] JT-Q2210, Version 1, Apr. 24, 1996