

Create Trust Category

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2014, 2015. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Introduction	1
1.1	Prerequisites	1
2	Procedure	3





1 Introduction

This document describes how to create a trust category, which is a group of trusted certificates.

A trusted certificate can belong to multiple trust categories.

1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

1.1.1 Conditions

The following conditions must apply:

- The user has the System Security Administrator role.
- An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.





2 Procedure

To create a trust category:

1. Navigate to the *CertM* Managed Object (MO), for example:

```
>dn ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, CertM=1
```

2. Enter Config mode:

```
(CertM=1) >configure
```

3. Create the *TrustCategory* MO, for example:

```
(config-CertM=1) >TrustCategory=aurora
```

4. Set at least one *TrustedCertificate* MO reference, for example:

```
(config-TrustCategory=aurora) >trustedCertificates=["ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, CertM=1, TrustedCertificate=1", "ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, CertM=1, TrustedCertificate=2"]
```

5. Commit the setting:

```
(config-TrustCategory=aurora) >commit
```

6. Verify the committed trusted certificate reference in attribute *trustedCertificates*, for example:

```
(TrustCategory=aurora) >show
```

The following is an example output:

```
TrustCategory=aurora
  trustedCertificates
    "ManagedElement=1, SystemFunctions=1, SecM=1, =>
CertM=1, TrustedCertificate=1"
    "ManagedElement=1, SystemFunctions=1, SecM=1, =>
CertM=1, TrustedCertificate=2"
```