

# MTAS AppTrace

## MTAS

---

### USER GUIDE

**Copyright**

© Ericsson AB 2016. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Prerequisites	1
1.1.1	Documents	1
<b>2</b>	<b>AppTrace</b>	<b>3</b>
<b>3</b>	<b>AppTrace Use</b>	<b>5</b>
3.1	Trace Levels for Live System	5
3.2	Trace Levels for Single Session	5
3.3	EventHistory	6
3.4	Catalina Log	6
3.5	Applog	7
3.6	One Subscriber Tracing	7
3.7	Default Trace	8
<b>4</b>	<b>AppTrace Process Types in MTAS</b>	<b>9</b>
<b>5</b>	<b>AppTrace Domains in MTAS</b>	<b>13</b>
5.1	Domain Parameters	18
<b>6</b>	<b>Trace Profiles</b>	<b>21</b>
6.1	Trace Profiles for Single Session Software Trace	21
6.2	Trace Profiles for Live System Software Trace	27
6.3	Trace Profiles for Single Session Network Trace	31
6.4	Trace Profiles for Live System Network Trace	33
<b>7</b>	<b>Example</b>	<b>37</b>





# 1 Introduction

This document describes how to use and apply the Application Trace (AppTrace) in the MTAS. The document lists the MTAS process types and domains that are applicable for collecting trace information. AppTrace is a service available in the vDicos execution environment. AppTrace is used for tracing vDicos applications selectively and safely.

## 1.1 Prerequisites

It is assumed that users of this document are familiar with performing operations within the area for Operation and Maintenance (O&M), in general.

### 1.1.1 Documents

Information on how to use the AppTrace, the different states, levels, and commands can be found in *AppTrace User Guide*.

For information about how to troubleshoot the MTAS node, refer to *MTAS Troubleshooting Guideline*.





## 2 AppTrace

The AppTrace is a service available in the vDicos runtime environment. The main purpose of the AppTrace is to provide practical assistance in troubleshooting vDicos applications on live systems. By using the AppTrace, an AppTrace end user can gain insight into the current behavior of an application. An AppTrace end user is an Ericsson support personnel performing operation and service provisioning tasks in a live network. Operators are not considered AppTrace end users.

Use the AppTrace with caution, since the inherent problem with observing the behavior of a system by tracing is the consumed capacity of the tracing itself. If the cost is too high, it can interfere with the primary function of the system and at worst even cause system failure.

The traces end up in the console log. The console log is a two-file wrapping log writer that writes one log per processor.

Each AppTrace statement includes the following:

- Date
- Time
- Trace level
- Filename
- Line
- Forlop identity
- Processor name
- Process identity
- Process name

Abstract domains cannot be used in the AppTrace definition because they mask underlying concrete domains and generate empty lines in console logs.

For more information about how to configure the AppTrace, refer to *AppTrace User Guide*.

For more information about the Console Logs, refer to *MTAS Logs*.





## 3 AppTrace Use

This section describes how to use the AppTrace and the defined trace levels in the MTAS. The trace level must be set to the defined trace level+1 to include the trace level in the log, for example, for DEBUG (55), the trace level is set to 56.

**Note:** Narrow down the trace domains when applying AppTrace for the MTAS. All trace domains must not be used at once and do not apply together with the vDicos or other application traces.

There is also a possibility to use preconfigured trace profiles. For more information about handling of trace profiles, refer to section *Trace Profiles* in *MTAS Troubleshooting Guideline*.

### 3.1 Trace Levels for Live System

Trace levels used in the MTAS for live systems are listed in ascending order in the following table:

**Note:** It is possible to use FORLOP (56) to trace a single user in a live system providing the load does not exceed 50%.

Trace Level	Description
CRITICAL (7)	Applied to report when a service or an interface is not working, for example, owing to a faulty configuration, DNS resolution problems, or unsupported protocol versions.
CONFIG (20)	All changes of configuration data are reported in this trace level. Normally, only one trace per configuration change is reported.
MAJOR (24)	Used to report network tracing of SIP messages for a specific subscriber in the live network.
WARNING (36)	Traces to be generated whenever an unexpected event internally in the node is detected and no assert or error is to be called. This scenario occurs when source of the fault is unclear. It could be owing to node internal errors or external misbehavior (transport errors, and so on), therefore assert is not appropriate to use.
PROTOCOL_ERROR (38)	Traces to be generated whenever a message received on an interface is erroneous or received in unexpected state.
MINOR (39) or MINOR_LOW (40)	Two levels used to report an unexpected event which not necessarily indicates an error. Any important information can also be logged with these trace levels.
PROTOCOL_TIMEOUT (41)	Traces to be generated whenever there is a protocol time-out.

### 3.2 Trace Levels for Single Session

The recommended trace level for single session, DEBUG (55), is 56 or FORLOP (56) is 57. Other trace levels used in the MTAS are listed in ascending order in the following table:



Trace Level	Description
PROGRESS (43)	Function progress (call setup), interface signaling (SIP, Diameter, H248 signaling), and state transitions are reported using this trace level. Applying this trace level, it is possible to follow the progress of a call, with state transitions, through all protocol functions and services.
PROCESS (51)	Applied when report creation or termination of a dynamic and static process and creation or deletion of vDicos dialogues.
DEBUG (55)	Applied to generate debug traces.
FORLOP (56)	Applied to generate traces when forlop has a value higher than zero.
SIP_STACK (61)	Applied for traces generated by the SIP stack. Must not be used unless a SIP problem is identified.

### 3.3 EventHistory

In a live system, it is not possible to use full tracing owing to the number of logs generated. To help analyze problems occurring under these circumstances, important trace strings can be written to the EventHistory.

These traces are output to the console logs if there is an unexpected process termination in the following Capsule Abortion (CA) cases:

- Divide by zero
- Illegal opcode
- Page fault exception

The type of information saved in the EventHistory could, for example, be the incoming and outgoing SIP messages, h.248, expiring timers, created events, and code execution

The MTAS EventHistory is always on.

### 3.4 Catalina Log

The MTAS Catalina log files contain information about MTAS XDMS processes. Each Catalina file has a maximum size of 10 MB. Once this size has been reached, a new file is created. The total number of files can be up to 11, named `catalina.log`, `catalina.log.1`, and so on. The resulting string starts with the date, time, thread name, log level, AppTrace domain, session, and sequence number. Next part of the string is the “-” character, after which is the logging information. The resulting string ends up in the Catalina log and is printed to the following directory:

```
/opt/mmas/appserver/traffic_instance0/standalone/logs/
```

The following are examples of a Catalina string:



```
2015-09-15 10:10:01,260 [http-apr-127.0.0.1-8095-exec-8]
DEBUG mtas.xdms.xdms.cai3g A192D168D83D100Z1441384753S516P
65537 1688257881 - Document pre-edit
```

```
2015-09-15 10:07:07,879 [http-apr-127.0.0.1-8090-exec-2]
DEBUG mtas.xdms.xdms.validation 127.0.0.1 simservs
sip:user@telcom.com - ...application validated.
```

## 3.5 Applog

The MTAS applog log files contain information about terminated MTAS processes. Such a terminated process is a fault indication. Each applog file is determined to a maximum size of 40 MB. Once this size has been reached, a new applog file is created. The total number of applog files can be up to 15, and are named `MTAS_<timestamp>.log`, `MTAS_<timestamp>.log.1`, `MTAS_<timestamp>.log.2`, and so on.

The resulting string starts with the sequence number, time stamp, log level, process key, and descriptive field. The resulting string ends up in the following directory:

```
/cluster/storage/no-backup/coremw/var/log/saflog/MTASApp
Logs/vdicos
```

The following is an example of an applog string:

```
163 11:11:40 10/29/2014 WA "[SipDistributorProcess]
Control::init() SipDistributorControl ok, done
synchronizing! OamSynchronizerPortName published!!!"
```

For more information about the AppLogs, refer to *MTAS Logs*.

## 3.6 One Subscriber Tracing

Subscriber tracing can be done using the existing forlop tracing supported by vDicos AppTrace. Forlop tracing makes it possible to inject a forlop identity into the AppTrace at a trace event and then to use that identity in subsequent AppTrace expressions to capture related events. The basic idea is to allow the trace-user to trace an entire “call”, as it propagates through the system by passing through various processes on several processors. A forlop identity is simply an integer value. The default value of zero is a predefined “anonymous forlop”, that is, forlop tracing is turned off.

Trace profiles for forlop can be found in Section 6 on page 21

Example of using forlop can be found in Step 6.

For an example use of a subscriber tracing profile, refer to section *Trace Profiles in MTAS Troubleshooting Guideline*.



## 3.7 Default Trace

The MTAS automatically writes certain number of important trace events into console log files without any manual action needed from the end user. The default trace printouts provide useful information about potential problems on a live system even if the logs do not contain more detailed and specific traces that can be produced by starting an AppTrace session.

The trace events that are printed by default are randomly selected from WARNING, CONFIG, and CRITICAL level trace events. The number of printed trace events is under control: 10 WARNING and another 10 CONFIG, and CRITICAL events are logged by default on average each minute into each console log file of each processor (if so many such events happen at all).

The following is an example of a default trace string:

```
DEF-TRACE: WARNI 7220 sip:B_barring_dndcb_
10202668@barringdndcb.imsas.uab.ericsson.se
ApplicationProcess
SubscriberLanguageCdcsHandler.cc:127
Found no language mapping entry for sv
```

The default trace feature can be controlled through CM attributes. The feature can be turned off and also an intensive default tracing can be achieved for debugging purposes.

For more details, see the description of the `mtasTraceDefaultWarningPerMinute`, `mtasTraceDefaultCriticalConfigPerMinute`, and `mtasTraceDefaultTracePrintSubscriberKey` CM attributes in *Managed Object Model (MOM)*.



## 4 AppTrace Process Types in MTAS

MTAS static processes and most dynamic processes start directly after system startup. Certain dynamic processes can however be started or restarted a long time after the system startup. The following table lists the available MTAS processes, each with a short description or comment.

The table shows the complete syntax used in AppTrace process name. This is for most process types written according to the following format:

**<ProcessName>.RTID**

Process Type	Description or Comment
AcrStorageHandlerProc.1119246	When communication with an offline Charging Server is lost, this process is used by the application process to store all offline charging ACR messages on disk.
ApplicationProcess.1060633	Application process
CarrierSelectDataProcess.1101115	Handles the MTAS configuration data for Carrier Select
ChargingBackupHandlerProcNew.1101924	Charging backup handler process
ChargingProcess.1101151	Charging process
CmControllerPT.1058017	CM controller processes
CmJimLDAPAdapterProcess.1058088	CMjim ldap adapter process
Cm_TcpSetupHandlerProcess.1058091	CM TCP setup handler process
DIA_PRC_ConnectionMgrProcess.1015860	-
DIA_PRC_DBAccessHandlerProcess.1053645	-
DIA_PRC_DefaultService.1015914	-
DIA_PRC_HandlerProcess.1015878	-
DIA_PRC_TransportListenerProcess.1015881	-
DeeUtilCliDaemon.1045185	-
DeeUtilGlobalRootDaemon.1045188	-
DeeUtilLocalRootDaemon.1045191	-
DeeatCAgent.1041553	-
DeeatCCoord.1041547	-
DialPlanProcess.1101962	Caches configuration tables of Dial Plan, Barring Programs and CAC Connection Limit at MTAS start and implements to match the input number against the different cached tables.
DiameterInstallerProc.1060881	Diameter installer process
DiameterInstallerShProc.1101088	Diameter installer Sh process
DicosAppTraceMO_PT.1044688	Dicos application trace Managed Object
DoamEventProcess.1109439	-
FilterHandlerProcess.1117544	-
H248ProcessNew.1101915	H248 process



Process Type	Description or Comment
H248TransportProcessTypeNew.1101945	H.248 transport process
HTTP_TransportProc.1105060	HTTP process
HeadProcessNew.1101927	Head process
HttpDistributorProcessNew.1101918	-
ICMP_Traffic_Proc.1105036	-
ImrnAllocatorProcess.1101646	Imrn allocator process
JIM_InstallerProcess.555481	-
JIM_ServerProcess.555497	-
MomCMInstallerProcess.1060808	Mom configuration installer process
ModelHandlerProcess.1117166	-
MProfSrvProc_PT.1101281	-
MTASPBxProcess.SWI_StPbxProcess	Responsible for incrementing/decrementing SIP Trunking Call Admission Control (CAC) counters on PBX level and for controlling if CAC limits have been reached or not.
NUMANA_ConfigSyncProc.1105198	-
NUMANA_OamInstallerProc.1105203	-
NUMANA_Proc.1105183	-
NumberTranslationProcess.1119085	Number translation process
OamProcess.1060627	At initial startup, the subsystem instantiates the MIB (MOM) and connects to the license server and periodically checks license status.
PotAuditProcess.1101244	Pot audit process
PbxProcess.1126156	-
PmCollector.1117076	-
SS7DistributorProcess.1101552	SS7DistributorProcess receives and sends CAP messages.
SS7MapDistributorProcess.1119989	Responsible for handling SS7/MAP communication.
SctpOamProcess.1101098	SCTP OAM process
ShNotifyProcessNew.1101930	Sh notify process
ShRequestProcessNew.1101921	Sh request process
SipDistributorProcessNew.1101932	SIP distributor process
SipWorkerProcess.1126164	SIP distributor worker process
SubscriberDataControlProcess.1126150	Subscriber data process
SubscriberDataOamProcess.1061067	Subscriber data OAM process
TimerProcessNew.1101935	Timer process
vDicosLdapInstallerProcess.1127011	-
XdmsDiameterDistributor_PT.1101094	XDMS Diameter distribution process
XdmsDiameterInstallerProc.1061368	Process on vDicos that runs the code for initializing the XDMS instance of the Diameter stack.
XdmsLinuxServer_PT.1101006	XDMS Linux server process



Available Common Components (CMCOs) processes are listed in the following table:

Process Type	Description or Comment
CMCO_UtcOffsetMgrProc_PT.1105704	-
CARSEL_CsProc.1084367	Handles Carrier Select functions used by the MTAS.
CARSEL_DsaProc.1084423	Handles Carrier Select functions used by the MTAS.
CARSEL_OamInstallerProc.1084373	Handles Carrier Select functions used by the MTAS.
CARSEL_ConfigSyncProc.1084447	Handles Carrier Select functions used by the MTAS.
DnsCacheProc.1041760	Handles DNS server functions used by the MTAS.
DnsTransportProc.1042512	Handles DNS server functions used by the MTAS.
DnsApplInstallProc.1041869	Handles DNS server functions used by the MTAS.
HTTP_TransportProc.1105060	Handles HTTP transport functions used by the MTAS.
ICMP_ControllerProc.1084198	Handles the creation and removal of the ICMP sockets.
ICMP_OamInstallerProc.1084211	Runs the code for initializing the ICMP Framework data.
ICMP_OamInstallerProc.1084211	Runs the code for initializing the ICMP Framework data.
Ipmm_NumberNormalization_Proc.1041857	Handles the Number Normalization function used by the MTAS.
IpmmNumNormOamInstallerProc.1041979	Handles the Number Normalization function used by the MTAS.
IpmmNumNormConfigSyncProc.1105066	Handles the Number Normalization function used by the MTAS.







## 5 AppTrace Domains in MTAS

To collect trace output from a trace domain, the name of the domain is added to the trace session as shown in Section 7 on page 37. A subset of AppTrace domains and domain groups in the MTAS are listed in the following table:

**Note:** Select the MTAS trace domains with four levels in the AppTrace session. Example: `ims.mtas.sip.*`.

Domain	Description or Comment
<code>ims.mtas.ccmp.dispatcher</code>	This trace domain handles traces on the <code>ccmpDispatcher</code> . Centralized Conferencing Manipulation Protocol
<code>ims.mtas.charging.common</code>	This trace domain handles traces on commonly used functions for Charging.
<code>ims.mtas.common.common</code>	This trace domain handles the common parts.
<code>ims.mtas.common.headprocess</code>	This trace domain exists in only one instance. It supervises the processors to detect added, removed, or restarted processors, and provides the overall control of small restarts and the overall control of the actions required as a result of changes to the administrative states.
<code>ims.mtas.common.nc</code>	This trace domain handles the traces for Node control.
<code>ims.mtas.common.timers</code>	This trace domain handles the traces for Timers.
<code>ims.mtas.common.trace</code>	This trace domain contains the MTAS trace.
<code>ims.mtas.common.utils</code>	This trace domain handles traces on commonly used functions.
<code>ims.mtas.csi.applicationprocess</code>	This trace domain handles traces in the CSI subsystem for CAMEL interaction steps done in the application process. Typically activated together with <code>ims.mtas.csi.common</code> , <code>ims.mtas.csi.staticprocess</code> , and <code>ims.mtas.services.ncc</code> .
<code>ims.mtas.csi.common</code>	This trace domain handles traces in the CSI subsystem for CAMEL interaction steps done in the <code>SS7DistributorProcess</code> and Application process. Typical activated together with <code>ims.mtas.csi.staticprocess</code> , <code>ims.mtas.csi.applicationprocess</code> , and <code>ims.mtas.services.ncc</code> .
<code>ims.mtas.csi.staticprocess</code>	This trace domain handles traces in the CSI subsystem for CAMEL interaction steps done in the <code>SS7DistributorProcess</code> . Typically activated together with <code>ims.mtas.csi.common</code> , <code>ims.mtas.csi.applicationprocess</code> , and <code>ims.mtas.services.ncc</code> .
<code>ims.mtas.errlog.diam.rf</code>	This trace domain handles traces of the Error responses and Reason phrases for Diameter on the RF interface.
<code>ims.mtas.errlog.diam.ro</code>	This trace domain handles traces of the Error responses and Reason phrases for Diameter on the Ro interface.
<code>ims.mtas.errlog.diam.sh</code>	This trace domain handles traces of the Error responses and Reason phrases for Diameter on the SH interface.
<code>ims.mtas.errlog.h248</code>	This trace domain handles traces of the Error responses and Reason phrases on the H.248 interface.
<code>ims.mtas.errlog.sip</code>	This trace domain handles traces of the Error responses and Reason phrases on the SIP interface
<code>ims.mtas.if.http</code>	This trace domain handles traces on the HTTP interface.
<code>ims.mtas.if.mr</code>	This trace domain handles traces on the Mr interface.
<code>ims.mtas.if.mrfc</code>	This trace domain handles traces on the MRFC interface.
<code>ims.mtas.if.namedb</code>	This trace domain handles traces on the Name DB interface.
<code>ims.mtas.if.rx</code>	This trace domain handles traces on the online charging interface.
<code>ims.mtas.if.sh</code>	This trace domain handles traces on the SH interface.



Domain	Description or Comment
ims.mtas.if.sip	This trace domain handles traces on the SIP interface.
ims.mtas.log.start	This trace domain starts forlop tracing.
ims.mtas.memory	This trace domain handles traces about memory use information by Application Process.
ims.mtas.mrfc.additionalmediaresource	This trace domain handles the traces on the media framework towards MRFC for additional media resource.
ims.mtas.mrfc.h248stack	This trace domain handles the traces on the H.248 stack.
ims.mtas.mrfc.mediafw	This trace domain handles the traces on the media framework towards MRFC.
ims.mtas.netio.info	This trace domain handles the traces for NetTrace on maximum level in human readable format.
ims.mtas.netio.rx	This trace domain handles the traces for NetTrace on maximum level in human readable format.
ims.mtas.netio.sip	This trace domain handles the traces for NetTrace, SIP signalling trace on maximum level in human readable format.
ims.mtas.netio.tx	This trace domain handles the traces for NetTrace on maximum level in human readable format.
ims.mtas.nettrace.info	This trace domain handles the traces for NetTrace on maximum level in machine-readable format as defined by 3GPP.
ims.mtas.nettrace.init	This trace domain handles the traces for NetTrace on maximum level in machine-readable format as defined by 3GPP.
ims.mtas.nettrace.rx	This trace domain handles the traces for NetTrace on maximum level in machine-readable format as defined by 3GPP.
ims.mtas.nettrace.sip	This trace domain handles the traces for NetTrace, SIP signalling trace on maximum level in machine-readable format as defined by 3GPP.
ims.mtas.nettrace.tx	This trace domain handles the traces for NetTrace on maximum level in machine-readable format as defined by 3GPP.
ims.mtas.oam.3pty	This trace domain handles the traces on configuration attributes for three-party.
ims.mtas.oam.abdial	This trace domain handles the traces on configuration attributes for Abbreviated Dialing.
ims.mtas.oam.aoc	This trace domain handles the traces on configuration attributes for Advise Of Charge.
ims.mtas.oam.ap	This trace domain handles the traces on configuration attributes for aggregation proxy.
ims.mtas.oam.asiw	This trace domain handles the traces on configuration attributes for application server interworking.
ims.mtas.oam.cac	This trace domain traces on configuration attributes for Call Admission Control.
ims.mtas.oam.cb	This trace domain traces on configuration attributes for Communication Barring.
ims.mtas.oam.cc	This trace domain handles traces on configuration attributes for Call Completion.
ims.mtas.oam.cdiv	This trace domain handles traces on configuration attributes for call diversion.
ims.mtas.oam.charging	This trace domain handles traces on configuration attributes for Charging.
ims.mtas.oam.comdetails	This trace domain handles traces on configuration attributes for Communication details.
ims.mtas.oam.common	This trace domain handles traces on configuration attributes for commonly used parts.
ims.mtas.oam.conf	This trace domain handles traces on configuration attributes for Conference.
ims.mtas.oam.cpc	This trace domain handles traces on configuration attributes for Call party category.
ims.mtas.oam.cps	This trace domain handles traces on configuration attributes for Carrier Pre-Select.
ims.mtas.oam.cr	This trace domain handles the traces on configuration attributes for call return
ims.mtas.oam.cs	This trace domain handles traces on configuration attributes for Carrier Select.
ims.mtas.oam.csi	This trace domain handles traces on configuration attributes for CSI subsystem, Circuit Switch Interworking.



Domain	Description or Comment
ims.mtas.oam.csvfb	This trace domain handles traces on configuration attributes for Carrier Select Video Fallback.
ims.mtas.oam.cug	This trace domain handles the traces on configuration attributes for close user group.
ims.mtas.oam.cw	This trace domain handles traces on configuration attributes for Communication Waiting.
ims.mtas.oam.dialplan	This trace domain handles traces on configuration attributes for Dial Plan.
ims.mtas.oam.dr	This trace domain handles the traces on configuration attributes for Distinctive Ring.
ims.mtas.oam.dtm	This trace domain handles traces on configuration attributes for Dial Tone Management.
ims.mtas.oam.ect	This trace domain handles traces on configuration attributes for Explicit Communication Transfer.
ims.mtas.oam.fcd	This trace domain handles traces on configuration attributes for Flexible Communication Distribution.
ims.mtas.oam.fsfs	This trace domain handles the traces on configuration attributes for file transfer
ims.mtas.oam.ga	This trace domain handles traces on configuration attributes for Generic Announcement.
ims.mtas.oam.gls	This trace domain handles traces on configuration attributes for Global Licensing Service.
ims.mtas.oam.gm	This trace domain handles traces on configuration attributes for Gateway Model.
ims.mtas.oam.hold	This trace domain handles traces on configuration attributes for hold.
ims.mtas.oam.hotline	This trace domain handles the traces on configuration attributes for hotline.
ims.mtas.oam.idpres	This trace domain handles traces on configuration attributes for Identity Presentation.
ims.mtas.oam.jc	This trace domain handles traces on configuration attributes for Japanese Charging.
ims.mtas.oam.mcid	This trace domain handles traces on configuration attributes for Malicious Communication Identification.
ims.mtas.oam.mmt	This trace domain handles traces on configuration attributes for Multimedia Telephony.
ims.mtas.oam.mrfc	This trace domain handles traces on configuration attributes for the MRFC.
ims.mtas.oam.na	This trace domain handles traces on configuration attributes for network announcement.
ims.mtas.oam.namedb	This trace domain handles traces on configuration attributes for nameDb.
ims.mtas.oam.ncc	This trace domain handles traces on configuration attributes for Northbound Call Control.
ims.mtas.oam.numnorm	This trace domain handles traces on configuration attributes for Number Normalization.
ims.mtas.oam.numport	This trace domain handles the traces on configuration attributes for Number Portability.
ims.mtas.oam.oct	This trace domain handles the traces on configuration attributes for Operator Controlled Transfer
ims.mtas.oam.priocall	This trace domain handles traces on configuration attributes for priority call.
ims.mtas.oam.px	This trace domain handles traces on configuration attributes for Parlay-X.
ims.mtas.oam.rbt	This trace domain handles the traces on configuration attributes for Ring Back Tone.
ims.mtas.oam.scc	This trace domain handles the traces on configuration attributes for Supplementary Service Code.
ims.mtas.oam.sds	This trace domain handles the traces on configuration attributes for Service Domain Selection.
ims.mtas.oam.sh	This trace domain handles traces on configuration attributes for SH.
ims.mtas.oam.sip	This trace domain handles traces on configuration attributes for SIP.
ims.mtas.oam.snd	This trace domain handles traces on configuration attributes for Short Number Dialing.
ims.mtas.oam.ssc	This trace domain handles traces on configuration attributes for supplementary service codes.
ims.mtas.oam.st	This trace domain handles traces on configuration attributes for STAS (SIP Trunking AS).
ims.mtas.oam.subscriberdata	This trace domain handles traces on configuration attributes for subscriber data.



Domain	Description or Comment
ims.mtas.oam.tads	This trace domain handles the traces on configuration attributes for Terminating Access Domain Selection.
ims.mtas.oam.vtp	This trace domain handles traces on configuration attributes for virtual
ims.mtas.oam.xdms	This trace domain handles traces on configuration attributes for XDMS.
ims.mtas.px.dispatcher	This trace domain handles traces on the pxDispatcher.
ims.mtas.services.3pty	This trace domain handles traces on the Three Party service.
ims.mtas.services.abdial	This trace domain handles traces on the Abbreviated Dialing service.
ims.mtas.services.aoc	This trace domain handles traces on the Advice of Charge service.
ims.mtas.services.asiw	This trace domain handles traces on the Application Server InterWorking service.
ims.mtas.services.cac	This trace domain handles traces on the Call Admission Control service.
ims.mtas.services.cat	This trace domain handles traces on the Customized Alerting Tones service.
ims.mtas.services.cb	This trace domain handles traces on the Communication Barring service.
ims.mtas.services.cc	This trace domain handles traces on the Call Completion service.
ims.mtas.services.cd	This trace domain handles traces on the Communication Distribution service.
ims.mtas.services.cdiv	This trace domain handles traces on the Communication Diversion service.
ims.mtas.services.charging	This trace domain handles traces on the Charging service.
ims.mtas.services.common	This trace domain handles traces on the commonly used functions for services.
ims.mtas.services.conf	This trace domain handles traces on the Conference service.
ims.mtas.services.conference	This trace domain handles traces on the Conference service.
ims.mtas.services.cpc	This trace domain handles traces on the Call party category service.
ims.mtas.services.cps	This trace domain handles traces on the Carrier Pre-Select service.
ims.mtas.services.cr	This trace domain handles traces on the Call Return service.
ims.mtas.services.cs	This trace domain handles traces on the Carrier Select service.
ims.mtas.services.csvfb	This trace domain handles traces on the Carrier Select Video Fallback service.
ims.mtas.services.cug	This trace domain handles traces on the Closed User Group service.
ims.mtas.services.cw	This trace domain handles traces on the Communication Waiting service.
ims.mtas.services.dbl	This trace domain handles traces on the Dynamic Black List service.
ims.mtas.services.dr	This trace domain handles traces on the Distinctive Ring service.
ims.mtas.services.dtm	This trace domain handles traces on the Dial Tone Management service.
ims.mtas.services.ect	This trace domain handles traces on the Explicit Communication Transfer services.
ims.mtas.services.emergencystate	This trace domain handles traces on the Emergency State service.
ims.mtas.services.flp	This trace domain handles traces on Scheduled Conference service.
ims.mtas.services.gls	This trace domain handles traces on the GLS service.
ims.mtas.services.gm	This trace domain handles traces on the Gateway Model service.
ims.mtas.services.hold	This trace domain handles traces on the Hold service.
ims.mtas.services.hotline	This trace domain handles traces on the hotline service.
ims.mtas.services.idpres	This trace domain handles traces on the Identity Presentation service.
ims.mtas.services.jc	This trace domain handles traces on the Japanese Charging service.



Domain	Description or Comment
ims.mtas.services.mcid	This trace domain handles traces on the Malicious Communication IDentification service.
ims.mtas.services.mmt	This trace domain handles traces on the Multimedia Telephony service.
ims.mtas.services.na	This trace domain handles traces on the Network Announcement service.
ims.mtas.services.ncc	This trace domain handles traces on the Northbound Call Control service.
ims.mtas.services.numbertranslation	This trace domain handles traces on the Number translation service.
ims.mtas.services.numnorm	This trace domain handles traces on the Number Normalization service.
ims.mtas.services.numport	This trace domain handles traces on the Number Portability service.
ims.mtas.services.ocb	This trace domain handles traces on the Outgoing Communication Barring service.
ims.mtas.services.oct	This trace domain handles traces on the Operator Controlled Transfer service.
ims.mtas.services.presence	This trace domain handles traces on the Presence Service.
ims.mtas.services.priocall	This trace domain handles traces on the Priority Call service.
ims.mtas.services.px3pcc	This trace domain handles traces on the Parlay-X Third-Party Call Control service.
ims.mtas.services.pxcn	This trace domain handles traces on the Parlay-X Common Name service.
ims.mtas.services.rbt	This trace domain handles traces on the Ring Back Tone service.
ims.mtas.services.scc	This trace domain handles traces on the Service Centralization and Continuity service.
ims.mtas.services.scn	This trace domain handles traces on the Subscriber Credit Notification service.
ims.mtas.services.sds	This trace domain handles traces on the Service Domain Selection service.
ims.mtas.services.servicefw	This trace domain handles traces on the Service Framework service.
ims.mtas.services.snd	This trace domain handles traces on the Short Number Dialing service.
ims.mtas.services.srvcc	This trace domain handles traces on the Single Radio Voice Call Continuity service.
ims.mtas.services.ssc	This trace domain handles traces on the Supplementary Service Codes service including the DICOS part of the Generic SSC feature.
ims.mtas.services.stod	This trace domain handles traces on the Session Transfer to Own Device service.
ims.mtas.services.subdata	This trace domain handles traces on the Subscriber Data service.
ims.mtas.services.tads	This trace domain handles traces on the Terminating Access Domain Selection service.
ims.mtas.services.uloc	This trace domain handles traces on the user location service.
ims.mtas.services.unreg	This trace domain handles traces on the unregistered Subscriber service.
ims.mtas.services.vm	This trace domain handles traces on the Voice Mail service.
ims.mtas.sip.dispatcher	This trace domain handles traces on the sipDispatcher.
ims.mtas.sip.distributor	This trace domain handles traces on the SipDistributor.
ims.mtas.sip.sipstack	This trace domain handles traces on the SIP stack.
ims.mtas.st.core	This trace domain handles traces in the core parts of the STAS (SIP Trunking AS).
ims.mtas.st.services	This trace domain handles traces for all services in ST AS.
ims.mtas.subscriberdata.conferencedata	This trace domain handles traces on the conference part of the subscriber data.
ims.mtas.subscriberdata.core	This trace domain handles traces on the core of subscriber data.
ims.mtas.subscriberdata.servicedata	This trace domain handles traces on the service data of the subscriber data.
ims.mtas.subscriberdata.servicenumdata	This trace domain handles traces on Number Normalization part of the subscriber data.
ims.mtas.subscriberdata.stasdata	This trace domain handles traces in the STAS (SIP Trunking AS) part of subscriber data.



Domain	Description or Comment
ims.mtas.subscriberdata.userdata	This trace domain handles traces on the user data of the subscriber data.
ims.mtas.tools.mprof	This trace domain handles traces on the Memory profiler.
ims.mtas.utils.potaudit	This trace domain handles traces on the POT Audit.
ims.mtas.xdms.cai3g	This trace domain handles traces on the CAI3G operator provisioning interface.
ims.mtas.xdms.ccmp	This trace domain handles traces for the CCMP interface.
ims.mtas.xdms.charging	This trace domain handles traces for Charging for Ut interface updates.
ims.mtas.xdms.dao	This trace domain handles traces for common functions for the XML service data access.
ims.mtas.xdms.dtm	This trace domain handles traces for the XDMS part of the Dial Tone Management feature.
ims.mtas.xdms.genssc	This trace domain handles traces for the XDMS part of the Generic SSC feature.
ims.mtas.xdms.license	This trace domain handles traces for XDMS licenses.
ims.mtas.xdms.misc	This trace domain handles traces for commonly used functions in XDMS.
ims.mtas.xdms.numnorm	This trace domain handles traces for XDMS Number Normalization.
ims.mtas.xdms.oam	This trace domain handles traces for O&M functions (configuration and performance management) within the XDMS.
ims.mtas.xdms.rules	This trace domain handles traces on application rule checks for the XML service data consistency.
ims.mtas.xdms.timings	This trace domain handles traces for timer code within the XDMS.
ims.mtas.xdms.trace	This trace domain handles traces for XDMS trace.
ims.mtas.xdms.triggers	This trace domain handles traces for trigger operation including triggering of Dial Tone Management (DTM).
ims.mtas.xdms.utility	This trace domain handles traces for commonly used utility support functions.
ims.mtas.xdms.xcap	This trace domain handles traces for the Ut XCAP interface for self-administration of XML service data.
ims.mtas.xdms.xconconferenceinfo	This trace domain handles traces for the XDMS part of the conference feature.
ims.mtas.xdms.xdp	This trace domain handles traces for inter-process communication within the XDMS.
ims.mtas.xdmsval.validation	This trace domain handles traces for XDMS validation.

## 5.1 Domain Parameters

The Msg parameter is available for all CMCO and most MTAS domains, exceptions are the ones listed.

Domain	Parameters
ims.mtas.netio.rx	Max level trace in human readable format \$Mild, \$MiVer, \$Length, \$Msg
ims.mtas.netio.tx	Max level trace in human readable format \$Mild, \$MiVer, \$Length, \$Msg
ims.mtas.nettrace.info	\$Mild, \$MiVer, \$Length, \$Msg
ims.mtas.nettrace.sip	\$Mild, \$MiVer, \$Length, \$Msg



Domain	Parameters
ims.mtas.nettrace.rx	Max level trace in machine-readable format as defined by 3GPP \$Mild, \$MiVer, \$Length, \$Msg
ims.mtas.nettrace.tx	Max level trace in machine-readable format as defined by 3GPP \$Mild, \$MiVer, \$Length, \$Msg
ims.mtas.errlog.sip	\$FromID, \$Response, \$Reason, \$SessSide
ims.mtas.errlog.h248	\$Response, \$Reason
ims.mtas.errlog.diam.sh	\$Response, FromID, \$Response, \$Reason
ims.mtas.errlog.diam.rf	\$FromID, \$Response, \$Reason, \$SessSide
ims.mtas.errlog.diam.ro	\$Reason, \$SessSide





## 6 Trace Profiles

Preconfigured trace profiles can be used for either a single session or a live system.

### 6.1 Trace Profiles for Single Session Software Trace

Table 1 shows the preconfigured trace profiles for a single session software trace:

*Table 1 Trace Profiles for Single Session Software Trace*

Profile Name	MtasProgressTrace43
Description	Dumps information about any user. <sup>(1)</sup>
Trace level	PROGRESS (43)

**Table 1** *Trace Profiles for Single Session Software Trace*

Processes	ApplicationProcess.SWI_ApplicationProcess H248ProcessNew.SWI_H248ProcessNew TimerProcessNew.SWI_TimerProcessNew DiameterInstallerProc.SWI_DiameterInstaller ChargingBackupHandlerProcNew.SWI_ChargingBackupHandlerProcNew HeadProcessNew.SWI_HeadProcessNew SubscriberDataOamProcess.SWI_SubscriberDataOamProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew ShRequestProcessNew.SWI_ShRequestProcessNew DiameterInstallerShProc.SWI_DiameterInstallerSh ShNotifyProcessNew.SWI_ShNotifyProcessNew ChargingProcess.SWI_ChargingProcess PotAuditProcess.SWI_PotAuditProcess H248TransportProcessTypeNew.SWI_H248TransportProcessTypeNew HttpDistributorProcessNew.SWI_HttpDistributorProcessNew ImsAsXdms_PT.OU_ImsAsXdms MomCMIInstallerProcess.SWI_MomCMIInstaller SS7DistributorProcess.SWI_SS7DistributorProcess XdmsDiameterDistributor_PT.OU_XdmsDiameterDistributor XdmsLinuxServer_PT.OU_XdmsLinuxServer OamProcess.SWI_OamProcess AcrStorageHandlerProc.SWI_AcrStorageHandlerProc XdmsDiameterInstallerProc.OU_XdmsDiameterInstaller NumberTranslationProcess.SWI_NumberTranslationProcess CarrierSelectDataProcess.SWI_CarrierSelectDataProcess DialPlanProcess.SWI_DialPlanProcess ImrnAllocatorProcess.SWI_ImrnAllocatorProcess PbxProcess.SWI_StPbxProcess SS7MapDistributorProcess.SWI_SS7MapDistributorProcess SS7ReporterProcess.SWI_SS7ReporterProcess SipWorkerProcess.SWI_SipWorkerProcess SubscriberDataControlProcess.SWI_SubscriberDataControlProcess SctpOamProcess.SWI_SctpOamProcess
-----------	---



**Table 1** Trace Profiles for Single Session Software Trace

Domains	ims.mtas.ccmp.dispatcher ims.mtas.charging.common ims.mtas.common.* ims.mtas.csi.* ims.mtas.errlog.diam.sh ims.mtas.errlog.diam.rf ims.mtas.errlog.diam.ro ims.mtas.errlog.h248 ims.mtas.errlog.sip ims.mtas.if.* ims.mtas.mrfc.* ims.mtas.oam.* ims.mtas.px.dispatcher ims.mtas.services.* ims.mtas.sip.* ims.mtas.st.* ims.mtas.subscriberdata.* ims.mtas.utils.* ims.mtas.tools.mprof ims.mtas.xdms.* ims.mtas.xdmsval.validation
Profile Name	MtasLoggingOfErrorResponsesDebug55
Description	Dumps information about the Error Responses received on the H.248, Rf, Ro, Sh, and SIP interfaces and debug traces.
Trace level	DEBUG (55)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew ShNotifyProcessNew.SWI_ShNotifyProcessNew ChargingProcess.SWI_ChargingProcess H248ProcessNew.SWI_H248ProcessNew H248TransportProcessNew.SWI_H248TransportProcessNew

**Table 1** *Trace Profiles for Single Session Software Trace*

Domains	ims.mtas.charging.common ims.mtas.common.common ims.mtas.common.utils ims.mtas.errlog.diam.rf ims.mtas.errlog.diam.ro ims.mtas.errlog.diam.sh ims.mtas.errlog.h248 ims.mtas.errlog.sip ims.mtas.if.* ims.mtas.sip.dispatcher ims.mtas.sip.distributor
Profile Name	MtasUserTraceforFromID56, MtasUserTraceToID56, or MtasUserTraceforFromIDandToID56
Description	Dumps information about a particular user or users.
Trace level	FORLOP (56)
Processes	ApplicationProcess.SWI_ApplicationProcess
Domains	ims.mtas.common.common ims.mtas.sip.dispatcher ims.mtas.services.* ims.mtas.st.*
Profile Name	MtasDebugTrace55
Description	Dumps information about any user. <sup>(1)</sup>
Trace level	DEBUG (55)



**Table 1** Trace Profiles for Single Session Software Trace

Processes	ApplicationProcess.SWI_ApplicationProcess H248ProcessNew.SWI_H248ProcessNew TimerProcessNew.SWI_TimerProcessNew DiameterInstallerProc.SWI_DiameterInstaller ChargingBackupHandlerProcNew.SWI_ChargingBackupHandlerProcNew HeadProcessNew.SWI_HeadProcessNew SubscriberDataOamProcess.SWI_SubscriberDataOamProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew ShRequestProcessNew.SWI_ShRequestProcessNew DiameterInstallerShProc.SWI_DiameterInstallerSh ShNotifyProcessNew.SWI_ShNotifyProcessNew ChargingProcess.SWI_ChargingProcess PotAuditProcess.SWI_PotAuditProcess H248TransportProcessTypeNew.SWI_H248TransportProcessTypeNew HttpDistributorProcessNew.SWI_HttpDistributorProcessNew ImsAsXdms_PT.OU_ImsAsXdms MomCMInstallerProcess.SWI_MomCMInstaller SS7DistributorProcess.SWI_SS7DistributorProcess XdmsDiameterDistributor_PT.OU_XdmsDiameterDistributor XdmsLinuxServer_PT.OU_XdmsLinuxServer OamProcess.SWI_OamProcess AcrStorageHandlerProc.SWI_AcrStorageHandlerProc XdmsDiameterInstallerProc.OU_XdmsDiameterInstaller NumberTranslationProcess.SWI_NumberTranslationProcess CarrierSelectDataProcess.SWI_CarrierSelectDataProcess DialPlanProcess.SWI_DialPlanProcess ImrnAllocatorProcess.SWI_ImrnAllocatorProcess PbxProcess.SWI_StPbxProcess SS7MapDistributorProcess.SWI_SS7MapDistributorProcess SS7ReporterProcess.SWI_SS7ReporterProcess SipWorkerProcess.SWI_SipWorkerProcess SubscriberDataControlProcess.SWI_SubscriberDataControlProcess SctpOamProcess.SWI_SctpOamProcess
-----------	---

**Table 1** *Trace Profiles for Single Session Software Trace*

Domains	ims.mtas.errlog.sip ims.mtas.errlog.h248 ims.mtas.errlog.diam.sh ims.mtas.errlog.diam.rf ims.mtas.errlog.diam.ro ims.mtas.common.* ims.mtas.charging.common ims.mtas.if.* ims.mtas.ccmp.dispatcher ims.mtas.services.* ims.mtas.px.dispatcher ims.mtas.csi.* ims.mtas.mrfc.* ims.mtas.oam.* ims.mtas.sip.* ims.mtas.subscriberdata.* ims.mtas.utils.* ims.mtas.xdms.* ims.mtas.xdmsval.validation ims.mtas.tools.mprof ims.mtas.st.*
Profile Name	MtasSCCASTrace55
Description	Dumps information about any user in SCC AS
Trace level	DEBUG (55)



**Table 1** Trace Profiles for Single Session Software Trace

Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew SS7DistributorProcess.SWI_SS7DistributorProcess SS7MapDistributorProcess.SWI_SS7MapDistributorProcess
Domains	ims.mtas.charging.common ims.mtas.common.common ims.mtas.common.utils ims.mtas.errlog.sip ims.mtas.errlog.diam.sh ims.mtas.errlog.diam.rf ims.mtas.if.sh ims.mtas.services.common ims.mtas.services.scc ims.mtas.services.sds ims.mtas.services.servicefw ims.mtas.services.srvcc ims.mtas.services.subdata ims.mtas.services.tads ims.mtas.csi.* ims.mtas.sip.* ims.mtas.subscriberdata.*

(1) Only recommended to be used for single session.

## 6.2 Trace Profiles for Live System Software Trace

Table 2 shows the preconfigured trace profiles for a live system software trace:

**Table 2** Trace Profiles for Live Stream Software Trace

Profile Name	MtasWarningTrace36
Description	Dumps information about unexpected events and EventHistory.
Trace level	WARNING (36)

**Table 2** *Trace Profiles for Live Stream Software Trace*

Processes	ApplicationProcess.SWI_ApplicationProcess H248ProcessNew.SWI_H248ProcessNew TimerProcessNew.SWI_TimerProcessNew DiameterInstallerProc.SWI_DiameterInstaller ChargingBackupHandlerProcNew.SWI_ChargingBackupHandlerProcNew HeadProcessNew.SWI_HeadProcessNew SubscriberDataOamProcess.SWI_SubscriberDataOamProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew ShRequestProcessNew.SWI_ShRequestProcessNew DiameterInstallerShProc.SWI_DiameterInstallerSh ShNotifyProcessNew.SWI_ShNotifyProcessNew ChargingProcess.SWI_ChargingProcess PotAuditProcess.SWI_PotAuditProcess H248TransportProcessTypeNew.SWI_H248TransportProcessTypeNew HttpDistributorProcessNew.SWI_HttpDistributorProcessNew ImsAsXdms_PT.OU_ImsAsXdms MomCMIInstallerProcess.SWI_MomCMIInstaller SS7DistributorProcess.SWI_SS7DistributorProcess XdmsDiameterDistributor_PT.OU_XdmsDiameterDistributor XdmsLinuxServer_PT.OU_XdmsLinuxServer OamProcess.SWI_OamProcess AcrStorageHandlerProc.SWI_AcrStorageHandlerProc XdmsDiameterInstallerProc.OU_XdmsDiameterInstaller NumberTranslationProcess.SWI_NumberTranslationProcess CarrierSelectDataProcess.SWI_CarrierSelectDataProcess DialPlanProcess.SWI_DialPlanProcess ImrnAllocatorProcess.SWI_ImrnAllocatorProcess PbxProcess.SWI_StPbxProcess SS7MapDistributorProcess.SWI_SS7MapDistributorProcess SS7ReporterProcess.SWI_SS7ReporterProcess SipWorkerProcess.SWI_SipWorkerProcess SubscriberDataControlProcess.SWI_SubscriberDataControlProcess SctpOamProcess.SWI_SctpOamProcess
-----------	---





**Table 2** Trace Profiles for Live Stream Software Trace

Domains	ims.mtas.errlog.sip ims.mtas.errlog.h248 ims.mtas.errlog.diam.sh ims.mtas.errlog.diam.rf ims.mtas.errlog.diam.ro ims.mtas.common.* ims.mtas.charging.common ims.mtas.if.* ' ims.mtas.ccmp.dispatcher ims.mtas.services.* ims.mtas.px.dispatcher ims.mtas.csi.* ims.mtas.mrfc.* ims.mtas.oam.* ims.mtas.sip.* ims.mtas.subscriberdata.* ims.mtas.utils.* ims.mtas.xdms.* ims.mtas.xdmsval.validation ims.mtas.tools.mprof ims.mtas.st.*
Profile Name	MtasLoggingOfErrorResponses40
Description	Dumps information about the Error Responses received on the H.248, Rf, Ro, Sh, and SIP interfaces.
Trace level	40
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew ShNotifyProcessNew.SWI_ShNotifyProcessNew ChargingProcess.SWI_ChargingProcess H248ProcessNew.SWI_H248ProcessNew H248TransportProcessNew.SWI_H248TransportProcessNew
Domains	ims.mtas.errlog.sip ims.mtas.errlog.h248 ims.mtas.errlog.diam.sh ims.mtas.errlog.diam.rf ims.mtas.errlog.diam.ro
Profile Name	MtasProtocolTimeoutTrace41

**Table 2** *Trace Profiles for Live Stream Software Trace*

Description	Dumps information about unexpected events provided by MTAS.
Trace level	PROTOCOL_TIMEOUT (41)
Processes	ApplicationProcess.SWI_ApplicationProcess H248ProcessNew.SWI_H248ProcessNew TimerProcessNew.SWI_TimerProcessNew DiameterInstallerProc.SWI_DiameterInstaller ChargingBackupHandlerProcNew.SWI_ChargingBackupHandlerProcNew HeadProcessNew.SWI_HeadProcessNew SubscriberDataOamProcess.SWI_SubscriberDataOamProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew ShRequestProcessNew.SWI_ShRequestProcessNew DiameterInstallerShProc.SWI_DiameterInstallerSh ShNotifyProcessNew.SWI_ShNotifyProcessNew ChargingProcess.SWI_ChargingProcess PotAuditProcess.SWI_PotAuditProcess H248TransportProcessTypeNew.SWI_H248TransportProcessTypeNew HttpDistributorProcessNew.SWI_HttpDistributorProcessNew ImsAsXdms_PT.OU_ImsAsXdms MomCMInstallerProcess.SWI_MomCMInstaller SS7DistributorProcess.SWI_SS7DistributorProcess XdmsDiameterDistributor_PT.OU_XdmsDiameterDistributor XdmsLinuxServer_PT.OU_XdmsLinuxServer OamProcess.SWI_OamProcess AcrStorageHandlerProc.SWI_AcrStorageHandlerProc XdmsDiameterInstallerProc.OU_XdmsDiameterInstaller NumberTranslationProcess.SWI_NumberTranslationProcess CarrierSelectDataProcess.SWI_CarrierSelectDataProcess DialPlanProcess.SWI_DialPlanProcess ImrnAllocatorProcess.SWI_ImrnAllocatorProcess PbxProcess.SWI_StPbxProcess SS7MapDistributorProcess.SWI_SS7MapDistributorProcess SS7ReporterProcess.SWI_SS7ReporterProcess SipWorkerProcess.SWI_SipWorkerProcess SubscriberDataControlProcess.SWI_SubscriberDataControlProcess SctpOamProcess.SWI_SctpOamProcess



**Table 2** Trace Profiles for Live Stream Software Trace

Domains	ims.mtas.errlog.sip ims.mtas.errlog.h248 ims.mtas.errlog.diam.sh ims.mtas.errlog.diam.rf ims.mtas.errlog.diam.ro ims.mtas.common.* ims.mtas.charging.common ims.mtas.if.* ims.mtas.ccmp.dispatcher ims.mtas.services.* ims.mtas.px.dispatcher ims.mtas.csi.* ims.mtas.mrfc.* ims.mtas.oam.* ims.mtas.sip.* ims.mtas.subscriberdata.* ims.mtas.utils.* ims.mtas.xdms.* ims.mtas.xdmsval.validation ims.mtas.tools.mprof ims.mtas.st.*

## 6.3 Trace Profiles for Single Session Network Trace

Table 3 shows the preconfigured trace profiles for a single session network trace:

**Table 3** Trace Profiles for Single Session Network Trace

Profile Name	MtasNetIoMinLevelOrigUser56
Description	NetTrace, SIP signalling trace on minimum level including debug traces in human readable format.
Trace level	FORLOP (56)
Processes	ApplicationProcess.SWI_ApplicationProcess ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew

**Table 3** *Trace Profiles for Single Session Network Trace*

Domains	ims.mtas.netio.info ims.mtas.netio.sip ims.mtas.common.utils ims.mtas.sip.dispatcher ims.mtas.sip.distributor ims.mtas.common.common
Profile Name	MtasNetIoMaxLevelOrigUser56
Description	NetTrace, SIP signalling trace on maximum level including debug traces in human readable format.
Trace level	FORLOP (56)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.netio.info ims.mtas.netio.rx ims.mtas.netio.tx ims.mtas.common.utils ims.mtas.sip.dispatcher ims.mtas.sip.distributor ims.mtas.common.common
Profile Name	MtasNetTraceMinLevelOrigUser56
Description	NetTrace, SIP signalling trace on minimum level including debug traces.
Trace level	FORLOP (56)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.nettrace.info ims.mtas.nettrace.sip ims.mtas.common.utils ims.mtas.sip.dispatcher ims.mtas.sip.distributor ims.mtas.common.common
Profile Name	MtasNetTraceMaxLevelOrigUser56
Description	NetTrace, SIP signalling trace on maximum level including debug traces.
Trace level	FORLOP (56)



**Table 3** Trace Profiles for Single Session Network Trace

Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.nettrace.info ims.mtas.nettrace.rx ims.mtas.nettrace.tx ims.mtas.common.utils ims.mtas.sip.dispatcher ims.mtas.sip.distributor ims.mtas.common.common

## 6.4 Trace Profiles for Live System Network Trace

Table 3 shows the preconfigured trace profiles for a live system network trace:

**Table 4** Trace Profiles for Live System Network Trace

Profile Name	MtasNetIoMinLevelOrigUser23
Description	NetTrace, SIP signalling trace on minimum level in human readable format
Trace level	MAJOR (23)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.netio.info ims.mtas.netio.sip
Profile Name	MtasNetIoMaxLevelOrigUser23
Description	NetTrace, SIP signalling trace on maximum level in human readable format.
Trace level	MAJOR (23)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.netio.info ims.mtas.netio.rx ims.mtas.netio.tx
Profile Name	MtasNetIoMinLevelTermUser23
Description	NetTrace, SIP signalling trace on minimum level in human readable format.
Trace level	MAJOR (23)
Processes	ApplicationProcess.SWI_ApplicationProcess DistributorProcessNew.SWI_SipDistributorProcessNew

**Table 4** *Trace Profiles for Live System Network Trace*

Domains	ims.mtas.netio.info ims.mtas.netio.sip
Profile Name	MtasNetIoMaxLevelTermUser23
Description	NetTrace, SIP signalling trace on maximum level in human readable format.
Trace level	MAJOR (23)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.netio.info ims.mtas.netio.rx ims.mtas.netio.tx
Profile Name	MtasNetIoMinLevelOrigUserTermUser23
Description	NetTrace, SIP signalling trace on minimum level in human readable format.
Trace level	MAJOR (23)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.netio.info ims.mtas.netio.sip
Profile Name	MtasNetTraceMaxLevelOrigUser23
Description	NetTrace, SIP signalling trace on maximum level in machine-readable format
Trace level	MAJOR (23)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.nettrace.info ims.mtas.nettrace.rx ims.mtas.nettrace.tx
Profile Name	MtasNettraceMinLevelTermUser23
Description	NetTrace, SIP signalling trace on minimum level in machine-readable format as defined by 3GPP.
Trace level	MAJOR (23)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.nettrace.info ims.mtas.nettrace.sip
Profile Name	MtasNettraceMaxLevelTermUser23



**Table 4** Trace Profiles for Live System Network Trace

Description	NetTrace, SIP signalling trace on maximum level in machine-readable format as defined by 3GPP.
Trace level	MAJOR (23)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.nettrace.info ims.mtas.nettrace.rx ims.mtas.nettrace.tx
Profile Name	MtasNettraceMinLevelOrigAndTerm23
Description	NetTrace, SIP signalling trace on minimum level in machine-readable format as defined by 3GPP. Used for tracing call between specific users A and B.
Trace level	MAJOR (23)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.nettrace.info ims.mtas.nettrace.sip
Profile Name	MtasNettraceMaxLevelOrigAndTerm23
Description	NetTrace, SIP signalling trace on maximum level in machine-readable format as defined by 3GPP. Used for tracing call between specific users A and B.
Trace level	MAJOR (23)
Processes	ApplicationProcess.SWI_ApplicationProcess SipDistributorProcessNew.SWI_SipDistributorProcessNew
Domains	ims.mtas.nettrace.info ims.mtas.nettrace.rx ims.mtas.nettrace.tx







## 7 Example

As an example on how to start AppTrace, do the following:

**Note:** The different processes and domains in the MTAS are shown in Section 4 on page 9 and Section 5 on page 13.

1. Log on to any of the payloads in the cluster (PL-3 in the example below):  
ssh PL-3.
2. Go to the AppTrace directory and start a new session:

```
cd /opt/lpmsv/bin/appttrace
./collect_domains.sh
./verify_domains.sh
```

Output example:

```
.....
ims.mtas.sip[abstract|OK]
ims.mtas.sip.dispatcher[concrete|OK]
ims.mtas.sip.distributor[concrete|OK]
ims.mtas.sip.sipstack[concrete|OK]
.....
SUMMARY: All domains verified OK
AppTrace verify_domains done
```

3. Begin the AppTrace session:

```
./begin_session.sh
```

Output example:

```
AppTrace begin_session done sessionId: 1264422676
```

4. Trace on all processors (alternatively, specify the processor to be traced):

```
./include_processors.sh -a
```

Output example:

```
Result from [.lpmsv.director.tutil]:AppTrace include_processors done
```

5. Add process types:

```
add_process_type <PT1>[<PT2>...]
```



For example:

```
./add_process_type.sh ApplicationProcess.1060633
```

Output example:

```
AppTrace add_process_type done
```

## 6. Add domains:

For forlop tracing insert:

```
./insert_expression.sh ims.mtas.log.start\ (seek\ (string\ (<user@domain>\), \ $FromID\)\) \=> \ $forlop\=> \ $forlop_set
```

For example:

```
./insert_expression.sh ims.mtas.log.start\ (seek\ (string\ (7888005@\\), \ $FromID\)\) \=> \ $forlop\=> \ $forlop_set
```

For all other MTAS domains, insert:

```
./insert_expression.sh ims.mtas.sip.*
```

For example:

```
./insert_expression.sh ims.mtas.sip.* \=> L\ (\ $id, \ $forlop, \ $Msg\)
```

Output example:

```
===Trace Program(simplified)===
```

```
[0]:ims.mtas.info
[1]:ims.mtas.log.start
[2]:ims.mtas.sip.dispatcher
[3]:ims.mtas.sip.distributor
[4]:ims.mtas.sip.sipstack
AppTrace insert_expression done
```

For subscriber-specific domains, insert:

```
./insert_expression.sh ims.mtas.errlog.sip \ (\ $forlop \!= 0\)\ \=> L\ (\ $processorname, \ $pid, \ $date, \ $time, \ $id, \ $forlop, \ $FromID, \ $Response, \ $Reason, \ $SessSide\)
```

Output example:

```
===Trace Program(simplified)===
[0]:ims.mtas.info
[1]:ims.mtas.log.start
```



```
[2]:ims.mtas.sip.dispatcher
[3]:ims.mtas.sip.distributor
[4]:ims.mtas.sip.sipstack
[5]:ims.mtas.errlog.sip AppTrace insert_expression done
```

**Note:** Output example [0]:ims.mtas.info, gives all trace variables.

To see all domains, enter:

```
./ls_domains.sh
```

To see all subdomains for a specific domain, enter the following (this is an example of the domain **ims.mtas.sip.\***):

```
./cat_domain.sh ims.mtas.sip
```

Output example:

Result from [.lpmsv.director.tutil]:

```
=====
---Domain ims.mtas.sip---
---Condition: [abstract|OK]
---Signatures:
---Output prefix:
---Parameter Types:NONE
---Parameter Names:
NONE
---Parameter Postfixes:
NONE
---Subdomains:
Subdomain:ims.mtas.sip.dispatcher
Subdomain:ims.mtas.sip.distributor
Subdomain:ims.mtas.sip.sipstack
---Errors:
NONE
```

## 7. Execute the AppTrace session:

```
./route_output.sh console
```

Output example:

AppTrace route\_output command done

```
./display_session.sh
```

Output example:

Result from [.lpmsv.director.tutil]:

```
---Session 1414676139 is OPEN for editing
---general state:Clean
---Included processors:
```



```

SC-1
---Enable process types:
ApplicationProcess.1060633/1060633 located on:
SC-1
---Enable process instances:
NONE
---Trace program:

[0] ims.mtas.log.start() => L
Compiled: 1=>L($[0:48,0], $[0:0,0], $[0:1,0], $2)
[1] ims.mtas.log.start(seek(string(7888005@),$FromID))
=> L
Compiled: seek([_7888005@],$[0:0,0])=>L($[0:48,0],
$[0:0,0], $[0:1,0], $2)
[2] ims.mtas.log.start(seek(string(7888005@),$FromID))
=> L
Compiled: seek([_7888005@],$[0:0,0])=>L($[0:48,0],
$[0:0,0], $[0:1,0], $2)
[3] ims.mtas.sip.dispatcher() => L
Compiled: 1=>L($[0:48,0], $[0:0,0])
[4] ims.mtas.sip.distributor() => L
Compiled: 1=>L($[0:48,0], $[0:0,0])
[5] ims.mtas.sip.sipstack() => L
Compiled: 1=>L($[0:48,0], $[0:0,0])
[6] ims.mtas.sip.dispatcher() => L
Compiled: 1=>L($[0:48,0], $[0:0,0])
[7] ims.mtas.sip.distributor() => L
Compiled: 1=>L($[0:48,0], $[0:0,0])
[8] ims.mtas.sip.sipstack() => L
Compiled: 1=>L($[0:48,0], $[0:0,0])
---Routing of output:
To (buffered) console. Bytes/sec max:25000.
BuffSize/processor: 16384.
AppTrace display_session done

```

## 8. Upload the AppTrace session:

```
./upload_session.sh
```

Output example:

```

====Upload Session====
====Enabling Processes====
AppTrace upload_session done

```

## 9. Start tracing, for example, level DEBUG (55):

```
./start_trace.sh 56
```

Output example:



```
Trace level is 56 [trace events in ranges:  debug,
minor, major, and exceptional]
====Starting Trace====
AppTrace start_trace done
```

Output of the trace shows in the console logs.

Output example:

```
2014-10-30 15:02:21.760 APP-TRACE: id:"ims.mtas.sip.
dispatcher"
Msg:"2014-10-30 14:02:21.749 DEBUG
SipDispatcher.cc:773
SC-1 167 ApplicationProcess 00| mKey = [sip:A-TC_TCP_
LMCOIR0010@ericsson.com] "
```

10. Stop the AppTrace session:

```
./stop_trace.sh

./unload_session.sh

./end_session.sh
```

The Console logs are stored in the `/cluster/storage/no-backup/cdclsv/log/lpmsv` directory. For more information about console logs, see *MTAS Logs*.