

# Delete Scheduled Event

---

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2016. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Prerequisites	1
<b>2</b>	<b>Procedure</b>	<b>3</b>



Delete Scheduled Event



# 1 Introduction

This document describes how to delete a scheduled event. Deleting a scheduled event prevents the associated scheduled backups from occurring.

A scheduled event can be deleted when no longer needed due to, for example, a new preventive maintenance strategy.

## 1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

### 1.1.1 Conditions

The following conditions must apply:

- The backup type is known.
- The scheduled event type is known, that is, `BrmSingleEvent`, `BrmPeriodicEvent`, or `BrmCalendarBasedPeriodicEvent`.
- The scheduled event name is known.
- An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.



Delete Scheduled Event



## 2 Procedure

To delete a scheduled event:

1. Navigate to the *BrmBackupScheduler* managed object, for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,BrM=1,BrmBackupManager=SYSTEM_DATA,BrmBackupScheduler=SYSTEM_DATA
```

2. Enter Config mode:

```
(BrmBackupScheduler=SYSTEM_DATA) >configure
```

3. Delete the scheduled event, for example:

```
(config-BrmBackupScheduler=SYSTEM_DATA) >no BrmSingleEvent=S_EVENT_20140428_152
```

**Note:** If the scheduled event name is unknown, use command **show**. The event names are listed at the end of progressReport of BrmBackupScheduler.

4. Commit the change:

```
(config-BrmBackupScheduler=SYSTEM_DATA) >commit
```

5. Verify that the event has been deleted:

```
(BrmBackupScheduler=SYSTEM_DATA) >show -v
```

The following is an example output:

```
BrmBackupScheduler=SYSTEM_DATA
[...]
  progressReport
[...]
    progressPercentage=100
    result=SUCCESS
[...]
    state=FINISHED
[...]
  BrmPeriodicEvent=P_EVENT_20140428_204
```

The event is no longer shown at the end of the BrmBackupScheduler progress report.