

Unlock Administrative Lock for User Account

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2015. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Introduction	1
1.1	Prerequisites	1
2	Procedure	3





1 Introduction

This document describes how the administrator can unlock an administratively locked local Operation and Maintenance (O&M) user account.

1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

1.1.1 Conditions

The following conditions must apply:

- The user has sufficient access rights to perform the task, for example, the user has Local Authentication Administrator role.
- An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.
- The username for the local user account is known. In this document, username is `j_oedoe`.
- The password state of the account is not `EXPIRED`. To reset the password for the user, refer to *Reset Password for User Account*.





2 Procedure

To unlock the account for a local O&M user:

1. Navigate to the *UserAccountM* Managed Object (MO), for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SecM=1
,UserManagement=1,LocalAuthenticationMethod=1,UserAc
countM=1
```

2. Select the appropriate user account, for example:

```
(UserAccountM=1) >UserAccount=joedoe
```

3. Enter Config mode:

```
(UserAccount=joedoe) >configure
```

4. Set attribute *administrativeState* , for example:

```
(config-UserAccount=joedoe) >administrativeState=UNLOC
KED
```

5. Commit the settings:

```
(config-UserAccount=joedoe) >commit
```

6. Verify the settings, for example:

```
(UserAccount=joedoe) >show accountState
```

The following is an example output:

```
accountState=UNLOCKED
```

If the account state is still locked, refer to *Unlock Operational Lock for User Account*.