

# Change Trust Category

---

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2014, 2015, 2016. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Prerequisites	1
<b>2</b>	<b>Procedure</b>	<b>3</b>



Change Trust Category



# 1 Introduction

This document describes how to change a trust category.

A trusted certificate can belong to multiple trust categories. *TrustedCertificate* Managed Object (MO) references can be deleted from a *TrustCategory* MO if more than one *TrustedCertificate* MO reference exists.

## 1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

### 1.1.1 Conditions

The following conditions must apply:

- The user has the System Security Administrator role.
- MO *TrustCategory* exists.
- MO *TrustCategory* includes at least two *TrustedCertificate* references.
- An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.





## 2 Procedure

To change a trust category:

1. Navigate to the *TrustCategory* MO, for example:

```
>dn ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, CertM=1, TrustCategory=aurora
```

2. List the trusted certificates:

```
(TrustCategory=aurora) >show
```

The following is an example output:

```
TrustCategory=aurora
  trustedCertificates
    "ManagedElement=NODE06ST, SystemFunctions=1, ⇒
SecM=1, CertM=1, TrustedCertificate=1 "
    "ManagedElement=NODE06ST, SystemFunctions=1, ⇒
SecM=1, CertM=1, TrustedCertificate=2 "
```

3. Enter Config mode:

```
(TrustCategory=aurora) >configure
```

4. Delete the unwanted *TrustedCertificate* MO reference, for example:

```
(config-TrustCategory=aurora) >no trustedCertificates="ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, CertM=1, TrustedCertificate=2 "
```

5. Commit the change:

```
(config-TrustCategory=aurora) >commit
```

6. Verify the change:

```
(TrustCategory=aurora) >show
```

The following is an example output:

```
TrustCategory=aurora
  trustedCertificates
    "ManagedElement=NODE06ST, SystemFunctions=1, ⇒
SecM=1, CertM=1, TrustedCertificate=1 "
```