

Fetch File in Logical File System

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2016. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Introduction	1
1.1	Prerequisites	1
2	Procedure	3





1 Introduction

This document describes how to fetch a file in the logical file system.

This operation can be used by Northbound Interface (NBI) clients (such as OSS, LCT, and CLI script), which need to fetch files from the logical file system. Only SSH File Transfer Protocol (SFTP) is supported.

Depending on security management rules, all or part of the SFTP protocol operations can be allowed. For more information, refer to *Section 6* in *File Management*.

1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

1.1.1 Conditions

The following conditions must apply:

- Some files exist in the selected file group.
- The file to fetch is known.
- The folder containing the file is known.
- The user has at least read access to the logical file system.
- The managed element O&M IP address or the Fully Qualified Domain Name (FQDN) is known.





2 Procedure

To fetch a file in the logical file system:

1. Open an SFTP session, for example:

```
shell$ sftp <user name>@<O&M IP or FQDN>
```

2. Navigate to the folder containing the file, for example:

```
>cd /var/filem/nbi_root/AlarmLogs
```

3. Fetch the file using command **get** and specifying the full filename, for example:

```
sftp>get FmAlarmLog_20130403_234240_20130403_234442.log
```

For information about how to find correct directories and filenames, refer to *List File Groups and File Information in Logical File System*.

The following is an example output when fetching a file from the AlarmLogs folder:

```
Fetching FmAlarmLog_20130403_234240_20130403_234442.log
```

4. Exit the SFTP session:

```
sftp>exit
```