

Change Prefix for Exported Backup Names

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	1
2.1	Change Prefix for Exported Backup Names	1





1 Description

This instruction describes how to change prefix for exported backup names.

This is used to specify a text (maximum 128 characters) that is to be added to the beginning of the label generated for all backup export packages. It can be used to identify the managed element from which the exported backup originated.

2 Procedure

2.1 Change Prefix for Exported Backup Names

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - No other backup operation is in progress.
 - The prefix text is known.
 - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

Steps

1. Navigate to the *BrM* managed object, for example:

```
>dn ManagedElement=NODE06ST, SystemFunctions=1, BrM=1
```

2. Enter Config mode:

```
(BrM=1) >configure
```

3. Enter the export package label prefix, for example:

```
(config-BrM=1) >exportPackageLabelPrefix=NODE06ST
```



Note: The value of attribute `exportPackageLabelPrefix` cannot be cleared using ECLI command `no exportPackageLabelPrefix`.

The `exportPackageLabelPrefix` text string supports alphanumeric, dash, underscore, and period characters.

4. Commit the change:

```
(config-BrM=1) >commit
```

5. Verify the change:

```
(BrM=1) >show
```

The following is an example output:

```
exportPackageLabelPrefix="NODE06ST"
```