

Change Trust Category

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2014, 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	1
2.1	Change Trust Category	1



Change Trust Category



1 Description

This instruction describes how to change a trust category.

A trusted certificate can belong to multiple trust categories. *TrustedCertificate* Managed Object (MO) references can be deleted from a *TrustCategory* MO if more than one *TrustedCertificate* MO reference exists.

2 Procedure

2.1 Change Trust Category

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - The user has the System Security Administrator role.
 - A *TrustCategory* MO exists.
 - The *TrustCategory* MO includes at least two *TrustedCertificate* references.
 - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

Steps

1. Navigate to the *TrustCategory* MO, for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,Ce  
rtM=1,TrustCategory=aurora
```

2. List the trusted certificates:

```
(TrustCategory=aurora) >show
```

The following is an example output:



```
TrustCategory=aurora
  trustedCertificates
    "ManagedElement=NODE06ST, SystemFunctions=1, =>
SecM=1, CertM=1, TrustedCertificate=1 "
    "ManagedElement=NODE06ST, SystemFunctions=1, =>
SecM=1, CertM=1, TrustedCertificate=2 "
```

3. Enter Config mode:

```
(TrustCategory=aurora) >configure
```

4. Delete the unwanted *TrustedCertificate* MO reference, for example:

```
(config-TrustCategory=aurora) >no trustedCertificates="ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, CertM=1, TrustedCertificate=2 "
```

5. Commit the change:

```
(config-TrustCategory=aurora) >commit
```

6. Verify the change:

```
(TrustCategory=aurora) >show
```

The following is an example output:

```
TrustCategory=aurora
  trustedCertificates
    "ManagedElement=NODE06ST, SystemFunctions=1, =>
SecM=1, CertM=1, TrustedCertificate=1 "
```