

Create SNMPv2C Target

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	1
2.1	Create SNMPv2C Target	1





1 Description

This instruction describes how to create an SNMPv2C target. An SNMPv2C target is created to forward Simple Network Management Protocol (SNMP) notifications to a management system over the SNMPv2C protocol.

2 Procedure

2.1 Create SNMPv2C Target

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - The SNMP community, target IP address, and `networkPrefixLength` are known and according to the network IP plan.
 - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

Steps

1. Navigate to the *Snmp* Managed Object (MO), for example:

```
>dn ManagedElement=NODE06ST, SystemFunctions=1, SysM=1, Snmp=1
```

2. Enter Config mode:

```
(Snmp=1) >configure
```

3. Create an SNMPv2C target, for example:

```
(config-Snmp=1) >SnmpTargetV2C=OSS_v2C
```

4. For the *SnmpTargetV2C* MO, set attributes `community`, `address`, and `networkPrefixLength`, for example:

```
(config-SnmpTargetV2C=OSS_v2C) >community=group
```



```
(config-SnmpTargetV2C=OSS_v2C) > address=192.0.2.10  
(config-SnmpTargetV2C=OSS_v2C) > networkPrefixLength=24
```

5. Commit the settings:

```
(config-SnmpTargetV2C=OSS_v2C) > commit
```

6. Verify the settings

```
(SnmpTargetV2C=OSS_v2C) > show -v
```

The following is an example output:

```
SnmpTargetV2C=OSS_v2C  
  address="192.0.2.10"  
  administrativeState=UNLOCKED <default>  
  community="group"  
  informRetryCount=1 <default>  
  informTimeout=300 <default>  
  isMibWritable=true <default>  
  networkPrefixLength=24  
  operationalState=ENABLED [] <read-only>  
  port=162 <default>  
  snmpTargetV2CId=OSS_v2C  
  transportMethod=TRAP <default>
```