

# Configure LDAP Basic Connection

---

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Description</b>	<b>1</b>
<b>2</b>	<b>Procedure</b>	<b>1</b>
2.1	Configure LDAP Basic Connection	1





# 1 Description

This instruction describes how to configure a clear text connection to a remote centralized LDAP server for the Managed Element (ME) to control access to the LDAP directory. Such change can be triggered by the organization security policy.

## 2 Procedure

### 2.1 Configure LDAP Basic Connection

#### Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
  - The user has the System Security Administrator role.
  - The LDAP server is configured for the ME.
  - The URI of the remote LDAP server and, optionally, the fall back LDAP server URI is known.
  - The base distinguished name in the LDAP server is known.
  - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

#### Steps

1. Navigate to the *Ldap* managed object, for example:

```
>dn ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, UserManagement=1, LdapAuthenticationMethod=1, Ldap=1
```

2. Enter Config mode:

```
(Ldap=1) >configure
```



3. Set `ldapIpAddress` to the IP address of the remote LDAP server, for example:

```
(config-Ldap=1) >ldapIpAddress="192.168.0.10"
```

4. Optionally, set the `fallbackLdapIpAddress` to be used when the primary LDAP server is down, for example:

```
(config-Ldap=1) >fallbackLdapIpAddress="192.168.0.11"
```

5. Configure the `baseDn` from where the LDAP server starts to search for users, for example:

```
(config-Ldap=1) >baseDn="dc=my-domain,dc=com"
```

6. If LDAP server is listening to a non-default port, then the `serverPort` must be set, for example:

```
(config-Ldap=1) >serverPort=1000
```

7. Turn off TLS:

```
(config-Ldap=1) >useTls=false
```

8. Commit the settings:

```
(config-Ldap=1) >commit
```

9. Verify the result:

```
(Ldap=1) >show
```

The following is an example output:

```
Ldap=1
baseDn="dc=my-domain,dc=com"
fallbackLdapIpAddress="192.168.0.11"
ldapIpAddress="192.168.0.10"
serverPort=1000
useTls=false
[...]
```

A basic LDAP connection is set between ME and the remote LDAP server.