

MTAS Performance Measurements

MTAS

USER GUIDE

Copyright

© Ericsson AB 2017, 2018. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

| | | |
|----------|--|-----------|
| 1 | Introduction | 1 |
| 1.1 | Prerequisites | 1 |
| 2 | Overview of Performance Management | 3 |
| 2.1 | Performance Measurement Name Convention | 3 |
| 2.2 | MTAS Performance Measurement File Location | 4 |
| 2.3 | Measurement Description Template | 4 |
| 2.4 | MTAS Performance Measurements | 5 |
| 2.5 | Configure Threshold-Based Alarms | 5 |
| 2.6 | Performance Management Report Files | 5 |
| 2.7 | Platform Specific Measurement Jobs and Counters | 6 |
| 2.8 | Threshold Monitoring Job for MtasChargingBufferedEventsCount | 6 |
| 2.9 | Threshold Monitoring Job for MtasMmtNoSubscriptionCallReceived | 6 |
| 3 | MTAS Measurement Jobs and Counters | 9 |
| 4 | MTAS Measurement Groups | 13 |





1 Introduction

This document describes the Performance Measurement (PM) parameters available in the MTAS.

Scope

This document covers the following topics:

- Performance measurement groups
- Performance measurements

Target Groups

This document is intended for personnel involved in initiation of performance monitoring of the MTAS, designing performance, reports, and evaluating performance data of the MTAS.

1.1 Prerequisites

It is assumed that the user of this document is familiar with the Operation and Maintenance (O&M) area, in general.





2 Overview of Performance Management

This section describes the MTAS performance measurements. MTAS reports performance measurement information using Core MW Performance Management.

For more information on Performance Management, refer to the *Performance Management*.

2.1 Performance Measurement Name Convention

Recommended format for performance measurement name is structured in the three parts described and exemplified in Table 1.

Table 1 Performance Measurement Name Structure

| | Node Instance | Object Class | Counter Name |
|-----------------|----------------------|---------------------|---------------------|
| Example: | MTAS | Mmt | InitOrigSessOk |

The QoS counter names guide the operator where to take possible actions, as follows:

- Counter names including “Init” and “Ok” – hold the number of sessions that have been successfully set up.
- Counter names including “Init” and “NOkI” – hold the number of sessions that have failed during setup, and indicate that actions are needed to correct or improve the operation of the MTAS (internal).
- Counter names including “Init” and “NOkE” – hold the number of sessions that have failed during setup, and point out the rest of the IMS network (external).
- Counter names including “Term” and “NOkI” – hold the number of sessions that have been dropped, and indicate that actions are needed to correct or improve the dropped operation of the MTAS (internal).
- Counter names including “Term” and “NOkE” – hold the number of sessions that have been dropped, and point out the rest of the IMS network (external).
- Counter names including “Term” and “Ok” – hold the number of sessions that were successfully set up, minus the number of sessions that were dropped:
 “Term” and “Ok” = “Init” and “Ok” - “Term” and “NOkI” - “Term” and “NOkE”



2.2 MTAS Performance Measurement File Location

The default file location for the performance measurement XML files is:
`/cluster/storage/no-backup/nbi_root/PerformanceManagement
ReportFiles/`

The report files have a default preventive maintenance policy in which the maximum number of PM report files is 1000.

If the preventive maintenance limit is exceeded, the oldest files are automatically deleted.

2.3 Measurement Description Template

Each parameter listed in this document is described as follows:

- **Measurement Name**
This contains the name of measurement
- **Description**
This contains a short description of the measurement.
- **Condition**
This contains the condition which causes the measurement result data to be updated.
- **Collection Method**
This contains the form in which this measurement data is obtained.
The Collection Method can be on the following
`Cumulative Counter (CC)` and `GAUGE`
- **Aggregation**
The Aggregation could be one of the following.
`SUM`, `AVG`, `LAST UPDATE`, `MIN`, and `MAX`.
- **Measurement Result (Result Type, Output Unit)**
This contains a description of expected result values, the result type (for example, integer or float value), and output unit (for example, seconds, number of messages).
- **cpi Heading**
This specifies the measured object class name.



- measurement Status

Measurement status, possible values are PRELIMINARY, USED, OBSOLETE, and DEPRECATED.

- KeyName

This contains names of the keys related to this measurement.

- Multiplicity

This represents the size of the array if counter is an array of values

- fmAlarmType

Reference to a possible alarm associated with the measurement, in case the measurement generates a threshold alarm.

2.4 MTAS Performance Measurements

The MTAS provides measurements supporting the following features:

- A Measurement Job is a group of performance measurements, or counters that are output in a report. The Measurement Readers are described in the context of them belonging to these Measurement Jobs. The grouping of Measurement Jobs and Measurement Readers is flexible.
- Monitor Quality of Service (QoS). QoS is available on both node and service level. As long as the QoS on node level is within the wanted target, there is no need to analyze the data on service level.
- Support Fault Investigation (drill down). Fault investigation is supported by counters on node level, function level, and protocol level. The counter names relate to the Managed Object (MO).

2.5 Configure Threshold-Based Alarms

Threshold-based Alarms can be configured for the measurement types that have threshold alarm support by defining Threshold Monitoring Jobs.

For information on how to create Threshold Monitoring Jobs refer to *Create Threshold Monitoring Job*.

2.6 Performance Management Report Files

Performance measurement results are reported in XML files, which must be transferred out of the MTAS node using the secure File Transfer mechanism.

For more information on File Transfer, refer to *Fetch File in Logical File System*.



For information of Performance Management Report File format, refer to *Performance Management Report File Format*.

2.7 Platform Specific Measurement Jobs and Counters

This section describes the Platform Performance measurements with links. For information about the measurements, refer to *Managed Object Model (MOM)*.

- *Diameter Measurements*
- *DBS Measurements*
- *LDE Measurements*
- *LEM Measurements*
- *LPM Measurements*

2.8 Threshold Monitoring Job for MtasChargingBufferedEventsCount

The threshold Monitoring Job for PM measurement Counter `MtasChargingBufferedEventsCount` has the threshold job parameters and values detailed in Table 2.

For more information on how to create Threshold Monitor Job refer *Create Threshold Monitoring Job*.

Table 2 Threshold Job Parameters for MtasChargingBufferedEventsCount

| Parameter Name | Parameter Value |
|---|-----------------|
| <code>granularityPeriod</code> | FIVE_MIN |
| <code>thresholdRateOfVariation</code> | PER_GP |
| <code>thresholdHigh</code> | 10000 |
| <code>thresholdLow</code> | 8000 |
| <code>thresholdDirection</code> | INCREASING |
| <code>thresholdSeveritythresholdSeverity</code> | MAJOR |

2.9 Threshold Monitoring Job for MtasMmtNoSubscriptionCall Received

The threshold Monitoring Job for PM measurement Counter `MtasMmtNoSubscriptionCallReceived` has the threshold parameters and values detailed in Table 3.



For more information on how to create Threshold Monitor Job, refer *Create Threshold Monitoring Job*.

Table 3 Threshold Job Parameters for MtasMmtNoSubscriptionCall Received

| Parameter Name | Parameter Value |
|--|-----------------|
| granularityPeriod | ONE_HOUR |
| thresholdRateOfVariation | PER_GP |
| thresholdHigh | 300 |
| thresholdLow | 150 |
| thresholdDirection | INCREASING |
| thresholdSeveritythreshold Severity | MINOR |





3 MTAS Measurement Jobs and Counters

In this section, the performance measurements defined in the MTAS are described in detail.

Node-Level Measurements

- Measurement Job = MtasFunction
- Measurement Job = MtasLicenses
- Measurement Job = MtasQos
- Measurement Job = MtasTraf

Service-Specific Measurements

- Measurement Job = Mtas3pty
- Measurement Job = MtasAbDial
- Measurement Job = MtasAoc
- Measurement Job = MtasAp
- Measurement Job = MtasAslw
- Measurement Job = MtasCat
- Measurement Job = MtasCc
- Measurement Job = MtasCDiv
- Measurement Job = MtasComBarring
- Measurement Job = MtasConf
- Measurement Job = MtasCr
- Measurement Job = MtasCpc
- Measurement Job = MtasCps
- Measurement Job = MtasCs
- Measurement Job = MtasCw
- Measurement Job = MtasDnm
- Measurement Job = MtasDtm
- Measurement Job = MtasEct



- Measurement Job = MtasFcd
- Measurement Job = MtasFsfs
- Measurement Job = MtasGCac
- Measurement Job = MtasHold
- Measurement Job = MtasHotline
- Measurement Job = MtasMediaResourceSite
- Measurement Job = MtasMmt
- Measurement Job = MtasMmtNoSubscription
- Measurement Job = MtasNa
- Measurement Job = MtasNp
- Measurement Job = MtasIdPres
- Measurement Job = MtasPx
- Measurement Job = MtasSds
- Measurement Job = MtasSnd
- Measurement Job = MtasSSCodes
- Measurement Job = MtasSrvcc
- Measurement Job = MtasStCac
- Measurement Job = MtasStIdPres
- Measurement Job = MtasStod
- Measurement Job = MtasTa
- Measurement Job = MtasTads
- Measurement Job = MtasUCac
- Measurement Job = MtasVideoFB
- Measurement Job = MtasWsNameDb

Function-Specific Measurements

- Measurement Job = MtasCharging
- Measurement Job = MtasEtxMrfc
- Measurement Job = MtasGa



- Measurement Job = MtasMrfc
- Measurement Job = MtasNumNorm
- Measurement Job = MtasReBalancing
- Measurement Job = MtasSubsData
- Measurement Job = MtasSubsDataMgmt
- Measurement Job = MtasShInterface
- Measurement Job = MtasXdms

Interface-Specific Measurements

- Measurement Job = MtasCsi
- Measurement Job = MtasH248
- Measurement Job = MtasScc
- Measurement Job = MtasSip





4 MTAS Measurement Groups

This section lists the performance measurement groups with links. For information about the measurements, refer to *Managed Object Model (MOM)*.

- [*Mtas3pty*](#)
- [*MtasAbDial*](#)
- [*MtasAoc*](#)
- [*MtasAp*](#)
- [*MtasAslw*](#)
- [*MtasCDiv*](#)
- [*MtasCac*](#)
- [*MtasCat*](#)
- [*MtasCc*](#)
- [*MtasCharging*](#)
- [*MtasComBarring*](#)
- [*MtasComDetails*](#)
- [*MtasConf*](#)
- [*MtasCpc*](#)
- [*MtasCps*](#)
- [*MtasCr*](#)
- [*MtasCs*](#)
- [*MtasCsi*](#)
- [*MtasCsiMap*](#)
- [*MtasCug*](#)
- [*MtasCw*](#)
- [*MtasDen*](#)
- [*MtasDnm*](#)
- [*MtasDr*](#)



- *MtasDtm*
- *MtasEct*
- *MtasExtMrfc*
- *MtasFcd*
- *MtasFsfs*
- *MtasFunction*
- *MtasGa*
- *MtasGenSSCodes*
- *MtasH248*
- *MtasHold*
- *MtasHotline*
- *MtasIdPres*
- *MtasLicenses*
- *MtasMcid*
- *MtasMediaPolicy*
- *MtasMediaResourceSite*
- *MtasMmt*
- *MtasMmtLongDurationCall*
- *MtasMmtNoSubscription*
- *MtasMrfc*
- *MtasNa*
- *MtasNp*
- *MtasNumNorm*
- *MtasOct*
- *MtasPrlw*
- *MtasPriorityCall*
- *MtasPriorityCallGetsService*
- *MtasPx*



- *MtasQos*
- *MtasReBalancing*
- *MtasRbt*
- *MtasSSCodes*
- *MtasScc*
- *MtasSds*
- *MtasShInterface*
- *MtasSip*
- *MtasSipOc*
- *MtasSnd*
- *MtasSrvcc*
- *MtasSt*
- *MtasStCDiv*
- *MtasStCac*
- *MtasStComBarring*
- *MtasStCps*
- *MtasStCs*
- *MtasStIdPres*
- *MtasStMcid*
- *MtasStod*
- *MtasStodCallPull*
- *MtasSubsData*
- *MtasSubsDataMgmt*
- *MtasTa*
- *MtasTads*
- *MtasTrace*
- *MtasTraf*
- *MtasUCRouting*



- *MtasVideoFB*
- *MtasWsNameDb*
- *MtasXdms*