

MtasMpController, One or More MRFPs Overloaded

MTAS

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2016. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Introduction	1
1.1	Alarm Description	1
1.2	Prerequisites	2
2	Procedure	5



MtasMpController, One or More MRFPs Overloaded



1 Introduction

This instruction concerns alarm handling.

1.1 Alarm Description

The `MtasMpController, One or More MRFPs Overloaded` alarm is raised when a congestion situation occurs in a Media Resource Function Processor (MRFP). The MRFP sends a notification to the MTAS that indicates that the MRFP is overloaded.

The MTAS provides a mechanism for an MRFP to report congestion to the MTAS so that the MTAS can reduce the amount of resource requests to the congested MRFP.

The `MtasMpController, One or More MRFPs Overloaded` alarm relates to connection between the MTAS and an MRFP node. This connection relates to the Media Resource Function Controller (MRFC) function. For more information, refer to *MTAS Media Control Management Guide*.

The MRFC function is a part of the MTAS. The operation requests are started by request from MTAS services and it operates external MRFPs by use of the standard Mp interface with text encoded H.248 over SCTP.

Note: Requests for adding new terminations to the MRFP can be rejected in case a critical overload situation occurs.

The alarm is issued in the following situations:

- Congestion in one or more MRFPs.

The possible alarm causes and the corresponding fault reasons, fault locations, and impacts are described in Table 1.

Table 1 Alarm Causes

Alarm Cause	Description	Fault Reason	Fault Location	Impact
Congestion in one or more MRFPs.	A congestion situation has occurred in one or several MRFPs.	One or more MRFPs cannot handle the amount of resource requests initiated by MTAS.	One or more MRFPs.	Congested MRFPs might not be able to handle media properly, certain services might not work as expected.



Note: The alarm can appear as a result of the maintenance activity.

The alarm attributes are listed and explained in Table 2.

Table 2 Alarm Attributes

Attribute Name	Attribute Value
Major Type	193
Minor Type	6619167
Managed Object Class	<i>MtasMpController</i>
Managed Object Instance	MtasFunction.applicationName=MtasFunction,MtasMpController.mtasMrfc=0
Specific Problem	MtasMpController, One or More MRFPs Overloaded
Event Type	qualityOfServiceAlarm (3)
Probable Cause	x733Congestion (308)
Additional Text	-
Perceived Severity	The severity of the alarm can be minor, major, or critical depending on the number of MRFPs that are overloaded and the number of MRFPs that are configured in the system, see Table 3.

Table 3 Severity Levels

Number of MRFPs	Number of Overloaded MRFPs	Alarm Severity
1	All	Critical(3)
2	All	Critical(3)
	All but one	Major(4)
>2	All	Critical(3)
	At least one	Major(4)
	One	Minor(5)

1.2 Prerequisites

This section provides information on the documents, tools, and conditions that apply to the procedure.



1.2.1 Documents

Before starting this procedure, ensure that the following documents are read:

- *Check Alarm Status*
- *Fault Management*
- *Managed Object Model (MOM)*

1.2.2 Tools

No tools are required.

1.2.3 Conditions

Before starting this procedure, ensure that the following conditions are met:

- No ongoing maintenance activities are affecting the network or network elements.
- The user has proper authority to handle configuration management of the network elements.
- An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.





2 Procedure

This section describes the procedure to follow when this alarm is received.

Do the following:

1. Depending on how many MRFPs are configured in the system, the severity changes when one or more MRFPs returns to normal operation, see Table 3. When the last MRFP has returned to normal operation, the alarm is cleared. The delay before the alarm is cleared or the severity is lowered is 30 minutes.
2. If the alarm does not cease or the severity level not goes down after 30 minutes, consult the next level of maintenance support. Further actions are outside the scope of this instruction.