

DBS, NR, Connection Lost

OPERATIONAL INSTRUCTIONS

Copyright

© Ericsson AB 2016–2018. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks are properties of their respective owners.



Contents

1	Alarm Description	1
2	Procedure	2
2.1	Handle Alarm DBS, NR, Connection Lost	2



DBS, NR, Connection Lost



1 Alarm Description

The alarm is raised when the connection is lost with the peer cluster.

Table 1 DBS, NR, Connection Lost

Alarm Cause	Description	Fault Reason	Fault Location	Impact
Reload	The connection endpoint reloaded (on software or hardware level).	N/A	N/A	Minor severity: After automatic recovery, additional resources will temporarily be needed to restore functionality. This can result in overload.
Network unavailability	The connection was closed because of network unavailability.		Network	
Configuration change	The peer cluster closed the connection because of configuration changes.		N/A	Major severity: Data is not synchronized with the relevant peer cluster. Changes in one cluster are kept and the changes in the other cluster are lost.
Backlog size limit reached	One of the clusters closed the connection as it reached the relevant limits on backlog size.		Network/Configuration	

Table 2 Alarm Attributes

Attribute Name	Attribute Value/Interpretation
Major Type	193
Minor Type	918532
MO Class	DbService
Source	DbvDirector
Specific Problem	DBS, NR, Connection Lost
Event Type	COMMUNICATIONSALARM
Probable Cause	frequencyHoppingFailure (74)
Perceived Severity	MAJOR or MINOR
Additional Information	The list of nodes that lost communication, for example PL - 3, PL - 5, PL - 6



2 Procedure

2.1 Handle Alarm DBS, NR, Connection Lost

Prerequisites

- This instruction references the following documents:
 - DBS, NR, Redundancy Disabled
- No tools are required.
- Before starting this procedure, ensure that the following condition is met:
 - The alarm is raised.

Steps

1. Are there any software or hardware problems in the peer cluster?

Yes: Take the necessary actions there to allow recovery.

No: Continue with the next step.
2. Is the DBS, NR, Redundancy Disabled alarm raised in the peer cluster?

Yes: Take the necessary actions to clear that alarm.

No: Continue with the next step.
3. Is the alarm still active?

Yes: Check network availability between the clusters. For the list of nodes that lost the connection, check the `infoValue` attribute of the alarm.

No: Contact the next level of maintenance support, as it is possible that the alarm was raised due to a dimensioning problem resulting in overload.
4. Job is completed.