

# Configure Ericsson LDAP Filter

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Description</b>	<b>1</b>
<b>2</b>	<b>Procedure</b>	<b>1</b>





# 1 Description

This instruction describes how to use the standard Ericsson profile filter. Such a change can be triggered by the organization security policy.

# 2 Procedure

## Prerequisites

- This instruction references the following documents:
  - [Configure LDAP Basic Connection](#)
  - [Configure TLS for LDAP](#)
- No tools are required.
- The following conditions must apply:
  - The user has the System Security Administrator role.
  - The Managed Element (ME) is configured to connect with remote LDAP server, refer to [Configure LDAP Basic Connection](#) and [Configure TLS for LDAP](#).
  - The LDAP server is configured for the ME.
  - The Ericsson LDAP schema is specified and loaded in the LDAP server and the user POSIX® accounts are updated to use the schema.
  - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

## Steps

1. Navigate to the **Ldap** managed object, for example:  

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LdapAuthenticationMethod=1,Ldap=1
```
2. Enter Config mode:  

```
(Ldap=1)>configure
```
3. Set the profileFilter:  

```
(config-Ldap=1)>profileFilter=ERICSSON_FILTER
```



4. Commit the settings:

```
(config-Ldap=1)>commit
```

5. Verify the result:

```
(Ldap=1)>show
```

The following is an example output:

```
Ldap=1
  baseDn="dc=my-domain,dc=com"
  fallbackLdapIpAddress="192.168.0.11"
  ldapIpAddress="192.168.0.10"
  profileFilter=ERICSSON_FILTER
  useTls=false
```