

# Create Custom Rule

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Description</b>	<b>1</b>
<b>2</b>	<b>Procedure</b>	<b>1</b>
2.1	Create Custom Rule	1



Create Custom Rule



# 1 Description

This instruction describes how to create a custom rule.

The administrator can create custom rules when the predefined rules do not match the needs of the organization authorization policy.

## 2 Procedure

### 2.1 Create Custom Rule

#### Prerequisites

- The instruction references the following documents:
  - [Create Custom Role](#)
  - [Change Custom Role](#)
- No tools are required.
- The following conditions must apply:
  - The user has the System Security Administrator role.
  - The model elements and permission types targeted by the custom rule are known and reflect the wanted authorization policy.
  - The new custom rule name is known.
  - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

#### Steps

1. Navigate to the `LocalAuthorizationMethod` Managed Object (MO), for example:  

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LocalAuthorizationMethod=1
```
2. Enter Config mode:  

```
(LocalAuthorizationMethod=1)>configure
```



3. Create a CustomRule MO, for example:

```
(config-LocalAuthorizationMethod=1)>CustomRule=Custom_FaultManagement_1
```

4. Set the model elements for which the permission is applicable, for example:

```
(config-CustomRule=Custom_FaultManagement_1)>ruleData="ManagedElement,SystemFunctions,Fm,*"
```

5. Set the permissions that the rule provides on a target specified by attribute ruleData, for example:

```
(config-CustomRule=Custom_FaultManagement_1)>permission=R
```

In this example, the custom rule gives read-only permission to class Fm, its attributes, and child MOs.

6. Describe the policy for the rule, for example:

```
(config-CustomRule=Custom_FaultManagement_1)>userLabel="R Rule for FM and Child MOs"
```

7. Commit the settings:

```
(config-CustomRule=Custom_FaultManagement_1)>commit
```

8. Verify the result:

```
(CustomRule=Custom_FaultManagement_1)>show
```

The following is an example output:

```
CustomRule=Custom_FaultManagement_1
  permission=R
  ruleData="ManagedElement,SystemFunctions,Fm,*"
  userLabel="R Rule for FM and Child MOs"
```

9. The custom rule can now be assigned to custom roles, refer to [Create Custom Role](#) or [Change Custom Role](#).