

Change Administrative State of ECLI or NETCONF over SSH

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	1
2.1	Change Administrative State of ECLI over SSH	1
2.2	Change Administrative State of NETCONF over SSH	2



Change Administrative State of ECLI or NETCONF over SSH



1 Description

This instruction describes how to change the administrative state of ECLI or NETCONF over SSH.

2 Procedure

2.1 Change Administrative State of ECLI over SSH

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - The user has the System Security Administrator role.
 - If locking ECLI over SSH, NETCONF over SSH must be unlocked, or the other way around.
 - An Ericsson Command-Line Interface (ECLI) in exec mode is in progress.

Attention!



Risk of system malfunction or traffic disturbance.

Before locking the administrative state of ECLI over SSH, make sure that the administrative state of NETCONF over SSH is UNLOCKED. Having both interfaces set to LOCKED disables O&M access to the ME. Refer to product-specific troubleshooting instructions to resolve such a scenario.

Steps

1. Navigate to the `CliSsh` Managed Object (MO), for example:



```
>dn ManagedElement=1,SystemFunctions=1,SysM=1,CliSsh=1
```

2. Enter Config mode:

```
(CliSsh=1)>configure
```

3. Set the administrativeState attribute, for example:

```
(config-CliSsh=1)>administrativeState=UNLOCKED
```

Note: To lock the administrative state, set the attribute value to LOCKED.

4. Commit the settings:

```
(config-CliSsh=1)>commit
```

5. Verify the settings:

```
(CliSsh=1)>show
```

The following is an example output:

```
CliSsh=1
[...]
administrativeState=UNLOCKED
```

2.2 Change Administrative State of NETCONF over SSH

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - The user has the System Security Administrator role.
 - If locking ECLI over SSH, NETCONF over SSH must be unlocked, or the other way around.
 - An Ericsson Command-Line Interface (ECLI) in exec mode is in progress.



Attention!

Risk of system malfunction or traffic disturbance.



Before locking the administrative state of NETCONF over SSH, make sure that the administrative state of ECLI over SSH is UNLOCKED. Having both interfaces set to LOCKED disables O&M access to the ME. Refer to product-specific troubleshooting instructions to resolve such a scenario.

Steps

1. Navigate to the `NetconfSsh` Managed Object (MO), for example:

```
>dn ManagedElement=1,SystemFunctions=1,SysM=1,NetconfSsh=1
```

2. Enter Config mode:

```
(NetconfSsh=1)>configure
```

3. Set the `administrativeState` attribute, for example:

```
(config-NetconfSsh=1)>administrativeState=UNLOCKED
```

Note: To lock the administrative state, set the attribute value to LOCKED.

4. Commit the settings:

```
(config-NetconfSsh=1)>commit
```

5. Verify the settings:

```
(NetconfSsh=1)>show
```

The following is an example output:

```
NetconfSsh=1
[... ]
    administrativeState=UNLOCKED
```