

Schedule Backups Based on Calendar Event

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	1
2.1	Schedule Backups Based on Calendar Event	1





1 Description

This instruction describes how to schedule a regularly occurring backup, which is to create a backup as a calendar-based periodic event.

A calendar-based periodic event can be used as follows:

- To schedule an event that is effective as soon as the configuration is committed
- To schedule an event that is effective from a specified time in the future

The procedure in this instruction illustrates the latter case.

Note: When any of the following backup operations is in progress, a scheduled backup event that is triggered is postponed and retried at regular intervals later:

- Manual backup creation
- Scheduled backup creation
- Backup deletion
- Backup restore

2 Procedure

2.1 Schedule Backups Based on Calendar Event

Prerequisites

- No documents are required.
- No tools are required.
- The following condition must apply:
 - The event name is known.
 - The calendar-based periodic event values are known.



- An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

Steps

1. Navigate to the *BrmBackupScheduler* managed object, for example:

```
>dn ManagedElement=NODE06ST, SystemFunctions=1, BrM=1, BrmBackupManager=SYSTEM_DATA, BrmBackupScheduler=SYSTEM_DATA
```

2. Enter Config mode:

```
(BrmBackupScheduler=SYSTEM_DATA) >configure
```

3. Enter the event name, for example:

```
(config-BrmBackupScheduler=SYSTEM_DATA) >BrmCalendarBasedPeriodicEvent=C_EVENT_20140428_314
```

4. Create the calendar-based periodic event by setting the relevant attributes, for example:

- (config-BrmCalendarBasedPeriodicEvent=C_EVENT_20140428_314) >**dayOfWeek=SUNDAY**

dayOfWeek defines what day of the week the event is triggered once effective, in this case Sunday.

- (config-BrmCalendarBasedPeriodicEvent=C_EVENT_20140428_314) >**dayOfWeekOccurrence=FIRST**

dayOfWeekOccurrence further specifies the value entered for *dayOfWeek*. In this case, the event is to be triggered only the first Sunday of the month once effective.

- (config-BrmCalendarBasedPeriodicEvent=C_EVENT_20140428_314) >**startTime=2014-06-31T23:59:59**

startTime defines the time in the future when the event becomes effective.

- (config-BrmCalendarBasedPeriodicEvent=C_EVENT_20140428_314) >**time=03:00:00**

time defines the time when the event is triggered once it becomes effective.

5. Commit the calendar-based periodic event:

```
(config-BrmCalendarBasedPeriodicEvent=C_EVENT_20140428_314) >commit
```

6. Verify that the calendar-based periodic event was created:



```
(BrmCalendarBasedPeriodicEvent=C_EVENT_20140428_314) >show
```

The following is an example output of a calendar-based periodic event where backups are created every first Sunday of the month at 03:00 from 2014-06-31, 23:59:59 until the end of the century.

```
BrmCalendarBasedPeriodicEvent=C_EVENT_20140428_314
  dayOfWeek=SUNDAY
  dayOfWeekOccurrence=FIRST
  startTime=2014-06-31T23:59:59
  time=03:00:00
```