

Delete Custom Rule

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	1
2.1	Delete Custom Rule	1



Delete Custom Rule



1 Description

This instruction describes how to delete a custom rule.

The administrator can delete custom rules when they are no longer needed by the organization authorization policy.

2 Procedure

2.1 Delete Custom Rule

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - The user has the System Security Administrator role.
 - The `CustomRule` MO to delete is known.
 - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

Steps

1. Navigate to the *LocalAuthorizationMethod* MO, for example:

```
>dn ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, UserManagement=1, LocalAuthorizationMethod=1
```

2. View the current settings:

```
(LocalAuthorizationMethod=1) >show -v
```

The following is an example output:



```
LocalAuthorizationMethod=1
[...]
CustomRule=Custom_FaultManagement_1
CustomRule=Custom_PerformanceManagement_1
CustomRule=Custom_SoftwareInventory_1
CustomRule=Custom_SoftwareManagement_1
CustomRule=Custom_SystemManagement_1
CustomRule=Custom_Top_1
CustomRule=Custom_Top_2
CustomRule=Custom_Top_3
[...]
```

3. Enter Config mode:

```
(LocalAuthorizationMethod=1) >configure
```

4. Delete the *CustomRule* MO, for example:

```
(config-LocalAuthorizationMethod=1) >no CustomRule=Custo  
m_SoftwareInventory_1
```

5. Commit the deletion:

```
(config-LocalAuthorizationMethod=1) >commit
```

6. Verify the deletion by checking the *CustomRule* instances:

```
(LocalAuthorizationMethod=1) >show -v
```

The following is an example output:

```
LocalAuthorizationMethod=1
[...]
CustomRule=Custom_FaultManagement_1
CustomRule=Custom_PerformanceManagement_1
CustomRule=Custom_SoftwareManagement_1
CustomRule=Custom_SystemManagement_1
CustomRule=Custom_Top_1
CustomRule=Custom_Top_2
CustomRule=Custom_Top_3
[...]
```

7. The custom rule has been deleted from the managed element.