

Configure Enrollment Authority

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2014, 2015, 2016. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

| | | |
|----------|---------------------|----------|
| 1 | Introduction | 1 |
| 1.1 | Prerequisites | 1 |
| 2 | Procedure | 3 |





1 Introduction

This document describes how to configure an enrollment authority.

In Certificate Management, an online enrollment requires the creation of an *EnrollmentAuthority* Managed Object (MO), which represents a Certificate Authority (CA) or a Registration Authority (RA).

An *EnrollmentAuthority* MO can be used by several *EnrollmentServer* MOs.

1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

1.1.1 Conditions

The following conditions must apply:

- The user has the System Security Administrator role.
- A *TrustedCertificate* MO exists.
- An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.





2 Procedure

To configure an enrollment authority:

1. Navigate to the *CertM* MO, for example:

```
>dn ManagedElement=NODE06ST, SystemFunctions=1, SecM=1
, CertM=1
```

2. Enter Config mode:

```
(CertM=1) >configure
```

3. Create the *EnrollmentAuthority* MO, for example:

```
(config-CertM=1) >EnrollmentAuthority=1
```

4. Set the CA authority name, for example:

```
(config-EnrollmentAuthority=1) >enrollmentAuthorityName=
"CN=atrcus3409NECertCA, OU=ericssonOAM, O=Ericsson"
```

Here CN=atrcus3409NECertCA, OU=ericssonOAM, O=Ericsson is an example of a Distinguished Name for a CA enrolling the certificates for O&M node credentials.

5. Set the reference to the certificate of the chosen CA authority, for example:

```
(config-EnrollmentAuthority=1) >enrollmentCaCertificate=
"ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, Cert
M=1, TrustedCertificate=1"
```

6. Enter a description of the CA, for example:

```
(config-EnrollmentAuthority=1) >userLabel="atrcus3409NEC
ertCA O&M Certificate Authority"
```

7. Commit the settings:

```
(config-EnrollmentAuthority=1) >commit
```

8. Verify the settings:

```
(EnrollmentAuthority=1) >show
```

The following is an example output:



```
EnrollmentAuthority=1
  enrollmentAuthorityName="CN=atrcus3409NECertCA,OU=>
ericssonOAM,O=Ericsson"
  enrollmentCaCertificate="ManagedElement=NODE06ST,SystemFunctions=1,>
SecM=1,CertM=1,TrustedCertificate=1"
  userLabel="atrcus3409NECertCA O&M Certificate Authority"
```