

# Create Custom Role

---

## OPERATING INSTRUCTIONS

**Copyright**

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

**Disclaimer**

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

**Trademark List**

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



# Contents

<b>1</b>	<b>Description</b>	<b>1</b>
<b>2</b>	<b>Procedure</b>	<b>1</b>
2.1	Create Custom Role	1



Create Custom Role



# 1 Description

This instruction describes how to create a custom role.

The administrator can create custom roles when the predefined roles do not match the needs of the organization authorization policy.

## 2 Procedure

### 2.1 Create Custom Role

#### Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
  - The user has the System Security Administrator role.
  - At least one `CustomRule` Managed Object (MO) exists.
  - The new custom role name is known and matches the name used in the Lightweight Directory Access Protocol (LDAP) authentication and authorization information store.
  - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

**Note:** It is not allowed to define a new `CustomRole` MO with an existing `roleName`.

#### Steps

1. Navigate to the *LocalAuthorizationMethod* MO, for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LocalAuthorizationMethod=1
```

2. Enter Config mode:

```
(LocalAuthorizationMethod=1)>configure
```



3. Create a *CustomRole* MO, for example:

```
(config-LocalAuthorizationMethod=1) >CustomRole=CustomSystemOperator
```

4. Set the role name, for example:

```
(config-CustomRole=CustomSystemOperator) >roleName="CustomSystemOperator"
```

5. Associate some existing custom rules to the custom role, for example:

```
(config-CustomRole=CustomSystemOperator) >rules="ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, UserManagement=1, LocalAuthorizationMethod=1, CustomRule=Custom_FaultManagement_1"
```

6. Describe the role, for example:

```
(config-CustomRole=CustomSystemOperator) >userLabel="Custom System Operator Role"
```

7. Commit the settings:

```
(config-CustomRole=CustomSystemOperator) >commit
```

8. Verify the result:

```
(CustomRole=CustomSystemOperator) >show
```

The following is an example output:

```
CustomRole=CustomSystemOperator
  roleName="CustomSystemOperator"
  rules=
    "ManagedElement=NODE06ST, SystemFunctions=1, SecM=1, ⇒
UserManagement=1, LocalAuthorizationMethod=1, CustomRule=⇒
Custom_FaultManagement_1"
  userLabel="Custom System Operator Role"
```

9. The custom role can now be assigned to user accounts.