

Lock LDAP Authentication Method

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	1
2.1	Lock LDAP Authentication Method	1





1 Description

This instruction describes how to lock the LDAP authentication method.

In maintenance situations, if needed, the administrator can lock the LDAP authentication to prevent remote LDAP users to access the ME when it is not fully operational. When the LDAP authentication method is locked, the Management Information Base (MIB) is accessed by users authorized by other access control methods for example, `LocalAuthentication` or local Linux[®] users belonging to `com-emergency` group.

The procedure in this document must only be used during troubleshooting.

2 Procedure

2.1 Lock LDAP Authentication Method

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - The user has the System Security Administrator role.
 - The LDAP administrative state is `UNLOCKED`.
 - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

Steps

1. Navigate to the *LdapAuthenticationMethod* managed object, for example:

```
>dn ManagedElement=NODE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LdapAuthenticationMethod=1
```

2. Enter Config mode:

```
(LdapAuthenticationMethod=1) >configure
```



3. Lock the LDAP authentication method:

```
(config-LdapAuthenticationMethod=1) >administrativeState=LOCKED
```

4. Commit the setting:

```
(config-LdapAuthenticationMethod=1) >commit
```

5. Verify the result:

```
(LdapAuthenticationMethod=1) >show
```

```
LdapAuthenticationMethod=1  
  administrativeState=LOCKED  
  Ldap=1
```

Note: As long as the LDAP authentication method is locked, only users authorized by other access control methods for example, `LocalAuthentication` or local Linux users belonging to the `com-emergency` group can start ECLI or NETCONF sessions. Ongoing ECLI and NETCONF sessions are not affected by the change.

An ongoing session can be disconnected because of inactivity. At the next logon, the user is possibly not able to access the session again. It is therefore important to stay active in the ongoing session.