

Lock Health Check Job Scheduler

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2015. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Introduction	1
1.1	Prerequisites	1
2	Procedure	3





1 Introduction

This document describes how to lock a health check job scheduler related to a job. When the scheduler is locked, no scheduled event, for the current health check job, is triggered.

1.1 Prerequisites

This section describes the prerequisites, which must be fulfilled before using the procedure.

1.1.1 Conditions

The following conditions must apply:

- The name of the job for which the scheduler must be locked is known.
- The current value of attribute `administrativeState` is `UNLOCKED` for the job scheduler to lock.
- An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.





2 Procedure

To lock a health check job scheduler:

1. Navigate to the **HealthCheckM** Managed Object (MO):

```
>dn ManagedElement=<node_name>,SystemFunctions=1,HealthCheckM=1
```

Note: The string `node_name` is specific for the Managed Element (ME).

2. Navigate to the health check job for which the scheduler must be locked, for example:

```
(HealthCheckM=1)>HcJob=jobName
```

Note: The string `jobName` is the health check job name.

3. Navigate to the health check job scheduler to lock:

```
(HcJob=jobName)>HcJobScheduler=1
```

4. Enter Config mode:

```
(HcJobScheduler=1)>configure
```

5. Lock the health check job scheduler:

```
(config-HcJobScheduler=1)>administrativeState=LOCKED
```

6. Commit the change:

```
(config-HcJobScheduler=1)>commit
```

7. Verify the scheduler state:

```
(HcJobScheduler=1)>show administrativeState
```

The following is an example output:

```
HcJobScheduler=1
administrativeState=LOCKED
```