

# TPK-SV-009 USB-to-RJ11 Serial Programming Cable Installation Instructions



The TPK-SV-009 USB-to-RJ11 serial programming cable allows you to program Tait devices using the USB interface of your PC.

The kit contains the following items:

- programming cable
- driver CD (406-00079-xx)


**Notice** Applying mechanical force on the programming cable's USB connector while it is plugged in may damage the USB port of your PC.




## Installing the Driver

Tait Communications recommends that you install the driver from the CD before connecting the USB plug to the PC. Connecting the USB plug to the PC first will work, but will require you to browse the CD for the driver.

- 1 Insert the driver CD. (If your CD drive is not set to run CDs automatically, run the 'run-install.bat' file.)
- 2 Under Windows 7, on the Autoplay dialog select 'runinstall.bat'.
- 3 Follow the instructions of the Setup Wizard.

 Under Windows XP, you will be presented with dialogs stating that the software you are installing has not passed Windows Logo testing to verify its compatibility with Windows XP. It is safe for you to select to continue anyway.


- 4 Connect the USB plug to the PC.

 Under Windows XP, the Found New Hardware Wizard will appear. Select 'No, not at this time' and then 'Install the software automatically (recommended)'. As the driver consists of two parts, the Found New Hardware Wizard will appear twice. This is normal behavior.


## Identifying the Serial Port

The PC will assign a serial port number to the connected programming cable.

- 1 To identify the assigned serial port number, in the Device Manager of your operating system view the Ports settings.
- 2 In your Tait programming application, select the serial port as described in the Help file.

 If the assigned port number exceeds the maximum number that can be set in your Tait programming application, you can change the assigned port number.

Under Device Manager / Ports, right-click the Tait Programming Cable and select Properties. Then in the Port Settings tab select Advanced.

 If the Tait Programming Cable and the assigned port number do not appear in your Tait programming application, restart your computer.

## More Information

Refer to your radio provider for more information about this product.