

COPY

FEDERAL COMMUNICATIONS
COMMISSION
WASHINGTON, D.C. 20554

COPY

GRANT OF EQUIPMENT
AUTHORIZATION
Certification

Kenwood USA Corporation
5000 Research Ct Suite 700
Suwanee, GA 30024
United States

Date of Grant: 11/20/2001

Application Dated: 09/25/2001

Attention: Angelina Seay , Regulatory Support Engineer

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: ALH32253110
Name of Grantee: Kenwood USA Corporation
Equipment Class: Licensed Non-Broadcast Transmitter Held to Face
Notes: VHF Handheld Transceiver
Modular Type: Does not apply

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22, 74, 90.210	136.0 - 174.0	1.0	2.5 PM	11K0F3E
	22, 74, 90	136.0 - 174.0	1.0	2.5 PM	16K0F3E
BE	22, 74, 90.210	136.0 - 174.0	5.08	2.5 PM	11K0F3E
BE	22, 74, 90	136.0 - 174.0	5.08	2.5 PM	16K0F3E

Power output listed is at the antenna terminal on the device. This transmitter has been tested for SAR compliance in Push-to-Talk and body-worn operating configurations with a specific antenna, and only satisfies SAR limit for Occupational/Controlled RF Exposure Environment. Device must operate at a duty factor not exceeding 50% and SAR compliance for body-worn operating configurations is limited to the specific belt-clip and holster tested for this filing. This device must be restricted to work related operations in an Occupational/Controlled RF exposure Environment. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with Occupational /Controlled SAR limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements and users must be provided with the training information. The highest reported SAR values at 50% duty factor are - Head: 0.83 W/kg; Body-worn: 2.37 W/kg.

BE: The output power is continuously variable from the value listed in this entry to 15%-20% of the value listed.

Mail To:
Morton Flom, P. Eng., President
M. Flom Associates, Inc.
3356 N. San Marcos Pl., Suite 107
Chandler, AZ 85225-7176

EA102544