

COPY

FEDERAL COMMUNICATIONS  
COMMISSION  
WASHINGTON, D.C. 20554

COPY

GRANT OF EQUIPMENT  
AUTHORIZATION  
Certification

Kenwood USA Corporation  
5000 Research Ct Suite 700  
Suwanee, GA 30024  
United States

Date of Grant: 10/30/2001

Application Dated: 09/10/2001

Attention: Angelina Seay , Regulatory Support Engineer

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY  
for the equipment identified hereon for use under the Commission's Rules and Regulations listed  
below.

FCC IDENTIFIER: ALH32263110  
Name of Grantee: Kenwood USA Corporation  
Equipment Class: Licensed Non-Broadcast Transmitter Held to Face  
Notes: 22, 74, 90, 95  
Modular Type: Does not apply

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22, 74, 95, 90.210	450.0 - 490.0	1.0	2.5 PM	11K0F3E
BF	22, 74, 95, 90.210	450.0 - 490.0	4.5	2.5 PM	11K0F3E
	22, 74, 90, 95	450.0 - 490.0	1.0	2.5 PM	16K0F3E
BF	22, 74, 90, 95	450.0 - 490.0	4.5	2.5 PM	16K0F3E

Power output listed is at the antenna terminal on the device. This transmitter has been tested for SAR compliance in Push-to-Talk and body-worn operating configurations with a specific antenna, and only satisfies SAR limit for Occupational/Controlled RF Exposure Environment. Device must operate at a duty factor not exceeding 50% and SAR compliance for body-worn operating configurations is limited to the specific belt-clip tested for this filing. This device must be restricted to work related operations in an Occupational/Controlled RF exposure Environment. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with Occupational /Controlled SAR limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements and users must be provided with the training information. The highest reported SAR values at 50% duty factor are - Head: 4.24 W/kg; Body-worn: 4.67 W/kg.

BF: The output power is continuously variable from the value listed in this entry to 20%-25% of the value listed.

Mail To:  
Morton Flom, P. Eng., President  
M. Flom Associates, Inc.  
3356 N. San Marcos Pl., Suite 107  
Chandler, AZ 85225-7176

EA102342