

COPY

**FEDERAL COMMUNICATIONS
COMMISSION
WASHINGTON, D.C. 20554**

COPY

**GRANT OF EQUIPMENT
AUTHORIZATION**

Certification

**Kenwood USA Corporation
3970 Johns Creek Court Suite 100
Suwanee, GA 30024
United States**

Date of Grant: 08/21/2003

Application Dated: 05/29/2003

Attention: Don Wingo , Senior Product Planning & Development Manager

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: ALH36413110
Name of Grantee: Kenwood USA Corporation
Equipment Class: Licensed Non-Broadcast Transmitter Held to Face
Notes: VHF FM Transceiver
Modular Type: Does not apply

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
BF	22, 74, 80, 90	136.0 - 174.0	1.0	2.5 PM	16K0F3E
BF	22, 74, 80, 90.210	136.0 - 174.0	1.0	2.5 PM	11K0F3E
BF	22, 74, 80, 90	136.0 - 174.0	5.0	2.5 PM	16K0F3E
BF	22, 74, 80, 90.210	136.0 - 174.0	5.0	2.5 PM	11K0F3E

Output is at the antenna terminal of the device and must not exceed that tested for SAR compliance. This transmitter may operate with the antennas tested for this filing in Push-to-Talk and body-worn configurations. Body-worn SAR compliance is limited to the specific belt-clip and speaker/microphone configurations tested for this filing. This device must be restricted to work related operations in an Occupational/Controlled RF exposure Environment. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with Occupational /Controlled SAR limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements and users must be provided with the training information. The highest reported SAR values are - Head: 0.94 W/kg; Body-worn: 1.00 W/kg at 50% duty cycle.

BF: The output power is continuously variable from the value listed in this entry to 20%-25% of the value listed.

Mail To:
Morton Flom, P. Eng., President
M. Flom Associates, Inc.
3356 N. San Marcos Pl., Suite 107
Chandler, AZ 85225-7176

EA390786