

**TCB****GRANT OF EQUIPMENT  
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the  
Federal Communications Commission****By:****Timco Engineering, Inc.  
849 NW State Road 45  
Newberry, FL 32669****Date of Grant: 12/07/2004****Application Dated: 12/07/2004****Kenwood USA Corporation  
5000 Research Ct  
Suite 700  
Suwanee, GA 30024****Attention: Angelina Seay , Regulatory Support Engineer****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE,  
and is VALID ONLY for the equipment identified hereon for use under the  
Commission's Rules and Regulations listed below.

**FCC IDENTIFIER: ALH37693110****Name of Grantee: Kenwood USA Corporation****Equipment Class: Licensed Non-Broadcast Transmitter Held to  
Face****Notes: UHF FM HANDHELD TRANSCEIVER**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22, 74, 90, 95A, 90.210	450.0 - 490.0	1.0	2.5 PM	16K0F3E
BF	22, 74, 90, 95A, 90.210	450.0 - 490.0	4.0	2.5 PM	16K0F3E
	22, 74, 90, 95A, 90.210	450.0 - 490.0	1.0	2.5 PM	11K0F3E
BF	22, 74, 90, 95A, 90.210	450.0 - 490.0	4.0	2.5 PM	11K0F3E

Power listed is conducted. This device must be restricted to work related operations in an Occupational/Controlled RF exposure Environment, not exceeding a maximum transmitting duty factor of 50%. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with the Occupational/Controlled MPE limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements. SAR compliance for body-worn operating configurations is limited to the specific belt-clip tested for this filing. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. The highest reported SAR levels are: Head: 4.33 W/kg for 50% Duty Cycle; Body: 6.07 W/kg for 50% Duty Cycle.

BF: The output power is continuously variable from the value listed in this entry to 20%-25% of the value listed.