

TCB**GRANT OF EQUIPMENT
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the
Federal Communications Commission****By:****HCT America LLC
1726 Ringwood Avenue
San Jose, CA 95131****Date of Grant: 02/24/2018****Application Dated: 02/24/2018****Kenwood USA Corporation
5000 Research Ct
Suite 700
Suwanee, GA 30024****Attention: Angelina Seay , Regulatory Support
Engineer****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is
VALID ONLY for the equipment identified hereon for use under the Commission's
Rules and Regulations listed below.

FCC IDENTIFIER: ALH443801**Name of Grantee:** Kenwood USA Corporation**Equipment Class:** **Licensed Non-Broadcast Transmitter Held
to Face****Notes:** **UHF Digital Transceiver**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
BC EF	22, 74, 90	406.1 - 470.0	5.0	1.0 PM	11K0F3E
BC EF ES	22, 74, 90	406.1 - 470.0	5.0	1.0 PM	8K30F1E
BC EF ES	22, 74, 90	406.1 - 470.0	5.0	1.0 PM	8K30F1D
BC EF ES	22, 74, 90	406.1 - 470.0	5.0	1.0 PM	8K30F7W
BC EF ES	22, 74, 90	406.1 - 470.0	5.0	1.0 PM	4K00F1E
BC EF ES	22, 74, 90	406.1 - 470.0	5.0	1.0 PM	4K00F1D
BC EF ES	22, 74, 90	406.1 - 470.0	5.0	1.0 PM	4K00F7W
BC EF ES	22, 74, 90	406.1 - 470.0	5.0	1.0 PM	4K00F2D

Class II Permissive Change. Output Power Continuously Variable from to 0.25W to 5W.
 SAR for body worn operation has been tested and meets the FCC RF exposure guidelines
 when used with the listed accessory designated for this product. This device must be
 restricted to work related operations in an Occupational/Controlled RF exposure
 Environment. End users must be informed of the body worn requirements for satisfying RF
 Exposure compliance. This device may operate only with antennas as described in this
 filing and must transmit with a source-based time-averaging duty factor not exceeding 50%.
 This device must be restricted to work related operations in an Occupational/Controlled RF
 exposure Environment. SAR was evaluated for body worn and held-to-face operating
 modes. The highest reported head and body-worn accessory SAR values at 50% duty
 factor across all filings under this FCC ID are 3.43 W/kg and 4.19 W/kg, respectively.

BC: The output power is continuously variable from the value listed in this entry to 5%-10% of the value listed.

EF: This device may contain functions that are not operational in U.S Territories except as noted in the filing. This grant has extended frequencies as noted in the filing and Section 2.927(b) applies to this authorization.

ES: This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth.