

**197- AND 198-TYPE SWITCHES,  
BANKS, COMMUTATORS, WIPERS, JACK SPRINGS,  
AND SWITCH OPERATION  
REQUIREMENTS AND ADJUSTING PROCEDURES**

**1. GENERAL**

**1.01** This addendum supplements Section 030-705-704, Issue 9. Place this pink sheet ahead of Page 1 of this section.

**1.02** This addendum is issued for the following reasons:

1. To change part No. of a tool
2. To add a note to 2.08(b).

This addendum does not affect the Equipment Test List.

**2. CHANGES TO SECTION**

**2.001** On Page 3, after 2.08(b), add the following note.

*Note:* This requirement does not apply when a selector switch ED30976-02 is wired as four wire, but is being used as a 3 wire ckt. Refer to SD30976-01 Sheet 3, Test Note 2.

**2.002** On Page 7, under List of Tools and Gauges, change 555A 3/16-inch hex single-end socket wrench to 476A 3/16-inch hex offset socket wrench.

**2.003** On Page 8, 3.02(1), change the 555A wrench to 476A wrench.

**2.004** On Page 9, 3.09(4), change the 555A wrench to 476A wrench.

**2.005** On Page 10, 3.11(a) and (b), change the 555A wrench to 476A wrench.

**2.006** On Page 11, 3.18(1) and (2)(a), change the 555A wrench to 476A wrench.

**NOTICE**

Not for use or disclosure outside the  
Bell System except under written agreement.