

PATCHING CORD ASSEMBLIES
ONE-CONDUCTOR CORDS
1P1A THROUGH 1P12A
DESCRIPTION

1. GENERAL

1.01 This section lists and illustrates the 1P1A through 1P12A one-conductor cords.

1.02 This section is reissued to rate the 1P1A and 1P4A cords Mfr Disc. Revision arrows have been used to emphasize the more significant changes. This change does not affect the Equipment Test List.

1.03 For general information on these cords, refer to Section 032-311-100.

2. DESCRIPTION OF CORDS

◆**1P1A—MFR DISC.**◆

No replacement.

1P2A

One P1B cord, 3 feet long, equipped with two 347C plugs.

1P3A

One P1B cord, 3 feet long, equipped with two 347D plugs.

1P3B—MFR DISC.

Replaced by the 1P4C cord.

◆**1P4A—MFR DISC.**◆

No replacement.

1P4B

One P1B cord, 4 feet long, equipped with two 347D plugs.

1P4C

Replaces the 1P3B cord.

One P1B cord, 6 feet long, equipped with two 347D plugs.



1P5A—MFR DISC.

No replacement.

1P6A

One P1D cord, 6 feet long, equipped with two 310 plugs.



Res 0.006 Ω /ft

NOTICE

Not for use or disclosure outside the
Bell System except under written agreement

SECTION 032-311-102

1P7A

One P1E cord, 3 feet long, equipped with two 309 plugs.



Res 0.06 Ω /ft

1P8A—MFR DISC.

No replacement.

1P9A

One P1H cord, 1 foot long, equipped with two 241A plugs.



Res 0.006 Ω /ft

1P10A—MFR DISC.

No replacement.

1P11A

One P1L cord, 6 feet long, equipped with two 347D plugs.



Res 0.006 Ω /ft

1P12A

1 foot long



One P1Y cord, 1 foot long equipped with two 624B tools. The cord initially was intended for use with No. 5 crossbar line link circuit connected with the traffic usage recorder.